

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 28 T. S. R 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

145

C O N T - - - (1/4 Cor. Secs. 14,23)

Doug. Co. Surveyor
Office - R. Smith
S. Flaue Sept. 6,
C.S. 62/55

New BO's- A boat spike stamped BO 1 set through a bearing tree tag at the center of a 48" dia. 18" high D. fir stump bears N.82½°E., 19.6 ft. distant.
88 A boat spike stamped BO 2 set through a bearing tree tag at the center of a 24" dia. 1 ft. high D. fir stump bears N.32½°W., 62.9 ft. distant.
Monument is in a clearcut and approx. 400 ft. west from a line crossing tag on a G. fir at the east edge of USFS Rd. 780.

9/16/88

Angle Point on South line Section 35. (T. 27-2)
North 1/4 Corner Section 2) (Approx. 300 ft. East of 146

Found - A brass cap on iron pipe marked as per Ren. #52
A 6 ft. high, 32" hemlock stump bears N.67°E., 13.9 ft. - visible scribing.
A 9" yew, dead and broken off 4 ft. above ground bears N.17°W., 10.6 ft. - visible scribing.
A 54" D. fir, 4 ft. high stump, bears N.1°W., 13.2 ft. - visible scribing.
New BTs - 8" hemlock, S.20°W., 11.0 ft. scribed "AP BT".
18" double yew, S.70°W., 39.1 ft. scribed "AP BT"
Set ½" brass washers in BT faces marked "LS 1035".

10/20/88

147

Section Corner for Sections 34 and 35 only, T.27-2

Found - An alum. cap on a 3/4" iron rod mkd. as per Ren. #125
A 16" fir stump bears N.50°W., 22.7 ft.
A 15" cedar snag bears S.76°E., 6.6 ft.
A 48" cedar stump bears S.62°E., 25.6 ft. visible scribing
A 12" cedar bears N.41°E., 58.1 ft. visible scribing.
A 30" cedar stump bears N.45°E., 7.3 ft.
An 11" yew bears S.76°E., 207.0 ft. visible scribing.
An 11" hemlock snag bears N.12°W., 184.0 ft. visible scribing.
New BT - A 7" yew bears N.3°E., 39.2 ft. scribed "T27S R2W S35 BT"
A ½" brass washer was set in BT face marked "LS 1035".

10/20/88

148

1/4 Corner South boundary Section 34 of T.27-2

Found - A 2½" iron pipe with brass cap extended 8" above ground marked as per Ren. #126.
A 12" cedar snag bears N.84°E., 19.9 ft. visible scribing.
An 18" fir, dead and down, bears S.30°W., 50.7 ft. visible scribe.
Brass washers marked "RLS 1654 are set in BT faces.
New BTs - A 10" yew bears S.85°E., 81.7 ft. scribed "1/4 S34 BT".
A 6" yew bears S.40°W., 136.0 ft. scribed "1/4 S34 BT".
Brass washer marked "LS 1035" and set in BT faces.

10/14/88

1/4 Corner for Section 13 only of T.28-3

Found - A 2½" I.P. with brass cap extending 8" above ground mkd. RLS 1005 T28S R3W ¼S13 | T28S R2W 1980. (Rec. per Ren. #115 and M83-19 says cap mkd. RLS 1654)
A 7" hemlock bears N.40°W., 10.1 ft. - visible scribing.
A 9" madrona snag bears S.85°E., 7.2 ft. - visible scribing.
New BT - A 5" cedar bears N.74°E., 11.3 ft. scribed "X BT". A ½" brass washer was set in BT face marked "LS 1035".

149

Bearing tree and monument signs were placed on all BTs without them and a 6" red band and face blazes were painted on all bearing trees.

12/12/88

150

Closing Corner for Sections 7 and 18.

Found - A 1" I.P. with alum. cap extending 6" above stone mound. Ren. #27
A 26" stump bears N.32°W., 26.1 ft. - visible scribing.
A 40" D. fir stump bears S.60°E., 29.0 ft. - healed blaze.
A 24" stump bears N.82°E., (Rec. N.82°W.,) 56.1 ft. Ren. #114
A 12" maple bears N.49°E., 51.8 ft. - visible scribing.
New BT - A 10" cedar bears S.57°E., 19.5 ft. scribed "T28S R2W S18 BT". A ½" brass washer was set in BT face marked "RLS 1035".

Bearing tree and monument signs were placed on all BTs without them and a 6" red band and face blazes were painted on all bearing trees.

12/13/88

Gerald V. Nygren
L.S. #1035
October, 1988
C.S. 63/69

Gerald V. Nygren
L.S. 1035
For: USFS
December, 1988
C.S. 63/92