

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 28 T. S. R 2 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97401

Gerald Nygren
For: U.S.F.S.
Dec. 1988
(Filed 7/89)
C.S. 63/85

151

Center 1/4 Corner for Section 7
CORNER REPORT ONLY

Found - 1" iron pipe with 2½" alum. cap extended 10" above ground
and marked "T28S R2W C1/4 S7 RE 4287." Ren. No. 23
A 30" fir stump, S.46°E., 23.2 ft. (vis. scribe)
A 30" fir stump, N.52°W., 27.1 ft. (vis. scribe)
A 7" live Oak, N.4°W., (Rec. S.4°E.) 13.4 ft. (healed blaze.)
A 13" D. fir, N.80°E., 20.0 ft. (healed blaze.) Ren. #110
- - - - - 12/88

Do. Co. Surveyors Office
Randall Smith & Stephen Flause
C.S. 64/64-6
10/23/95

¼ cor. of secs. 5 & 6 see renewal #120
Mon. Fd. - 2½" dia. Brass cap on an iron pipe, 6" below with 2½' dia. mound
of stone on top. 152
Bt's Fd. - 14" now 16" dia. D.Fir, with partially haled burnt double blaze,
illegible scribing visible, bears S.42½°W., 25.2'
10" now 10" dia. 3' high Madrone stump, with a partially haled
double blaze scribing visible "¼ S5 BT" and 1½" dia. brass
washer mkd. "RLS 1005" attached to lower blaze, bears
S.65½°E., 26'.
New BT's - 10" dia. D.Fir, double blazed and scribed "¼ S6 CS BT", bears
N.15½°W., 8.5'.
10" dia. D.Fir, double blazed and scribed "¼ S5 CS BT", bears
N.85½°E., 7.9'.
10" dia. D.Fir, double blazed and scribed "¼ S5 CS BT", bears
S.15°E., 9.4'.

Do. Co. Surveyors Office
Randall Smith & Stephen Flause
C.S. 64/64 -8
11/20/95

Sec. Cor. of 9, 10, 15, & 16 Renewal # 37
Mon. Fd. - 2½" dia. alum cap on a 1" o.d. iron protrudes 12" above a 3'
dia. mound of stone.
BT's Fd. - All Orig Bt's now gone
22" now 29" dia. D.Fir with a fully healed double blaze, bears
N.42°E., 120.5'.
17" now 24" Dia. 2½' high solid D.Fir stump, with a fully healed
blaze, bears N.21½°W., 150.5'.
23" now 24" dia. D.Fir, with a fully healed double blaze, bears
S.81½°E., 154.7'.
18" now 13" dia. D.Fir, with a fully healed double blaze, bears
S.39½°W., 135'.
Mon. Set- Alum cap on a unflanged 36" long iron pipe is driven down an
stabilized with a 3½ dia. by 2' high mound of stone protrudes
7" above mound of stone.
BT's Fd. - 4" dia. D.Fir double blaze and scribed "X BT", bears S.70°E.,
3.3'.
corner lies approx 60' east of a gravel road on the easterly edge of a rock
quarry approx 25' higher than road. 153

Kristian DeGroot, PLS
#1941
June 1998
C.S. File 65/20-32 & 33

1/4 Cor. Secs. 6 & 7 Ren #122 154
Fd. - 1" iron pipe (O.D.) firmly set, projecting 10" above the ground with a 2½" alum. cap stamped,
properly marked, from which
21" Cedar bears N.56°30'E., 33.5 ft. with a healed blaze. (Rec. N56°E)
24" Cedar bears S.6°E., 95.3 ft. w/scribe marks "1/4 S7 BT" visible. (Rec. 98.0 ft.)
New Accessories - I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND
SURVEY MONUMENT" signs to all bearing trees. (CS 65/20-32)

C 1/4 Sec. 6 Ren # 119 155
Fd. - 2½" (O.D.) IP, firmly set, flush with the ground with a 2½" brass cap properly stamped.
19" Hemlock bears N.7°W., 53.6' with healed double blaze.
33" D.Fir bears S.75°E., 79.3' with a healed double blaze, (rec. S.70°E., 78.8')
1" (O.D.) IP, firmly set, projecting 30" above the ground with a 2½" alum. cap stamped "T28S R2W C
S6 RE 4287 1968" bears N.8°30'W., 1.84', (Rec. N.3°44'53"W., 1.93')
53" D.Fir bears N.32°W., 36.0', with healed blaze. (Rec. N.32°W., 37.2')
39" D.Fir bears S.82°W., 41.8', with healed blaze (Rec. S.81°W., 42.5')
New Accessories - I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY
MONUMENT" signs to all bearing trees. (CS 65/20-34)