

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 28 S. T. S. R 2 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

New BT's: 7" Hemlock S.21°E. 10.9 ft. mkd. T28S R2W S32 CS BT.
12" D.Fir N. 75°E. 22.5 ft. mkd. T28S R2W S29 CS BT.
8" D.Fir N.25°W. 17.0 ft. mkd. T28S R2W S30 CS BT.
12" D.Fir S.24°W. 15.1 ft. mkd. T28S R2W S31 CS BT.

39

Section Corner to Sections 19 - 20 - 29 - 30

Found - 6" Chinq., now stob, N.67°E. 23.1 ft., scribe visible.
8", now 19" D.Fir, S.43°E. 15.2 ft., shows good scar.
12", now 26" D.Fir S.28°W. 20.5 ft., shows good scar.
8" Pine, now dead, N.75°W. 15.8 ft., scribe visible
Stone, firmly set, at corner point.

Set - Brass Cap at Cor.Mkd: County Surveyor's Office
1968

T 28 S	R 2 W
S 19	S 20
S 30	S 29

New BT's: 29" D.Fir N.46½°W. 18.4 ft. mkd. T28S R2W S19 CS BT.
8" Hemlock N.36°E. 23.8 ft. mkd. T28S R2W S20 CS BT.

Note - This corner lies approx. 25.0 ft. N. of spring branch.

40

Section Corner to Sections 5 - 6 - 7 - 8.

Found - Orig. 8", now 16" Live Oak, N.65°E. 58.7 ft. (slope) (Rec. N.60°E.)
Alive, shows good scar.

Orig. 8", now 15" Laurel, alive, S.60°E. 56.8 ft., burnt out,
no scribe found, record bearing S.70°E.

Orig. 10", now 17" Laurel, alive, S.20°W. 43.6 ft., Open & find
scribe and reverse.

Orig. 7", now 15" Laurel, N.45°W. (Rec. N.40°W.) 46.2 ft., alive,
opened by D.Wright, U.S. Plywood, scribe visible in poor cond.

Set - Brass Cap at Cor.Mkd: County Surveyor's Office
1968

T 28 S	R 2 W
S 6	S 5
S 7	S 8

New BT's: 6" Live Oak S.33°E. 10.8 ft. mkd. T28S R2W S8 CS BT.
7" Live Oak N.67°W. 45.8 ft. mkd. T28S R2W S6 CS BT.
16" Live Oak N.66°E. 58.7 ft. mkd. T28S R2W S5 CS BT. (Orig. BT)
18" Laurel S.32°W. 35.0 ft. mkd. T28S R2W S7 CS BT.

Note - This corner lies on steep S.W. slope.

April 24, 1968

41

Section Corner to Sections 4 - 5 - 8 - 9.

Found - Original Corner Stone 14"x12"x8" in place & mkd. with
5 notches on South & 4 notches on East sides about
3" under duff.

Orig. 6" Alder, now only badly decayed remains, N.41°W. 25.1 ft. (Rec. N.51W)
find fragmentary reverse scribe.

Orig. 6", now 18" Hemlock S.40°W. (Rec. S.37°W) 40.3 ft., alive, shows
good scar. We do not open. Rescribe "T28S R2W S8 CS BT".

Orig. 36", now 44" Fir, alive, N.66°E. 41.9 ft. (Rec. N.19E.13.9')
We open & find, "SR2W.S4 BT" scribe. All face measurements.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office
1968

T 28 S	R 2 W
S 5	S 4
S 8	S 9

New BT's: 10" Hemlock N. 54° E. 15.7 ft. mkd. T28S R2W S4 CS BT.
9" Hemlock N. 17° W. 32.5 ft. mkd. T28S R2W S5 CS BT.
6" Hemlock S. 23° E. 11.6 ft. mkd. T28S R2W S9 CS BT.

Note - Creek calls S. and E. fit good.

May 7, 1968

¼ Corner to Sections 4 and 9.

42

Found - Orig. 8", now 23" Fir, S.45°W. 18.5 ft., alive, shows good
scar, we do not open.

Orig. 4", now 18" Fir, N.53°E. (Rec. N.43E) 11.9 ft. Open &
find "B" scribe & reverse.

Both BT's. scars face the location at which we Set:

Set - Brass Cap at Cor.Mkd: County Surveyor's Office
1968

T 28 S	R 2 W
S 4	
S 9	

New BT's: 8" D.Fir N.51°W. 8.4 ft. mkd: "¼ S 4 CS BT".
Orig. 23" D.Fir S.45°W. 18.5 ft. mkd: "¼ S9 CS BT" above old scar.

Note - This corner lies on nearly level flat approx. 5 ch. E. of
Wolf Camp & 60 ft. S. of Sta. 7+87 on recently staked "P" Line.

May 7, 1968

John M. Powell
Frank Jones &
W. Penley
Feb/ 8, 1968
C. S. File No. 54/26

Vernon "Ray" Tracy
Jack Heritage & V. Perron
April & May, 1968
C. S. File No. 54/26