

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO. EUGENE, ORE. 21881

43

$\frac{1}{4}$ Corner common to Sections 30 & 31, T.28S., R.2W.
 Orig. Corner set by U.S. Gov't. survey in 1909 & described as follows:
 Set Lava Stone, 8x8x12 in., 8 in. in the ground for $\frac{1}{4}$ Sec. Cor.,
 marked " $\frac{1}{4}$ " on N. face, from which:
 A fir, 5 inches diam., bears S. 6° E., 17 lks. dist. mkd: " $\frac{1}{4}$ S 31 BT".
 A laurel, 5 in. diam., bears N.50°E. 30 lks. dist., mkd: " $\frac{1}{4}$ S 30 BT".
 I found a 8x8x12" Stone, no " $\frac{1}{4}$ " visible, from which stone a:
 10" diam. Doug. Fir, an orig. BT. with scribes "S 31 BT" visible,
 bears S. 6° E. 11.2 feet.
 19" diam. Madrone, Orig. Laurel BT., face badly rotted with portions
 of scribes " $\frac{1}{4}$ " visible, bears N.64°E. (Rec. N.50°E) distance of 19.8 feet.
 At the Orig. Corner Stone I placed a Brass Cap mkd: "T28S, R2W,
 $\frac{1}{4}$ S30 & S31, 1968 ORE 4906, and from which Brass Cap a:
 10" diam. Madrone, Orig. Laurel BT., face badly rotted with portions
 of scribes " $\frac{1}{4}$ " visible, bears N.64°E. a dist. of 19.8 feet.
 10" diam. D. Fir, an Orig. BT. with scribes "S 31 BT" visible,
 bears S. 6° E., 11.2 feet.
 26" Sugar Pine, I scribed " $\frac{1}{4}$ S S30 T28S R2W BT", bears N. 88° W.,
 a distance of 10.4 feet.
 This corner is approximately 7 chains East of a logging road.

44

$\frac{1}{4}$ Corner Common to Sections 19 and 30.
 Orig. Cor. set by U.S. Gov't. survey in 1909, & described as follows:
 Set - Yew Post, 3 ft. long, 4" square, 24" in the ground for $\frac{1}{4}$ section
 corner, mkd: " $\frac{1}{4}$ S19" on N. & "30" on S. face, from which:
 A hemlock, 8" diam., bears S.78°E., 8 lks. dist., mkd: " $\frac{1}{4}$ S30 BT".
 A hemlock, 5" diam., bears N. 5° E., 17 lks. dist., mkd: " $\frac{1}{4}$ S19 BT".
 I found a badly decayed 4" square x 36" long Yew Post with scribe "4" and
 portions of other scribes visible; from which post a:
 7" hemlock, Orig. BT., badly chopped, no scribes visible, #142
 bears N. 5° E., 11.2 ft.
 8" Hemlock, Orig. BT., bearing S.78°E. 5.3 feet, now missing.
 The corner is at junction of very old blazed line running E-W and one
 running South. Original line calls of ravine at 3 chains E. and ridge
 at 4 chains E. are good.
 At the location of the Orig. Corner Post, I placed a Brass Cap
 which I marked "T28S, R2W, $\frac{1}{4}$ S, S19 & S30, 1968, ORE 4906", and from
 which Brass Cap a:
 7" hemlock, Orig. BT., badly chopped, no scribes visible bears
 N.5°E., 11.2 feet.
 44" D. Fir, I scribed " $\frac{1}{4}$ S S19 T28S R2W BT", bears N. 7° W. 18.0 feet.
 10" Yew BT, I scribed " $\frac{1}{4}$ S S30 T28S R2W BT", bears S.34°W. 24.5 feet.

45

$\frac{1}{4}$ Corner common to Sections 30 and 29.
 Orig. Corner set by U.S. Gov't. survey in 1909 and described as follows:
 Set Fir Stake, 3 ft. long, 4" square, 24" in the ground, mkd: " $\frac{1}{4}$ S 30"
 on W. and "29" on E. face, from which:
 A Pine, 8" diam., bears S.55°W. 14 lks. mkd: " $\frac{1}{4}$ S 30 BT".
 A Pine, 7" diam., bears N.71°E. 45 lks. mkd: " $\frac{1}{4}$ S 29 BT".
 Orig. Corner Stake was missing, but from the spot it occupied a:
 10" Pine, Orig. BT with scribes visible, no blown down and rotting,
 bears S.55°W. a dist. of 9.2 feet.
 16" White Pine, Orig. BT. with scribes visible, bears N.71°E. a distance
 of 29.7 feet.
 I Set a Brass Cap mkd: "T28S R2W $\frac{1}{4}$ S30 & S29, 1968, ORE 4906", at
 position of orig. corner stake from which Brass Cap a:
 10" Pine, Orig. BT. with scribes visible, no blown down & rotting,
 bears S. 55° W. a distance of 9.2 feet.
 16" White Pine, Orig. BT. with scribes visible, bears N. 71° E.
 a distance of 29.7 feet.
 10" D. Fir, I scribed " $\frac{1}{4}$ S S30 T28S R2W BT", bears S. 26° W.,
 a distance of 22.0 feet.

BRUCE A. SHANER
 UMPQUA NAT'L FOREST
 May 13, 1968
 C. S. File No. 55/74

RECORDED - CORNER NO. #142