

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

52

Angle Point on South Line of Section 35, T27-2W.
This corner lies on steep, east slope about 310 ft. E. of N $\frac{1}{2}$ Corner,
Section 2, T28-2W, see corner above.
Found - Orig. 24", now 28" Hemlock, alive, N. 67° E. 13.9 ft., scribe # 146
visible on unhealed blaze. Rescribe: "A P CS BT".
Orig. 7", now 9" Yew, dead & broken off 4' above ground,
N. 17° W. 10.6 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S T28S R2W A P
Office, 1968
New BT: 50" D. Fir N. 1° W. 13.2 ft. mkd: "A P CS BT". FOUND O.K. 6/28/72 V.R.T.

53

Standard Corner to Sections 35 and 36, T27-2W.
Found - Orig. BT's. by 40" Fir Snag, 40' high, N. 58° E. 36.3 ft., scribe visible
10", now 16" Fir, alive, N. 84° E. 40.9 ft., shows scar.
Rescribe: "T27S R2W S35 SC CS BT".
7", now 22" Fir, alive, N. 1° W. 44.2 ft., scribe visible on open blz.
Rescribe: "T27S R2W S36 SC CS BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S T28S R2W S 35 | S 36
Office, 1968
This corner lies on E. side of Red Butte Lookout Road.

54

Angle Point btwn. Sec. 34, T27-2W and Sec. 2, T28-2W.
Found - Unrecorded U.S. Ply. Alum. Cap mkd: "A.P." set from Orig. BT's,
both out of ground, scribing visible on N.W. Orig. BT.
No trace of new bearing trees.
Set - 6 ft. Steel Fence Post alongside Alum. Cap.
New BT's: 6" Yew N. 14° E. 18.0 ft. mkd: "A.P. CS BT".
12" W. Fir S. 81° E. 53.4 ft. mkd: "A.P. CS BT". #124
This corner lies 120 ft. west of C.C. Secs. 34 & 35, T27-2W in
flat logged-off unit. (Rec. Dist. btwn. corners 112.3 ft.)

55

Closing Corner to Sections 5 and 6, T28-2W. Rec. 15 S.E. TRACY'S FIELD NOTES READ S.W.
Found - Brass Cap at Corner & 2 BT's., See Ren. #18.
42", now 43" D. Fir, S. 45° W. 7.2 ft., shows bark scribing.
48", now 49" D. Fir, S. 34° W. 55.5 ft., shows bark scribing. #131
Remarked Brass Cap: County Surveyor's T27S R2W C.C. S 6 | S 5
Office, 1968
Rescribed: 49" D. Fir S. 34° W. 55.5 ft. mkd: T28SR2WS5 CC CS BT.
New BT: 6" Madrone S. 1° W. 44.0 ft. mkd: T28S R2WS6 CC CS BT.
This corner lies N. 85° E. 7.0 ft. of A.P. of Sec. 31, T27 & S6, T28-2 and
west 226.9 ft. of corner Sections 31 & 32, T27-2W., see below.

56

Section Corner to Sections 31 and 32, T27-2W.
Found - $\frac{1}{2}$ " I. Pipe & Good BT's., see Ren. #17.
10", now 12" D. Fir, N. 12° W. 14.7 ft., shows scribing.
6", now 7" Madrone, N. 78° E. 21.4 ft., shows scribing. #132
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S T28S R2W S 31 | S 32
Office, 1968
Note - This corner lies on top of rocky ridge sloping south and
east 226.9 ft. of C. C. Sections 6 and 5, T28-2W., see above.

11/21/68
57

$\frac{1}{4}$ Corner Section 6 only, T28-2W. (NOVA)
Set - 2 $\frac{1}{2}$ " diam. Aluminum Cap mkd: USPC Prop. Cor. "T28SR2WS6 R.E. 4287"
12" Cedar S. 30° E. 11.9 mkd: "S6 BT R.E. 4287".
18" Cedar S. 70° W. 34.3 ft. mkd: "S6 BT R.E. 4287".

58

$\frac{1}{4}$ Corner to Section 31 only, T27-2W.
Set - 2 $\frac{1}{2}$ " diam. Aluminum Cap mkd: "USPC Prop. Co. R.E. 4287".
 $\frac{1}{4}$ S31 only, T27S R2W."
6" D. Fir N. 39° E. 73.5 ft. " $\frac{1}{4}$ S31" BT. R.E. 4287".
40" Cedar Stump, N. 65° W. 45.2 ft. " $\frac{1}{4}$ S31, B.T. R.E. 4287".

Vernon "Ray" Tracy
Frank Jones & V. Perron
November & December, 1968 C.S. File No. 54/40

Thomas E. Shrum, Jr.
For U. S. Plywood Corp.
December, 1968
Map File M 37 - 17