

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 2 W. R.W.W.M.

ROBE-CHAPMAN CO., EUGENE, ORE. 21881

Vernon "Ray" Tracy
J. G. Heritage & V. Permon
6-12-69 C.S. File No. 54/40

Sections 32 & 33 (Angle Point) T. 27 R 2W 67
Found - Unrecorded 3/4" I.P. set from OBT's as follows. #136
Orig. 16" now 28" Fir N. 45°E 5.9 Ft. Alive - old bark blaze. No
scribe fd.
Orig. 16" now 30" Fir No 25°W 3.8 Ft. alive - chopped open &
Burned possible scribe mks.
Orig. 16" now 28" Fir S. 30°W. 64.7 Ft. alive - old bark blaze
fragmentary scribe Mk. Fd.
Also - Find O.B.T. unrecorded 32" Fir S. 27°E. 11.4 ft. Alive -
shows scar of Approx. same age as N. W. B. T.
DO NOT SET BRASS CAP - Mk. new B.T.S.
1" D. Fir N. 17°W. 11.2 Ft. Mkd. Ap. CS BT
28" D. Fir N. 45°E. 5.9 Ft. Mkd. AP CS BT
The closing Cor. of Sec."s 4 & 5 of T 28 S R 2W Bears West 96.3 Ft.
6-12-69

Closing Corner Sections 4 & 3 68
Found - O.B.T. as follows:
Orig. 6" Now 10" Yes S. 76°. 23.1 Ft. live - scribe visible
on unhealed blaze.
Orig. 6" Now 8" Cedar (record hemlock) East 38.9 Ft. Record
5.77°E. down & decayed - scribe S 3 BT visible at point for
closing Cor.
Set - 1" I. P. & Brass Cap Mkd:
County Surveyor's T 27 S
Office, 1969 C. C.
T 28 S4 / S3 R 2 W
Mk. new BTS
13" Cedar S. 12°W 10.8 Ft. Mkd. T 28 S R 2 W S 3 CC CS BT
28" W. Fir S. 29°E. 6.4 Ft. Mkd. T 28 S R 2 W S 3 CC CS BT
This Cor. lies on steep East slope. 6-16-69

Angle Point South Boundary Section 33, T27-2W. 69
(See field notes for Standard 1/4 Corner on S. Biry. Section 33)
Found - Orig. 8", now 36" Fir, alive, N. 70°E. 38.3 ft., shows good
scars & fragmentary bark scribe.
Orig. 7", now 32" Fir, alive, N. 30°E. 42.2 ft., shows good scars.
Set - Brass Cap at Angel Point Mkd: County Surveyor's T27S R2W A.P.
Office, 1969 T28S
New BT's: 18" D. Fir S. 66°W. 4.0 ft. mkd: "AP CS BT".
14" D. Fir N. 17° W. 8.7 ft. mkd: "AP CS BT".
6/16/69

South 1/4 Corner Section 33, T28-2W. 70
Found - Stone mkd: "1/4" on N. face as called for & Orig. BT's, as follows:
Orig. 10", now 22" Fir, alive, N. 23°W. 4.0 ft., shows good scar.
No trace of 1917 Orig. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T28S R2W S 33
Office, 1970 T29S
Reset Old Stone alongside.
New BT: 7" W. Fir N. 7° E. 55.1 ft. mkd: "1/4 S33 CS BT".
This corner lies in shallow ravine, course south.
The record distance, 258.1 ft., from this 1/4 corner to sec. cor. of
Sections 3 & 4, T29-2W., appears to be very close. We do not measure
due to logging debris on line.
10/26/70

Section Corner to Sections 4 and 3, T29 - 2 W. 71
Found - Old Corner Stone, in place, as called for & Orig. BT's, as follows:
Orig. 8", now 12" Hemlock S. 17 1/2° W. 9.2 ft., alive, we open & find "T29".
No trace other Orig. BT. due to logging.
Set - Brass Cap at Cor. Mkd: County Surveyor's T28S R2W S 4 | S 3
(Reset stone alongside) Office, 1970 T29S
New BT's: 18" D. Fir S. 28° W. 16.2 ft. mkd: "T29S R2W S4 CS BT".
20" Hemlock S. 72 1/2° W. 36.6 ft. mkd: "T29S R2W S4 CS BT".
There are no trees close in sec. 3 due to clear cut.
This corner lies approx. 300 ft. N. of logging access road, #USFS 2852.
10/26/70

C.
S.
F
I
L
E
N
O.
54/40