

**Douglas County Surveyor's Record of
Government Corners Renewed**

25 28 T. S. 2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

85

Section corner for 12 and 13 only.

Found - Orig. 1923 SW BT, 60" now 64" D. Fir alive and well healed.
The 1923 corner monument and NW BT have been lost due to logging activity.

At the true corner location as determined by the record measurements from the orig. SW bearing tree:

We set - A 1" x 30" I. Pipe 28" in the ground with brass cap attached:

Douglas Co. Surveyor	R	T 28 S	R
1976	2	S 12 S 18	1
	S	S 13	W

From which: The Orig. SW BT bears S.34°W., 34.3 ft.
New BT - A 16" G. Fir bears N.10°E., 34.2 ft. scribed "T28S R1W S18 CS BT" on a double blaze.

9/21/76

Gary Langlitz
Karen Cheney
Doug. Co. Surveyors
Sept. 21, 1976
C.S. 59/24

86

1/4 Corner for Secs. 12 and 13.

Found - 1923 GLO brass cap properly mkd., bent to the west, firmly embedded in the ground.

A 16" now 18" Hemlock, (now a broken stump) bears N.84°E., 24.4 ft. with visible scribing.

A 26" Hemlock, now 28", bears S.68°E., (Rec. S.71°E.) 45.5 ft. with visible scribing.

New BT- A 11" Yewwood bears N.36°W., 153.7 ft. scribed 1/4 S12 CS BT in double blaze.

9/21/76

K. Cheney
Langlitz
V. Cangie,
M. Tompkins
Doug. Co. Surveyors
Sept. 21, 1976
C.S. 59/24

3-77

87

Section corner for 18, 17, 19 and 20.

Found - No monument found.

A 9" D. Fir stump bears S.59°W., 19.8 ft. scribing visible "S19 on partly healed blaze.

A 16" D. Fir stump bears S.19°E., 17.4 ft. Has a healed blaze. (Rec. S17°E., 17.16 ft.).

A 17" D. Fir stump bears N.20°W., 26.61 ft. Has a healed blaze (Rec. N.20°W., 26.4 ft.)

A 42" D. Fir stump bears N.55°E., 34.98 ft. Has a healed blaze.

Set - A 2 1/2" brass cap in a mound of stone mkd: County Surveyors Office T28S R2W S18 S17 S19 S20 1977.

Set a 6 ft. Iron post alongside with a F.S. 54-4 sign attached. Set brass cap by reference to accessories. (O.BT's.)

New BT's- A 8" Chinquapin bears N.78°E., 105.5 ft. scribed "S17 CS BT" on a double blaze.

A 7" D. Fir bears S.53°E., 178.0 ft. scribed "T28S R2W S20 CS BT" on a double blaze.

New accessories:

A 8" Spike in top of 42" Orig. BT stump bears N.55°E., 34.75 ft.

A 8" Spike in top of 17" Orig. BT stump bears N.20°W., 26.6 ft.

A 8" Spike in the top of 17" Fir stump bears N.79°W., 30.3 ft.

A 8" Spike in the base of 16" Orig. BT stump bears S.19 1/2°E., 16.75 ft.

Note - Corner lies approx 100 ft. NW of F.S. Road No. 2817 in a clearcut unit.

4/14/77

Dennis Gaylord, Dep.
Doug. Co. Surveyors
with U.S. Forest Serv
Joel Sherriff, Witness
April 14, 1977
C.S. 59/31

88

Center 1/4 for Sec. 30

Set - 3" Brass cap on 2 1/2" x 30" Galv. I.P.

BT's- 9" Cedar bears N.38°E., 7.5 ft. sc rided "C 1/4 S30 BT".

12" Cedar bears S.58°E., 24.6 ft. scribed "C 1/4 S30 BT"

Note - BT's with brass washers stamped "P.L.S. 835" attached.

4/77

Donald R. Stone
For: U.S. Forest
Service
April 1977
M 63 - 80

89

1/4 Corner Secs. 17 and 20.

Found - No monument.

A 15" Hemlock bears N.25 1/2°E., 25.74 ft. Has healed blaze.

A 48" D. Fir bears S.23°E., 24.46 ft. Has a healed blaze.

Both BT's alive and well. Placed County BT signs on both.

Set - 2 1/2" Brass cap on 1" I.P. stamped County Surveyors Office T28S R2W 1/4 S17 S20 1977. Set by reference to orig. BT's.

Place a 18" x 12" x 10" rock moug around Brass cap.

No new accessories.

7/6/77

Dennis Gaylord U.S.F.
Deputy, Doug. Co.
Surveyors Office
Travis Worthen
July 6, 1977
C.S. 59/38