Douglas County Surveyor's Record of Government Corners Renewed

T 28 T. S. R 2 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

94

South 1/4 Corner for Sec. 36 only.
Found - 1923 GLO brass cap on 3/4" I.P. set solidly in ground. I add "T28S R2W" to brass cap above the 1/4 S36.
A 51" Fir stump with a railroad spike in top. Spike bears N.52°W., 10.1 ft. (not of record).
A 45" Cedar stump with a railroad spike in top. Spike bears N.9°30'W 14.7 ft. (not of record).
No trace of remains of orig. BT's.
Condition report only. Did not remonument.
Placed County BT signs on both stumps.
In a clearcut unit. No trees nearby.

Dennis Gaylord
U.S.F.S.
Deputy, Doug. Co.
Surveyors Office
Witness:Randall Lopez
March 1978
C.S. 59/46

— — — — — — 3/16/78

95

Section Corner for Secs. 3 and 2 only of T29-2.
Found - Orig. 14" now a 17" Fir stump bears S.40°W., 12.54 ft. (Rec. S.36°W.) Has a healed scar.
Orig. 14" now 16" Pine stump bears S.79°E., 29.70 ft. (Rec. S.78°E.) scribing visible on unhealed blaze, "T29S R2W S2 BT".
Set - Using record distances & bearing tree stumps, at the intersect point I SET a 2 1/2" Brass cap on a 1" Gal. I. P. stamped:
County Surveyors Office T 28 S 1978

S 34	R
S3 | S2	2
T 29 S	W

New BT's- A 16" D. Fir bears S.10°E., 144.4 ft. scribed "T29S R2W S2 CS BT" on a double blaze.
A 22" D. Fir bears S.37°30'W., 115. 8 ft. scribed "T29S R2W S3 CS BT" on a double blaze.
Placed County BT signs on all BT's and stumps.
Corner lies 50 ft. North of Rd. No. 274. in a clearcut unit.

— — — — — — — — 3/9/78

96

Section Corner for Sec. 1, T29-2 & Sec. 6, T29-1 only.
(South Boundary Sec. 36 of T28-2)
Found - 1917 GLO Brass cap solidly set in ground & properly stamped.
A 18" D. Fir stump with a healed blaze bears S.35°W., 9.24 ft.
A 14" D. Fir stump with a healed blaze bears S.66°E., 31.8 ft. (Rec. 30.36 ft.)
New Bearing Objects:
A 3/4" Iron rod set in a 20" Cedar stump, 1" alum. cap, stamped R.M. on iron rod, bears N.58°W., 11.2 ft.
A 3/4" Iron rod with 1" alum. cap stamped R.M. set in a 19" D. Fir stump bears S.88°E., 39.0 ft.
Placed county BT signs on all 4 stumps.
Corner in a clearcut unit. No trees near by.

Dennis Gaylord
March 1978
C.S. 59/46

— — — — — — — — — 3/16/78

97

Section Corner for 2 and 1 only of T29-2.
Found - Orig. corner stone set firmly in place. No visible marks on stone, which is soft & somewhat weathered. Stone measures 15" x 12" x 6".
A 20" Hemlock bears S.35°45'E., 23.1 ft. Some scribing visible on partly healed blaze.
A 16" D. Fir bears S.55°W., 23.1 ft. (Rec. S.45°W., 23.1 ft.) Has a healed blaze.
Placed County BT signs on both trees.
Set - Moving corner stone aside, I SET in it's place a 2 1/2" brass cap on a 1" I.P. Brass cap stamped County Surveyor's Office
T 28 S

S 2	S 1
T 29 S	R 2 W

1978

I bury corner stone alongside & build a rock mound around iron pipe.
No new accessories.

— — — — — — —