

Douglas County Surveyor's Record of  
Government Corners Renewed

Twp. 28 S T. S. Rge. 3 W. R. W. W. M.

ROSE-CHEMMAN CO., EUGENE, ORE. 97126

W.A. EAPPELLMAN  
J. H. MARKHAM  
5-10-52  
A-37

SECTION 18 - NORTHWEST CORNER OF SECTION 18  
Determined by old B.T.  
Set 1" x 30" Iron Pipe  
19" Laurel which bears S. 5 degrees West, 23.6 ft.

RE-RENEWED, SEE CORNER NO. 29

QUARTER CORNER SECTIONS 13 and 18:  
Mile measured 5160 Ft.  
1" x 30" Iron Pipe  
Maple 22" N. 38 degrees West, 107.0 Ft. S. B.T.  
Fir 12" S. 82 degrees East, 160.0 Ft. S. B.T.  
Power Pole S. 58 degrees West, 178.0 Ft.  
Front door on house N. 2 degrees West, 157.0 Ft.

SECTION CORNER OF SECTIONS 13, 18, 24, 19:  
1" x 30" Iron Pipe  
8" Maple which bears N. 35 degrees East, 32.5 Ft.

Section corner to secs. 4, 5, 8 & 9.  
Found only one original BT, now a 46 inch D. Fir, bearing S.17° E. for  
44 lks. I chopped in and found old scribe marks. I rescribed this  
tree with S 9 BT and used it to reset the corner stake.  
Set a 4 inch x 4 inch x 4 foot cedar stake marked S4, S5, S8 and S9.  
Marked one new BT:  
A 42 inch D. Fir bearing N.39°E. for 50.7 feet, marked S4BT.

1/4 sec. corner to secs. 5 and 8.  
Found on original BT, now an 18 inch maple, bearing N.10°W. for 3 lks.  
I chopped in the old face and found the old marking, and then rescribed  
the outside with S5.  
Set a 3 inch x 4 inch x 4 foot cedar stake for corner.  
Marked 1 new B. T.:  
10 inch W. Fir, bearing S.17°W., for 19.4 feet and scribed  
S 1/4 SBT on the face.

1/4 corner to secs. 6 and 7.  
Point for corner determined by O. B. T. - A 20 inch La. bears S.28°E.,  
13.9 feet dist. - found scribe, O. B. T.  
Cedar B. T. completely gone.  
At corner point set 5/8 inch x 40 inch iron bolt with nut on top, 24 inches  
in ground.  
From which:  
A 10 inch Cedar bears N.70°E., 19.0 feet dist., mkd. 1/4 S 6 B.T.  
A 14 inch La. bears S.38E., 80.0 feet dist., mkd. 1/4 S 7 B. T.  
Logging road bears West 800 feet, more or less, North 330 feet more  
or less, and East 240 feet, more or less.

Closing corner to sections 5 and 6.  
Found:  
A 14 inch Fir bears S70E., 13.2 feet dist.- found scribe - O. B. T.  
A 20 inch La. windfall bears S65W 18.0 feet dist.- found scribe-O. B. T.  
At corner point set 1 1/2 inch x 20 inch steel shaft 14 inches in ground,  
from which:  
A 20 inch La. bears S.25W., 32.0 feet dist. mkd. S 6 B. T.  
A 30 inch Cedar bears N8E., 27.2 feet mkd. S 32 B. T.  
Section corner to secs. 31 - 32 bears West 11.2 feet.  
Main top bears West 120.0 feet.

Section Corner to Sections 18 & 19. Maple  
Found - Both original BTs. The 6 inch now 14 inch recently opened scribed  
"BT", N.35°E. 11.9 feet.  
The 48 inch now 60 inch R. Fir checks bearing & distance, no scribe  
Marks found. S18  
Set Brass Cap marked County Surveyor's Office, 1957, 1/4 Cor. S19 T.28S, R.3W.  
30 inch R. Fir S.31°E., 10.4 ft. scribed 1/4 S.19, CS BT (Bark Scribed)  
18 inch R. Fir N.16 1/2°E., 26.2 ft. scribed 1/4 S.18, CS BT.

Claude Kerr  
September, 1956.  
C. S. File No. 42/91.

John H. Markham Jr. - R. E. No. 2880.  
Work done for J. G. Loewen Logging Co.  
February 19, 1957.

C. S. File No. 42/247.

C.S. FILE No 49/22

11/23 M119-14  
FD OK  
10/21  
W. Ruppert  
M89-20

1  
1-A  
11  
1-B  
2  
3  
4  
5  
6