

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

Section Corner to Sections 21 - 22 - 27 - 28. 106
Found - All Orig. BT's. All check record except Orig. 12", now
30" Fir S.68°E. 44.0 ft., not 50.8 ft, shows good scar.
N.W. BT. shows good scribing.
Also find Stone at Corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's

S21	S22	T28S
S28	S27	R3W

Office, 1962

New BT's: 9" Laurel bears S.35°W. 11.0 ft. scribed S28 T28S R3W CS BT.
8" Laurel bears N.48°W. 17.8 ft. scribed S21 T28S R3W CS BT.

1/4 Corner to Sections 16 and 15. 107

Found - No Original BT's. We do find 12" x 10" x 6" Stone with
"1/4" chisled on North face.
Now 12" Fir bears S.80°W. 9.6 ft., shows good scribing on old
face "1/4". Scribing by ring count checks O.K. for 1908 survey.
Now 25" R. Fir N.74°E. 24.5 ft., shows good scar. We do not open.

Set - Brass Cap alongside Corner Stone & Mkd: County Surveyor's
Office, 1962 1/4 S16/S15 T28S R3W

Rescribe - Now 12" R. Fir S.80°W. 9.6 ft. 1/4 S16 CS BT.

South 1/4 Corner to Section 17 only. 108

Found - Orig. 18", now 30" Fir S.21°W., not South 44.2 ft., shows
good scar.

Orig. 20", now 36" Cedar N.28°W. 37.6 ft., shows scribe marks.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
South 1/4 S17 T28S R3W.

New BT's: 10" Cedar bears N.41°E. 20.6 ft. scribed S1/4 S17 CS BT.
30" Cedar bears N.13°W. 18.0 ft. scribed S1/4 S17 CS BT.

1/4 Corner to Sections 33 and 34. 109

Found - Both BT's. as recorded. Orig. 10", now 17" Laurel N.52°E. 6.6 ft.
shows good scribing on previously
Do not find Corner Stone opened face. "B".

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
1/4 S33/S34 T28S R3W

No New Bearing Trees..

Closing Corner Sections 33 and 34. 110

Found - Both Orig. BT's. & Stone at Cor. Orig. N.E. BT. shows
good scribe. Orig. N.W. BT. shows scars.

Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's Office
1962 CC S33/S34 T28S R3W
T29S

New BT: 24" Cedar bears N.62°W. 27.5 ft. scribed CC S33 T28S R3W CS BT.

1/4 Corner to Sections 21 and 22. 111

Found - Orig. 36" Fir, now 39" East 7.9 ft. good bark scribe
Orig. 15" Fir, now 18" N.45°W. 23.8 ft., good scar.
Also found Lava Stone at Corner, badly chipped & pitted.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
1/4 S21/S22 T28S R3W

Orig. Trees used: 39" Fir East 9.9 ft.
18" Fir N.45°W. 24.8 ft.

Section Corner to Sections 8 - 9 - 16 - 17. 112

Found - County Surveyor's Brass Cap marked 1957, See Ren. #10.
18" Hemlock, now 19", S. 5° E. 13.6 ft., scribing visible.
36" Cedar N. 38° W. 44.2 ft., scribing visible.
10" Hemlock N. 65° E. 29.3 ft.

New BT: 7" Hemlock S. 85° W. 36.7 ft. scribed T28S R3W S17 CS BT.

Dec. 19, 1966

James W. Byron, Deputy County Surveyor
John M. Powell and Wm. Stoffel
September and October 1962
C. S. File No. 52/126

RE-RENEWED, SEE CORNER NO. #154

John M.
Powell and
Crew
12/19/66
C. S. File
No. 52/126

174