

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 3 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21861

James W. Byron, Deputy
M. Godfrey
S. Bilow
June 11, 1958
C. S. File No. 49/47

Not T28-3W

12

Corner of Sec. 36, T.28S., R.4W., & Secs. 1 & 6 T29S, R3W. & R4W.
Found - Both Original Bearing Trees:
Orig. 18", now 30" Fir, now down, shows good scar, S.35°W. 22.4 ft.
Orig. 20", now 38" Fir, S.30°W. 40.2 ft. I open & find good
scribing "S".
Set Brass Cap at Corner Mkd: $\begin{matrix} S36 & T28S \\ R4W & | & R3W \\ S6 & T29S \end{matrix}$ County Surveyor's
Office, 1958
New BT's: 20" Cedar bears S.71°W. 55.2 ft. scribed S1 T29S R4W CS BT.
18" Cedar bears S.30°E. 29.5 ft. scribed S6 T29S R3W CS BT.

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
Feb. 2, 1960
C. S. File No. 49/47

13

Closing Corner Sections 35 & 36.
Found - Orig. 8", now 20" Laurel N.26°W. 25.1 ft., shows good
scribing on old face.
Orig. N.E. BT., face down in pond.
Note - Corner in Pond. I do not set Brass Cap. North $\frac{1}{2}$ Corner for
Section 1 T.29S R3W. bears S.84°E. 58.0 ft.
New BT's: 12" R.Fir N.33°W. 21.6 ft. scribed CC S35 T28SR3W CS BT.
7" R.Fir bears N.2°E. 38.2 ft. scribed CC S36 T28S R3W CS BT.

14

Closing Corner Sections 34 and 35.
Found - Orig. 6", now 20" Laurel N.48°W. 18.5 ft., shows good
"28S R3W 34 CC" scribing.
No trace of Orig. N.E. BT. found.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
 $\begin{matrix} T28S & R3W \\ S34/S35 \\ T29S \end{matrix}$
New BT's: 5" R.Fir bears N.16 $\frac{1}{2}$ °E. 24.3 ft. scribed S35 CS BT.
15" R.Fir bears N.51°W. 22.5 ft. scribed T28S R3W CC S34 CS BT.

Thomas E. Shrum, Jr.
For U. S. Plywood Corp.
December 1960
Map File M 11 - 79

15

Standard Corner to Sections 13 and 14.
Found - 6" x 12" x 14" Stone
36" Hemlock - N.64°W. - 42.9 ft. (Stump)
42" Fir - N.34°E. - 32.3 ft. (Stump)
42" Fir - S.55°E. - 41.6 ft. (Stump)
Set - $\frac{3}{4}$ " x 36" Iron Rod
42" Fir - N.15°30'E. - 32.6 ft. (Stump)
36" Hemlock - N.66°W. - 42.8 ft. (Stump)
8" Yew - S.12°E. - 96.0 ft.

16

Closing Corner to Sections 23 and 24.
Found - Stone 6" x 6" x 11"
18" Fir - S.27°E. - 8.6 ft. (Down)
22" Fir - S.52°W. - 42.5 ft. (Stump)
Set - $\frac{3}{4}$ " x 36" Iron Rod
5" Yew - S.61°30'W. - 33.6 ft.
15" Fir - N.85°E. - 64.5 ft.
15" Fir - S.24°30'E. - 58.8 ft.

17

$\frac{1}{4}$ Corner Sections 23 and 24.
Found - 13" Yew - N.79°E. - 31.2 ft.
56" Fir - West - 13.7 ft.
Set - $\frac{3}{4}$ " x 36" Iron Rod
12" Yew - N.48°W. - 58.0 ft.
13" Yew - N.79°E. - 31.2 ft. (Rescribed)

18

Section Corner to Sections 23 - 24 - 25 - 26.
Found - 6" x 10" x 14" Stone
26" Hemlock - S.14°E. - 45.2 ft.
12" Hemlock - S.49°W. - 37.0 ft.
Set - $\frac{3}{4}$ " x 36" Iron Rod
6" Hemlock - N.43°E. - 27.4 ft.