

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

121

Section Corner to Sections 1 - 2 - 11 - 12.

Found - 2 1/2" Aluminum Cap, See Ren. No. 98

27" D. Fir, S. 30° E. 28.4 ft., scribed S12 T28SR3W CS BT.,
Cut high stump above scribe.

24" W. Fir N. 13 1/2° E. 11.2 ft., scribed S1 T28SR3W CS BT.
Cut high stump above scribe.

10" W. Fir, S. 21° W. 26 ft., scribed S11 T28SR3W CS BT.

8" Yewwood N. 05° W. 28.8 ft., scribed S 2 CS BT.

New BT's: 6" W. Fir N. 75 1/2° E. 10.3 ft., scribed S1 BT, Alum Tag RE4287
8" Yew S. 57° E. 19.8 ft., scribed S12 BT, alum. tag RE4287

RENEWED CORNER NO. #170

Thomas E. Shrum, Jr.
For U. S. Plywood, Corp.
January 1965
C. S. File No. 51/254

122

1/4 Section Corner: Sections 4 and 9.

Found - 14" Ching., N. 16° W., 24.4 ft.

16" Madrone, S. 10° E. 16.1 ft.

New BT's: 36" Fir S. 72 1/2° W., 70.1 ft.

47" Fir N. 29 1/2° W. 71.9 ft.

Note - Proposed road will destroy Original BT's.

123

Witness Corner to Cl. Corner to Sections 35 & 36, T28-3W.

Found - Bearing Trees as recorded in Ren. #13, as follows:

12", now 14" R. Fir N. 33° W. 21.6 ft., blazes healed, alive.

7", now 10" R. Fir N. 2° E. 38.2 ft., alive, blazes healed.

Orig. Laurel N. 26° W. 25.1 ft., alive, scribe visible
on decaying face.

Corner falls in pond 60 ft. in diam. & 5 ft. deep.

Set - Wit. Cor. 30' N. of True Corner.

Brass Cap Mkd: County Surveyor's C.C.S 35/S36 T 28 S R 3 W
Office, 1966 Wit. Cor. T29S
30 ft. S. to Corner.

New BT's: 10" R. Fir N. 3° E. 8.2 ft. added "W.C." betwn. blazes.

9" R. Fir N. 70° W. 9.1 ft. mkd. WC T28S R3W S35 CC CS BT.

Witness Corner lies 7 ft. North of edge of pond.

12/22/66

MICROFILM TO HERE 10/67

Vernon "Ray" Tracy
Jack Heritage & E. West
Dec. 22, 1966
C. S. File No. 52/126

124

1/4 Corner to Section 6 only, T28-2W.

Set - 2 1/2" Aluminum Cap mkd: T28S R2W S6 R.E. 4287.

24" Madrone N. 46° E. 54.4 ft. mkd: S6 B.T. RE 4287.

26" Madrone S. 79° E. 82.3 ft. mkd: S6 B.T. R.E. 4287.

Thomas E. Shrum, Jr.
Dec. 1968
M 37 - 17

125

1/4 Corner to Sections 28 and 29.

Found - Corner Stone, in place, broken, "4" on larger piece.

Found - Orig. 14", now 26" Cedar sawed stump, N. 45° W. 1.3 ft., scribe on
log.

Ren. #58 B.T. buried under logs.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 28 S R 3 W
Office, 1970 1/4 S 29 | S 28

Also set 6.0 ft. Steel Fence Post 1.0 ft. South of Cap.

New BT's: 6" D. Fir S. 67° W. 13.7 ft. mkd: "1/4 S29 CS BT".

6" Hemlock N. 35° W. 11.8 ft. mkd: "1/4 S29 CS BT".

This corner lies in cutoff unit approx. 300 ft. West of Road.

3/12/70

126

Vernon "Ray" Tracy
J. Heritage & V. Perron
C.S. File 52/126

MARCH 71

Sec. Corner to Secs 19 & 30, T28-3W.

Set - 1" x 30" I.P. with Brass Cap

Marked New BT's: 14" Hemlock bears N. 30° E. 49.9 feet

7" White Fir bears S. 48° E. 4.4 feet

Baughman,
Glenn S.
For: Sun
Studs
July '71
C.S. File
M43 - 19

127

1/4 Corner Section 30 only, T28-3W. (WEST)

Set - 1" x 30" I.P. with Brass Cap

New BT: Marked 12" Maple for Sec. 30 only bears S. 65° E. 40.7 ft.