

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 28 S T. S. R 3 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

Bruce A. Shaner
LS #430
For: Longview
Fibre Co.
Sept. 25, 1978
M 73 - 52

139

1/4 Corner for Sec. 4 only. T29-3
Set - Brass cap mkd. 1/4 S4 T29S R3W 1979
From which a:
12" Maple orig. BT, I rescribe bark, "1/4 S4 BT" bears
S.80°E., 39.6 ft.
10" Cedar, I scribe "1/4 S4 BT" bears S.53°W 56.7 ft. Ren. #39
20" D. Fir, Hootman BT, stump bears N.67 1/2° E., 46.7 ft.
9/25/78

140

North 1/4 corner Section 24 only.
Set - 2" x 30" I.P. with brass cap stamped T28S R3W 1/4 S24
RLS 934 1978
From which:
12" Hemlock bears S.31°W., 17.7 ft. I blazed & scribed "N 1/4
S 24 BT".
16" Hemlock bears S.19°E., 5.5 ft. I blazed & scribed "N 1/4
S 24 BT".
9/78

141

1/4 Corner for Sec. 24 and Sec. 19 of T28-2
Set - Concrete monument approx. 6" wide on top, 12" wide at bottom
18" high, on steep NW rock slope.
3" brass disc in top of conc. mon. stamped T28S R3W S24 S19 R2W
RLS 934 1978.
From which:
10" yew OBT, bears S.13°E., 15.2 ft. (23 lks.) Good face with
scribing visible. Tree is down but alive.
16" Hemlock OBT, bears N.58°W., 24.4 ft. (37 lks.) No remains of
face found. Tree is down and almost completely rotted away.
Rotted stump hole apparent.
New BT's-10" Hemlock bears N.6°30'W., 26.9 ft. I blazed & scribed "T28S
R3W 1/4 S24 BT".
12" Hemlock bears N.83°E., 5.8 ft. I blazed & scribed "T28S R2W
1/4 S19 BT".

142

Section corner for Secs. 24, 25 and Secs. 19 and 30 of T28-2
Found - 1" I.P. with brass cap stamped County Surveyors Office T28S
R3W S24 S25 S19 S30 R2W 1962. Ren. #41
40" Hemlock bears S.14°E., 23.4 ft. face with scribing visible
36" D. Fir snag bears S.29°W., 19.7 ft. Healed face. Did not open.
36" D. Fir snag bears N.50°W., 15.8 ft. Face with scribing visible.
New BT- 18" Chinquapin bears S.14°30'W., 102.5 ft. I blazed & scribed
"T28S R3W S25 BT".

143

Section corner for Secs. 23, 24, 26 and 25.
Found - 3/4" I.R. with orig. stone alongside from which:
30" Hemlock bears S.22°30'E., 15.2 ft. face with scribing visible.
40" Cedar bears N.70°W., 33.8 ft. face with scribing visible.
SW and NE BT's are down. Ren. #18
Set - 2" x 30" Galv. I. P. with 3" brass cap stamped T28S R3W S23 S24
S26 S25 RLS 934 1978.
New BT's-26" Cedar bears S.44°30'W., 71.6 ft. I blazed & scribed T28S
R3W S26 BT"
8" Hemlock bears N.45°E., 35.7 ft. I blazed * scribed "T28S R3W
S24 BT"
Set 3/4" Iron rod and stone alongside new monument.
9/78

144

1/4 Corner for Secs. 23 and 24.
Found - 3/4" Iron rod. Ren. #17
From which:
14" Yew stump bears N.47°W., 57.8 ft. lower face with scribing
"BT" visible.
14" Yew bears N.82°E., 31.2 ft. face with scribing visible
56" Fir stump bears N.84°W., 15.5 ft. No scribing visible.
Set - 2" x 30" Galv. I.P. with 3" brass cap stamped T28S R3W 1/4 S23
S24 RLS 934 1978.
Set - 3/4" I.R. alongside.
9/78

Victor M McLind, LS #934
For: Umpqua National Forest
Sept. 1978
M 70 - 36

RE-RENEWED. SEE CORNER NO. #163

RE-RENEWED. SEE CORNER NO. #160

RE-RENEWED. SEE CORNER NO. #157