

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Ronald G. Geisler, Champion International
June, 1985 thru August, 1985
M 90 - 71

156

Township Corner for Sec. 1 (T28-3); Sec. 31 (T27-2); Sec. 36 (T27-3); and
Sec. 6 (T28-2). Renewal #150 (T28-3)

Found - A 1962 County Surveyor brass cap on an iron post, and the following
accessories;

- BT's - 27" Fir stump, bears N.40°E., 46.9 ft. dist., (Rec. N.43°E., 46.2 ft.)
Scribing partly visible. (Original)
- 44" Fir stump, bears N.52°W., 29.9 ft. (Rec. N.55°W., 30.4 ft.)
No scribing visible. (Original)
- Badly decayed stump, bears S.25°W., 27.7 ft. (Orig.)
- 11" broken-top Fir, bears N.10°W., 19.7 ft. Closed face. (1962)
- 22" Cedar, bears S.27°W., 71.6 ft. (Rec. 72.0 ft.) Closed face
(1962)
- 16" Madrone snag, 17 ft. tall, bears S.06°E., 17.0 ft.
(Rec. S.03°E) Scribing visible. (1962)
- 9" down and uprooted fir bears N.87°E., 50.0 ft. No scribing
found. (1962)
- 10" Fir, bears N.27°E., 35.1 ft. (Rec. 35.3 ft.) Closed face.
(1980)

NEW BT

Set - 5" Fir, bears S.79°E., 5.9 ft. dist. Scribed: X BT.

157

1/4 Corner for Sec. 23 and 24.

Found - A 2" galv. iron pipe with 3" brass cap extending 7" above ground
and a 3/4" iron rod alongside. Brass cap is marked "T 28S R3W
1/4 S23 S24 RLS 934 1978".

SEE REN #144

- BT's - A 14" Yew, bears N 82°E, 31.2 ft. (vis. scribing)
- 14" Yew stump, bears N 47° W, 57.8 ft. (vis. scribing)
- 56" fir stump, bears N 84°W, 15.5 ft.

NEW BT

Set - A 5" D. Fir, bears S 30°W, 17.8 ft. scribed "X" "BT".
A 1/2" washer marked "RLS 1035" was nailed flush to the
lower blaze.

Section Corner for Secs. 13 and 14.

Found - A 3/4" iron pipe with 2 1/2" alum. cap ext. 12" above ground and
marked "USPC PROP. COR. T28S R3W 14|13 RE 4287"

23

SEE REN #136

- A 9" D. Fir, bears N 14°45'W, 46.2 ft. Blaze healed.
- 9" D. Fir, bears S 62°W, 73.7 ft. Blaze healed.
- 18" Yew(dead), bears S12 1/2°E, 96.0 ft. Vis. scribe.
- 42" fir stump, bears N 37°E, 32.8 ft.
- 42" fir stump, bears N15 1/2°E, 32.6 ft. Vis. scribe.
- 36" Hemlock (rotted) stump, bears N67°W, 42.6 ft.

NEW BT

Set - A 6" D. fir, bears N73°E, 38.0 ft., scribed "S13 T28S R3W BT"
with brass washer stamped "RLS 1035" Nailed flush with the
lower end of the blaze.

158

1/4 Corner for Sec. 24.

Found - A 2" galv. iron pipe with 3" brass cap ext. 4" above ground and
mkd. "T28S R3W C 1/4 S24 RLS 934 1978"

SEE REN# 145

- BT's - A 8" Hemlock, dead and down, bears N 44°E, 10.4 ft. vis. scribe
- Set - A 9" D. fir, bears N2°W, 14.9 ft.
- 10" hemlock, bears S 48°W, 51.4 ft.

Both BT's scribed "C 1/4 S24 BT" with a brass washer stamped
"RLS 1035" nailed flush to the lower portion of the blaze.

159

Section Corner for Secs. 24&25, T28-3, and 19&30 T28-2.

Found - A 1" iron pipe with 2 1/2" brass cap ext. 14" above ground and
mkd. "T28S R3W S24|S19 R2W, 1962.

S25|S30

See Ren #142

- BT's - A 18" Chinquapin Oak, bears S14 1/2°W, 102.5 ft. vis. scribe.
- 40" Hemlock stump, bears S14°E, 23.4 ft. vis. scribe
- 36" D. fir stump, bears S29°W, 19.7 ft. blaze healed.
- 36" D. fir stump, bears N50°W, 15.8 ft. vis. scribe.

NEW BT

Set - A 8" Chinquapin Oak, S52°E, 45.0 ft. scribed "S30 T28S R2W BT"
5" Hemlock, bears N85°E, 43.3 ft., scribed "X" "BT".
A brass washer stamped "RLS 1035" was nailed flush with the
lower portion of the blazes.
No tree available in the NW quadrant.

160

Gerald Nygren LS 1035
C.S. 63/29-63/69
March 1988