

Douglas County Surveyor's Record of
Government Corners Renewed

T 28

T. S.

R 3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

165

Gerald V. Nygren
L.S. #1035
For: USFS
Dec. 13, 1988
C.S. 63/92

Closing Corner for Sections 7 and 18 only of T.28-2

- Found - A 1" I.P. with alum. cap extending 6" above stone mound. Ren.#116
A 26" stump bears N.32°W., 26.1 ft. - visible scribing.
A 40" D. fir stump bears S.60°E., 29.0 ft. - healed blaze.
A 24" stump bears N.82°E., (Rec. N.82°W.) 56.1 ft. Ren. #147
A 12" maple bears N.49°E., 51.8 ft. - visible scribing.
New BT - A 10" cedar bears S.57°E., 19.5 ft. scribed "T28S R2W S18 BT".
A ½" brass washer was set in BT face marked "RLS 1035".

Bearing tree and monument signs were placed on all BTs without them and a 6" red bank and face blazes were painted on all bearing trees.

12/13/88

166

Section Corner for Secs. 31; and 36 of T.28-4

- Found - A 1964 BLM ¾" brass cap on a 2½" dia. iron pipe, protruding 7" above ground.
Orig. 34" dia. Cedar now depression with burnt roots bears N.32°W., 25.7 ft. (agrees with 1964 BLM record)
Orig. 24" dia. D. fir bearing N.10°E., 130.7 ft in 1964 BLM dependent resurvey, is gone.
42" now 49" dia. D. fir with a fully healed single blaze bears N.48°E., 56.1 ft. (agrees with record) from 1964 BLM survey.
16" now 18" dia. 7 ft. tall tipped D. fir stump with illegible scribe marks in a partially healed single blaze bears N.50 3/4°W. 44.2 ft. (agrees with rec.) from 1964 BLM D. resurvey.
8" now 12" dia. I. Cedar with a partially healed single blaze, bears N.70°W., 15.8 ft. (agrees with rec.) from 1980 BLM D. resurvey. Note: Tree not likely to live long, recently girdled with a chain saw.
New BTS - 8" dia. I. Cedar double blazed and scribed "T28S R3W S31 CS BT" bears N.69½°E., 45.0 ft.
14" dia. D. fir double blazed and scribed "T28S R4W S36 CS BT" bears N.17½°W., 52.7 ft.

Corner lies at the intersection of a north and east cutting lines. Old growth in northeast quadrant.

9/15/89

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Sept. 15, 1989
C.S. 64/1

Section Corner for Sec. 31, T.27-3 and Sec. 36, T.27-4

- Found - ¾" dia. 1989 BLM brass cap on a 2½" dia. iron pipe protruding 8" above ground. (unrecorded 1989 BLM survey)
¾" iron rod from Ren. #118 not seen.
Orig. 14" now 22" dia. madrone with a rotted out center old blaze with possible reverse scribing visible, bears S.37½°W., 15.9 ft. (orig. rec. S.35°W., 14.5 ft.; BLM BT tag, N.37½°E., 14.5 ft.)
10" now 24" dia. madrone with a previously opened blaze, no scribing visible bears S.43°E., 12.6 ft. (orig. rec. S.31°E., 11.2 ft. BLM 1989 BT tags N.43°W., 13.8 ft.)
15" now 30" dia. madrone with a partially healed upper blaze scribing visible "T27S R3W S3 " lower blaze fully healed, bears N.48½°E., 13.9 ft. (Orig. rec. N.40°E., 13.9 ft.; 1989 BT tag S.48½°W., 13.9 ft.)
14" now 20" dia. 7 ft. high madrone snag with a partially healed double blaze, scribing visible "T27S R4W S36 CS BT" bears N.24½°W., 12.5 ft. (Orig. rec. N.23°W., 11.9 ft.; BLM 1989 BT tag, S.24½°E., no dist.)
1989 BLM BT, a 7" dia. D. fir with a single blaze, scribing visible "T27S R4W S36 SC BT" bears N.41½°W., 24.8 ft. (agrees with BLM 1989 BT tag.)
5" dia. D. fir double blazed, marks visible "X BT" bears N.59°E., 16.1 ft.)1989 BLM BT tag N.59°E., 16.1 ft.)
2½" dia. brass cap on a 1½" dia. iron pipe protruding 14" above ground, marked "County Surveyors Office T27S S36 R4W S1 S6 CC T28S 1961" bears N.87½°W., 52.5 ft. (Rec. 52.0 ft. from Ren. No. 26.

CORNER REPORT ONLY. NO NEW MONUMENT OR ACCESSORIES.

9/18/89

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Sept. 18, 1989
C. S. 64/3