

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 28 S.                      T. S.                      R. 3W.                      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

Douglas County Surveyor  
Randall Smith &  
Stephen Flause  
Feb. 19, 1997  
C.S. 64/71-17

**171**

Closing Corner for Sec. 2 & 3  
Condition Report Only  
Mon. Pd.- 2½" Alum. cap on a 1" O.D. Iron pipe protrudes 16" above  
ground. Set by Thomas Shrum date unknown not of record.  
Bt's Pd. - No orig. Bt's found  
See C.S. 64/71-9 for corner renewal of ~~35/36~~ 34/35

David Edwards  
For: J. Nelson  
June 1998  
M 128-70

**172**

Center 1/4 for Section 18  
Set - 5/8" x 30" steel pin w/red plastic cap mkd. "D.A. EDWARDS-LS 2339"  
BT's- 11" dia. Cedar, bears S.88°E., 22.60 ft.  
10" dia Fir, bears S.13°W., 10.90 ft.  
10" dia. Fir, bears N.87°W., 14.80 ft.  
15" dia. Fir, bears N.35°W., 16.53 ft.  
Note - Bearing trees were scribed according to the 1973 BLM manual, measured to  
center of tree at root crown.

*Doc D. Edwards 3/2000 CS 65/64-3*

David Edwards  
For: Seneca  
Jones Timber Co.  
CS 65/29-10  
10/2000

**173**

South 1/4 Cor. Sec. 16 only  
Found - A diligent search was made, with negative results.  
Near the south ¼ corner a cedar & fir (now a  
stump) called for in the County Surveyor's 1962  
search notes. Inquiries to survey staff at the  
Umpqua National Forest Office & local & state BLM  
offices produced no information as to the origin of  
the scribed trees, I therefore set the south ¼  
corner at the proportionate distance between the  
sec. corners.  
Set - 5/8"x36" steel pin W/ 2½" dia., alum. cap mkd: "T28S  
R3W ¼ S16 LS 2339 2000"  
The previously scribed Cedar (now 22" dia., &  
rescribed "¼ S16 BT" to face the new corners)  
A 17" dia., Cedar bears N.1°E., 9.95 ft. ("¼ S16 BT)

**174**

NW Cor. Sec. 16  
Found - DCSO brass cap. (Ren. #10)  
40" dia., Cedar (1957 BT) bears N.38°W., 44.2 ft.  
6" dia. Hemlock scribed "S9 BT" bears N.34°E. 10.40 ft  
New - 5" dia. Hemlock scribed "S16 BT" bears S.71°E. 15.0 ft  
6" dia., Hemlock scribed "S17 BT" bears S.39°W. 7.25 ft

**175**

NW Cor. of Sec. 21  
Found - DCSO brass cap (see Ren. #62)  
New BT- 7" dia., Fir scribed Fir scribed "S20 BT" bears S.19°W.  
24.0 ft.

Ted Baker  
For: Seneca Jones  
Timber Co.  
May 2001  
M138-15

**176**

1/4 Cor. Secs. 6 & 7  
Found - 3/4" iron bolt & nut. (Ren. #4)  
12" Cedar, N.76°E., 18.1' (scar vis)  
22" Madrone S.28°E., 13.9' (no marks)  
24" Madrone (Blowdown) S.38°E., 80.0' (scar vis)  
New BTs - 10" Fir, S.10°E., 42.4'  
All new BTs are scribed & painted red, distances to  
BTs are center measure.

**177**

1/4 Cor. Secs. 5 & 6  
Found - 1962 Douglas Co. 2½" brass cap. (Ren. #101)  
New BTs - 10" W.Fir, S.80°W., 14.4'  
6" Fir, N.33°E., 33.2'  
All new BTs are scribed & painted red, distances to  
BTs are center measure.