

Douglas County Surveyor's Record of
Government Corners Renewed

28

T. S.

3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Cor. Secs. 5 & 8 *Fd ok by C. Woodruff* 182
6/2007 M153-69

Greg Lang - Found - Brass cap set by Byron in 1962 (Ren. #55)
For: Seneca Orig. 1910 Maple now 21" dia., bears N.10°W., 3 lks
Jones Timber Co. Set spike in the base of the tree & placed new tag
Kerr's 1956 W. Fir now 20" dia., bears S.17¼°W., 18.6
ft. (We set a spike in this tree, but scratched
our information on the existing BT tag (Ren. #3)
Also fd. a metal "T" post at the corner.

July 2001 New - 7" Hemlock bears N.88¾°E. 19.0' scribed "¼ S5" "BT"
M 138-46 and C.S. 10" Hemlock bears S.70½°E. 24.3' scribed "¼ S8" "BT"
File 65/37-14 A thru E 6" Hemlock bears N.76¾°W. 27.0' scribed "¼ S5" "BT"
Set spike in the base of the trees & placed new tag.

Note - Corner lies on westerly slope less than 100' East of
a drainage; also at the S'y edge of logged unit
C.S. File 65/37-14A

Corey Woodruff

Cor. Secs. 4, 5, 8, & 9

183

6/2007
M153-69

Found - County Surveyor BCIP set by Byron (Ren #56)
24" R. Fir bears S.8°W., 46.3'
26" R. Fir bears S.81°E., 39.1'
28" R. Fir bears N.68°E., 32.6'

New - 13" Fir bears N.54°W., 11.8'