

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$ Section Corner to Sections 23 and 26. 19
Found - 12" Fir - S.41°E. - 40.9 ft. (down & rotten)
26" Fir - N.01°W. - 27.0 ft.
Set - $\frac{3}{4}$ " x 36" Iron Rod
18" Fir - N.19°E. - 31.0 ft.
18" Fir N.86°W. - 26.5 ft.
6" Fir S.37°30'E. - 39.7 ft.

Center $\frac{1}{4}$ Section 23. 20
Set $\frac{3}{4}$ " x 36" Iron Rod
21" Fir - S.16°E. - 18.4 ft.
13" Fir - N.06°30' - 14.2 ft.

$\frac{1}{4}$ Section Corner to Sections 22 and 23. 21
Found - Stone 7" x 11" x 14"
12" Fir S.39°W. 19.1 ft.
16" Fir N.77°W. 10.6 ft.

Section Corner to Sections 22 and 23. 22
Found - Stone 6" x 10" x 15"
26" Hemlock - S.38°E. - 39.0 ft.
St - $\frac{3}{4}$ " x 36" Iron Rod
10" Hemlock S.37°W. 30.4 ft.
60" Fir N.18°E. 81.5 ft. (stump)

$\frac{1}{4}$ Section Corner to Section 14 only. 23
Found - 24" Hemlock S.60°W. 12.5 ft. (down & rotten)
12" Cedar - N.40°W. 26.4 ft.
Set - $\frac{3}{4}$ " x 36" Iron Rod
12" Hemlock N.87°E. 29.0 ft.
10" Yew N.60°30'W. 18.0 ft.

$\frac{1}{4}$ Section Corner to Section 23 only. 24
Set - $\frac{3}{4}$ " x 36" Iron Rod
12" Hemlock S.27°W. 38.3 ft.
12" Hemlock S.14°30'E. 38.0 ft.

R4W R3W 25
Renewed Corner $\frac{S36/S31}{S6}$ T27S
Found - All four Orig. BT's. The SW & NW Orig. BT's. show good scribing. All check record.
Stake at Corner.
New BT's: 20"(Orig) Laurel bears N.22°W. 12.5 ft. scribed S36 T27SR4W CS BT.
32"(Orig) Laurel bears N.50°E. 13.0 ft. scribed S31 T27SR3W CS BT.

Closing Corner Renewed $\frac{S36}{S1/S6}$ T27S 26
R4W S1/S6 T28S R3W
Found - Both Orig. BT's. Orig. 60", now 66" Fir S.80°E. 19.8 ft., shows old bark scribing "B.8". Orig. 40", now 44" Fir S.85°W. (Not S.65°W) 15.8 ft., shows old bark scribing "S T".
Set - Brass Cap at Corner Mkd: CC $\frac{S36}{S6}$ T27S
Co. Surveyor's Office R4W. S1/S6 T28S R3W 1961
New BT's; 15" Cedar bears S.67°E. 23.8 ft. scribed S 6 T28S R3W CS BT.
6" R.Fir bears S.56°W. 33.6 ft. scribed S 1 CS BT.
Note - See Sketch in file for location of corners.

Closing Corner. Found - Both Orig. BT's. Each Tree is in good condition, each shows good scribing and each checks record. 27
Set - Brass Cap at Corner Mkd: CC $\frac{S6}{R4W/S7}$ T28S R3W County Surveyor's Office, 1961
No New BT's; Note - Corner is under 30" Log.

C. S. File 49/67

Thomas E. Shrum, Jr.
For U. S. Plywood Corp.
December 1960
Map File M 11 - 79

C.S. 49/67

Jms. W. Byron, Deputy
M. Godfrey & C. Putnem
July 13, 1961
C. S. File 49/130