

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 3 R. W. W. M.

KOKE-CHARMAN CO., EUGENE, ORE. 21681

28

C.S. 49/67

FD. B.C.
OK 10/81
W. RUPPEST
1789-20
11193 M 119-11

1/2 Corner to Sec. 18, T28-3W. & Sec. 13, T28-4W.
Found - Brass Cap at Corner & N. W. BT. S.E. BT. down. REN. #11
New BT: 20" Cedar bears N.82°E. 163.0 ft. scribed 1/4 S18 CS BT.
August 1, 1961

29

Section Corner to Secs. 7 & 18, T28-3W. & Secs. 12 & 13, T28-4W. REN. #1
Found - 1" I. Pipe at Cor. ^{REN} Orig. 60", now 60" Cedar, Face & Side gone,
burned out. Orig. 24", now 30" Laurel N.55°E. 42.9 ft., shows
old scribing. We also find a Fir Snag, rotted, that checks for S.W. BT.
Set - Brass Cap alongside 1" I. Pipe Mkd: County Surveyor's S12 | S 7 T28S
Office, 1961 R4W S13 | S18 R3W
New BT's: 60" Cedar O.B.T. bears N.70°W. 29.7 ft. scribed by others. S12
20" Laurel bears S.55°W. 23.5 ft. scribed by others, S13 T28S R4W 2880
R. Fir bears S.37°E. 25.0 ft. scribed S18 T28S R3W CS BT.

30

East 1/4 Corner S12, T28S R4W. West Side Section 7, T28S R3W.
Found - Orig. 16", now 30" Fir, down, S.30°E. 9.2 ft. We open & find good
Scribing "1/4".
Orig. S.W. BT. not found.
Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961 1/4 S12 T28S R4W.
New BT's: 18" Fir bears S.24°E. 22.6 ft. scribed 1/4 S 7 CS BT.
50" Fir bears S.76°W. 60.5 ft. scribed 1/4 S12 CS BT.
August 4-9, 1961

31

Closing Corner to Sections 30 and 31.
Found - Scribed Stake at Cor. - Orig. 20", now 32" Fir N.49°E. 34.3 ft.,
shows good scar. I do not open. - Orig. 24", now down & partly
rotted Fir S.80°E. 11.2 ft. I find good scribing on Stump Section.
Set - Brass Cap alongside Cor. Stake Mkd: County Surveyor's S30 | T28S
Office, 1961 R4W S31 | R3W CC
New BT: 12" R.Fir bears S.8°E. 7.3 ft. scribed S31 T28S R3W CS BT.

32

Corner to Sections 25 and 36 only, T28S R4W. - West Bdry. T28S R3W.
Found - Orig. 12", now 18" Laurel N.65°W. 27.7 ft. We open & find good scribe.
Orig. S.W. BT. now stump, rotted.
Set - Brass Cap at Cor. Mkd: County Surveyor's S25 |
Office, 1961 R4W S26 | R3W T28S
New BT's: 20" R.Fir bears S.71°W. 21.0 ft. scribed T28S R4W S36 CS BT.
10" Cedar bears N.23°W. 25.0 ft. scribed T28S R4W S25 CS BT.

33

1/4 Corner to Section 36, T28S R4W. See Cor. No. 83 in T28S R4W.
and Section 31 of T.28-3

34

John H.
Markham, Jr.
Dec. 12, 1961
C.S. File
No. 51/221

S. E. Corner Section 36, as det. by Old BT's.
40" Fir N.80°E. 31.5 ft., fd. scribe O.B.T.
52" Fir Snag N.50°W. 21.1 ft, fd. scribe O.B.T.
At Corner Point found Stone & Set 1 1/2" x 36" Truck Axle, flange up, from 131
40" Cedar bears S.83°E. 11.9 ft. mkd: S 6 B.T. which:
7" La. bears N.25°E. 25.9 ft, mkd: S31 T28S R2W B.T.
6" Fir bears N.59°W. 21.7 ft. mkd: S36 B.T.
Centerline Road bears South 42.0 ft.

35

Corner to Sections 18/17 only.
Found - Orig. 36", now 44" R.Fir S.20°E. 17.2 ft., shows fair bark
scribing. Orig. 10", now 20" Fir S.30°W. 17.8 ft. shows old
scar. Orig. 12", now 14" W.Fir N.60°W. 5.9 ft. shows bark
scribing. We also find stump of Orig. N.E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
S18/S17 T28S R3W
New BT: 21" W.Fir bears N.59 1/2°E. 22.0 ft. scribed S17 T28S R3W CS BT.
Rescribe, now 14" W.Fir N.60°W. 5.9 ft. S18 T28S R3W CS BT.

James W. Byron, Deputy
D. McFarland & J. Powell
March 14, 1962
C. S. File No. 49/67

Corner to 19/20 only. - 41.0 ft. East of 18/17
Find both Orig. Bearing Trees.
Set - 2" x 2" Sq. Cedar Stake at Corner.

36