

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 3 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$ Corner to Sections 18 and 17.

Found - Both Orig. Bearing Trees: Orig. 18", now 18" Cedar
S.49°E. 7.9 ft., shows good scribing.
Orig. 6", now 10" Cedar N.70°W. 27.7 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S18/S17 T28S R3W
No New Bearing Trees.

James W. Byron
& Crew
March 1962
C. S. File
No. 49/67

FD OK
10/18/61
w. Support
M89-20
M43 M119-11

South Boundary of T28-3W - Section corner common to Secs. 3 & 4, T29-3W.

This corner is not common to Sections 33 and 34, T28-3W.
I locate the true corner point from a 13" Fir BT., blazed &
scribed as per the 1910 notes; this corner is 9.8 ft. North
& 15.0 ft. West of corner set previously.
I Set a 1" Iron Pipe and witness the corner as follows:
13" Fir DBH bears S.41°E. 34.6 ft. mkd: in 1910, scribe marks
clearly visible.
14" Laurel DBH bears N. 3°30'W. 11.6 ft. Mkd: T28SR3W S33 BT.
Trees mkd. for the previous corner lay as follows:
Cedar 20", bears S.49°E. 38.7 ft. Mkd: T29S R3W S3 BT.
Fir 20", bears S.28°W. 21.0 ft. Mkd: S 4 BT.

Warren D. Hootman, No. 399
Survey for J. P. Heath
Sept. 21, 1961
C. S. File No. 51/164

North $\frac{1}{4}$ Corner of Section 4, T29-3W.

Found - Maple 12" DBH which bears S.80°E. 39.6 ft. faced but
no scribe marks left.

The true corner point falls under a large log.
Set - 2" x 2" x 3" Stake on top of the log, witness as follows:
D. Fir 20" DBH bears N.67°30'E. 46.7 ft. Mkd: H 913.
Remark Orig: Maple 12" DBH bears S.80°E. 3.96 ft. Mkd: H T. $\frac{1}{4}$ S 4, 399.

Corner to Sections 5 and 4 only, T29S-R3W.

The total distance across the N. line of Sec. 4 and E. $\frac{1}{2}$ of
the N. line of Sec. 5 nearly approximates those dist. of the
1910 survey and as no new trees were marked at that time for the
Sec. Cor. 5 & 4, I believe the two firs to be the Orig. BT's.

Set: $\frac{3}{4}$ " Iron Pipe from the 2 BT's at the dist. & bearing
called for by the 1910 notes and witness the cor. as follows:
Madrone 11" DBH bears West 5.2 feet.
Madrone 16" DBH bears S.45°E. 13.5 ft.

RE-RENEWED, SEE CORNER NO. #139
RE-RENEWED, SEE CORNER NO. #138

41

Section Corner to Sec. 24 & 25, T28-3W. & Secs. 19 & 30, T28-2W.
Found - Stone at Cor. & all BT's. except S. E. BT. S.W. BT., now
dead. Distance to S.W. BT. should be 18.0 ft., not 31.0 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
New BT: 36" Hemlock bears S.14°E. 23.4 ft. scribed S30 T28SR2W CS BT.

James W. Byron, Deputy Co. Surv.
John Powell & Mike Stone
July 12, 1962
C. S. File No. 52/126

$\frac{1}{4}$ Corner to Sec. 36, T28-3W. & Sec. 31, T28-2W.

Found - Stone at Corner & BT's., all as recorded. S.W. BT. has
previously been opened, shows good scribing.
Set - Brass Cap alongside Corner Stone & Mkd: County Surveyor's Office,
 $\frac{1}{4}$ R3S36/S31R2 T28S 1962
New BT: 13" R.Fir bears S.41°W. 10.0 ft. scribed $\frac{1}{4}$ S36 CS BT.

42