

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

51

North $\frac{1}{4}$ Corner Section 5, T29-3W.
Found - Orig. 8", now 10" Fir S.10°W. 5.9 ft., previously
opened, shows good scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
N $\frac{1}{4}$ S5 T29S R3W.
New BT: 8" R.Fir bears S.88°W. 16.3 ft. scribed N $\frac{1}{4}$ S5 CS BT.
(Dist. to BT. measured to base tree leans to West)

52

$\frac{1}{4}$ Corner to Sections 8 and 17.
Found - 8", now 13" Hemlock N.9°E. 6.6 ft. We open & find good scribing.
Original S.E. BT. not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{1}{4}$ S 8 T28S R3W
New BT: 7" Hemlock bears S.58°E. 31.3 ft. scribed $\frac{1}{4}$ S17 CS BT.

53

Section Corner to Sections 29 - 30 - 31 - 32.
Found - Orig. 8", now 8" R.Fir N. 1°E. 5.9 ft. We open & find good
scribing. We use this BT. to locate position of corner. We
find other Orig. BT's. thus: 14" R.Fir S.42°E. 19.5 ft.,
not S.53°W. 17.2 ft. Forked 10" Maple N.42°W. 16.5 ft., not
N.35°W. 19.1 ft. 5" Dead Laurel shows good scribing S.29°W.
23.7 ft., not S.36°E. 21.8 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{830}{S31} | \frac{S29}{S32}$ T28S R3W
New BT: 6" Laurel bears S.43°W. 16.7 ft. scribed S31 T28S R3W CS BT.
10" Maple N.48°W. 16.5 ft. scribed S30 T28S R3W CS BT.

54

$\frac{1}{4}$ Corner to Sections 8 and 9.
Found - Orig. 48", now 48" Fir S.85°E. 19.8 ft., shows bark scribing, "4/".
Orig. N.W. BT., down, shump hole, checks bearing & distance.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S8/S9 T28S R3W.
New BT's: 21" Cedar bears S.21 $\frac{1}{2}$ °W. 22.6 ft. scribed $\frac{1}{4}$ S8 CS BT.
24" Laurel bears S.70°E. 37.5 ft. scribed $\frac{1}{4}$ S9 CS BT.

55

$\frac{1}{4}$ Corner to Sections 5 and 8.
Found - BT's. & Stake at Corner as recorded by Kerr. REN.#3
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{1}{4}$ $\frac{S5}{S8}$ T28S R3W

56

Section Corner to Sections 4 - 5 - 8 - 9.
Found - Corner Scribed Stake & Orig. S.E. BT. & new BT., all as
recorded by Kerr, 1946. BT's. are now down. REN.#2
Set - Brass Cap alongside Corner Stake & Mkd: County Surveyor's Office, 1962 $\frac{S5}{S8} | \frac{S4}{S9}$ T28S R3W
New BT's: 14" R.Fir bears N. 1 $\frac{1}{2}$ °W. 47.3 ft. scribed S 5 T28S R3W CS BT.
6" R.Fir bears S. 8°W. 46.3 ft. scribed S 8 CS BT.
7" R.Fir bears S.81°E. 39.1 ft. scribed S 9 CS BT.
5" R.Fir bears N.68°E. 32.6 ft. scribed S 4 CS BT.

57

Section Corner to Sections 20 - 21 - 28 - 29.
Found - Orig. 6" or 7" Maple BT, down & out of position, shows good
reverse scribing. Corner is on steep south slope about 75 ft.
N. of bottom of draw. This BT. could be either SW. or SE.
Orig. BT. I find Maple Stump hole that checks for SE. BT.
location. We also find yellow tag on 5" Fir North 12.0 ft. It
is marked about 16 years ago.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{S20}{S29} | \frac{S21}{S28}$ T28S R3W
New BT's: 11" R.Fir bears N.22°E. 30.9 ft. scribed S21 T28S R3W CS BT.
21" R.Fir bears N.55°W. 70.5 ft. scribed S20 T28S R3W CS BT.
11" Maple bears S. 5°E. 43.7 ft. scribed S28 T28S R3W CS BT.
9" Eyewood bears South 49.0 ft. scribed S29 CS BT.
Note - Corner Stone not found.

James W. Byron, Deputy County Surveyor
John Powell
Wm. Staffrel
July 1962
C. S. File No. 52/126

181

182

#183