

Douglas County Surveyor's Record of  
Government Corners Renewed

T 28 S. T. S. R 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner to Sections 29 and 28. 58  
Found - Stone at Corner as recorded. Orig. 14" Cedar, now 25"  
N.45°W. 1.3 ft., shows scribing.  
Orig. N.E. BT., down, shows scar.  
New BT: 5" R.Fir bears S.69°E. 10.3 ft. scribed 1/4 S28 CS BT.

Renew Closing Corner Sections 21 and 22. 59  
Found - Both BT's. as recorded. The SW. has previously been opened.  
S. E. BT. shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's CC T28S R3W  
Office, 1962 S21/S22  
No new BT's. scribed.

Renew Corner to Sections 16 and 15 only. *FD OK BY D. EDWARDS 10/2000* 60  
Note - Closing Corner above bears East 88.7 ft., not 91.1 ft. *CS 65/29-16*  
Found - Both Orig. BT's. Orig. N.E. BT. previously opened, shows good Scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 S16/S15 T28-3W.

Witness Corner to Sections 17 and 16 only. 61  
Found - Section Corner to Section checks record bearing & dist.  
Also find Orig. SE. & SW. S20/S21 BT's. for this corner.  
Both BT's., now down, We find scribing (bark) on SE BT.  
SW. BT. shows scar, now 24" Cedar, not Fir.  
Note - Corner is in 2 lk. stream.  
Set - Wit. Corner 7.0 ft. North - Set Brass Cap at Wit. Cor. & Mkd:  
County Surveyor's Office, 1962 W. C. S17/S16 T28S R3W 7' S. to Cor.  
New BT; 16" Hemlock bears N.75°W. 25.0 ft. scribed W. C. S17 T28S R3W CS BT.  
5" Cedar bears N.22 1/2°E. 25.9 ft. scribed S16 CS BT.

Closing Corner Sections 20 and 21. 62  
Found - Orig. 6", now 14" Hemlock S.48°E. 73.3 ft. We open & find good  
scribing. Also find Orig. SW. BT., down, shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
CC S20/S21 T28S R3W  
New BT's:  
9" R.Fir bears S.14°E. 24.0 ft. scribed S21 T28S R3W CS BT.  
5" R.Fir bears S.55°W. 23.4 ft. scribed S20 CS BT.  
Note - Corner is on West Slope & 100 ft. East of 2 lk. stream.

Section Corner to Sections 9 - 10 - 15 - 16. 63  
Found - 2" I.R. at corner.  
12", now 20" Laurel S.70°W. 15.2 ft., shows good scribing on old face.  
Orig. 7", now 10" Laurel S.5°E. 16.5 ft., shows old scars.  
N.E. & N.W. BT's. not found.  
New BT's: 28" R.Fir bears N.33°W. 9.0 ft. scribed S9 T28S R3W CS BT.  
O.BT. rescribe now 20" Laurel S.70°W. 15.2 ft. S16 CS BT.  
14" Laurel bears N.4°E. 40.4 ft. scribed S10 T28S R3W CS BT.  
9" R.Fir bears S.14°E. 24.1 ft. scribed S15 T28S R3W CS BT.

N  
E  
X  
T  
  
P  
A  
C  
E

James W. Byron, Deputy County Surveyor  
John Powell and Wm. Stoffel  
July and August 1962  
C. S. File No. 52/126

*FD OK  
D. Edwards  
3/2008  
CS-65/29-16*  
  
*10/2000  
FD OK  
D. Edwards  
CS 65/29-16  
SWBT  
down*

RECORDED & INDEXED  
CORNER NO. 125

RECORDED & INDEXED  
CORNER NO. 175