

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

64
Section Corner to Sections 26 - 27 - 34 - 35.
Found - Orig. 5", now 11" R.Fir N. 11° E. 26.4 ft., shows scribing.
Orig. 14", now 24" R.Fir S. 52° E. 7.9 ft., shows scribing.
Orig. 5" Fir S. 73° W. 17.8 ft., dead, shows scribing.
Orig. 5", now 9" Cedar N. 44° W. 7.9 ft., shows scribing.
We do not find Corner Stone.
Set - Brass Cap at Corner Mkd: County Surveyor's $\frac{S27}{S34}$ | $\frac{S26}{S35}$ T28S R3W
Office, 1962
New BT: 11" Cedar bears S. 78° W. 17.5 ft. scribed $\frac{S34}{S35}$ T28S R3W CS BT.

65
 $\frac{1}{4}$ Section Corner to Sections 27 and 26.
Found - Stone, broken, at corner & Both BT's as recorded.
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's
 $\frac{1}{4}$ S27/S26 T28S R3W Office, 1962
Orig. 6" Fir N. 54° E. 23.8 ft., now dead, shows scribing.
Orig. 14" Cedar, now 24", N. 62° W. 4.6 ft., shows scar.
New BT: 10" W. Fir bears S. 82° E. 23.4 ft. scribed $\frac{1}{4}$ S26 CS BT.

66
 $\frac{1}{4}$ Section Corner to Sections 26 and 35.
Found - Stone at Cor. as recorded. Orig. 6", now 10" Dead Fir S. 6° W.
23.1 ft. We open & find good scribing. N.E. Orig. BT. not fd.
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's
 $\frac{1}{4}$ $\frac{S26}{S35}$ T28S R3W Office, 1962
New BT's: 56" Cedar bears S. 35° W. 4.8 ft. scribed $\frac{1}{4}$ S35 CS BT.
18" R.Fir bears N. 35° W. 49.9 ft. scribed $\frac{1}{4}$ S26 CS BT.
Note - Corner is at toe of West Slope.

67
 $\frac{1}{4}$ Section Corner to Sections 20 and 21.
Found - Both Orig. BT's. Orig. 7", now 13" R.Fir bears S. 57° W. 16.5 ft.,
not S. 15° W. 16.5 ft. We open this BT. & find good scribing.
Orig. 8", now 18" R.Fir bears S. 20° E. 15.2 ft., not S. 17° E.,
shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S20/S21 T28S R3W
Note - Corner is about 100 ft. East of draw & on West slope of
Ridge & 100 ft. West of top of ridge.

68
South Line T28S-R3W - Corner $\frac{T28S R3W}{S 3/S 2 T29S R3W}$
Found - Three Orig. BT's. Orig. 48", now 52" Cedar shows good scribing,
N. 50° E. 46.2 ft. Orig. 15", now 28" Cedar S. 62° W. 23.1 ft.,
shows good scribing. Orig. 20", now 40" Fir N. 54° W. 39.6 ft.,
not N. 62° W., shows good bark scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{T28 R3W}{S 3/S 2 T29S}$
New BT's: 11" R.Fir bears S. 29° E. 24.3 ft. scribed S 2 T29S R3W CS BT.
Rescribe, now 28" Cedar S. 56° W. 23.1 ft. S2 T29S R3W CS BT.
Note - Corner is on West Slope about 200 ft. West from top of ridge.

69
South $\frac{1}{4}$ Corner to Sections 32, T27-3W.
Found - Orig. 18", now 22" Laurel S. 50° E. 7.9 ft., not 83.2 ft., shows
good scribing $\frac{1}{4}$ ". Orig. 20", now 24" Laurel N. 20° E. 13.9 ft.
We open but old face rotted, no scribing found.
Note - We find S.E. BT. dist. should be 12 lks., not 126 lks. as this
area has a great number of old Laurel & Fir trees that would
have been close to corner had the distance been as recorded.
Set - Brass Cap at Cor. Mkd: County Surveyor's South $\frac{1}{4}$ $\frac{S32}{T28S}$ T27S R3W
Office, 1962
New BT's: 7" Fir bears N. 27° E. 23.4 ft. scribed $\frac{S 1}{4}$ S32 CS BT.
28" Laurel bears N. 52° W. 24.5 ft. scribed $\frac{S 1}{4}$ S32 CS BT.

70
Renew East $\frac{1}{4}$ Corner to Section 1 only, T28S R3W. #151
Found - Orig. 12", now 18" Fir N. 80° W. 13.9 ft., shows faint bark scribng.
Orig. 36" Fir, now down, N. 65° E. 33.7 ft., shows bark scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

James W. Byron, Deputy County Surveyor
John Powell and Bill Stoffel
August 8 - 10, 1962
C. S. File No. 52/126