

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 3 W. R. W. W. M.

Renew Corner to Sections 13 and 24 only, T28-3W. ⁷⁷
Found - All BT's as recorded. N.W. BT. shows good scribing. *FD. OK 3/80 BHW GWS. M83-9*
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{S13}{R3W S24} | \frac{R2W}{T28S}$
Rescribe Orig. 24", now 28" Hemlock S.25°W. 9.9 ft. S24 T28S R2W CS BT.

Renew Closing Corner to Sections 18 and 19, T28-2W. ⁷⁸
Found - Stone at Cor. & Both BT's, as recorded. *RE-RENEWED CORNER NO. #149*
N. W. BT. shows good scribing. $\frac{S18}{R3W} | \frac{S19}{R2W}$
DO NOT SET BRASS CAP AT CORNER.
New BT: 9" R.Fir bears S.43°E. 5.0 ft. scribed S19 CC T28S R2W CS BT.

Section Corner to Sections 11 - 12 - 13 - 14. ⁷⁹
Found - Orig. 8", Maple, down, N.20°W. 38.3 ft.
Orig. 36" Fir, now dead, S.20°W. 33.7 ft.
Orig. 10", now 17" Hemlock S.29°E., not S.25°E. 25.7 ft.,
not 29.7 ft., shows scribing.
Orig. 30", Fir, now dead, N.15°E. 21.7 ft., not 27.7 ft., shows
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{S11}{S14} | \frac{S12}{S13} T28S R3W$
New BT's: 34" Cedar bears N.83°E. 24.3 ft. scribed S12 T28S R3W CS BT.
8" Hemlock bears N.5°W. 32.2 ft. S.11 T28SR3W CS BT.
9" Hemlock bears S.49°W. 49.0 ft. scribed S14 T28S R3W CS BT.

Corner to Sections 35 and 36, T27-3W. ⁸⁰
Found - Orig. 14", now 17" Laurel, shows good scribing.
No other Orig. Bearing Trees found.
Find $\frac{3}{4}$ " Iron Rod at Corner & a $\frac{3}{4}$ " I. R. 9.2 ft. East
which is record for C. C. $\frac{S2}{S1}$
New BT's: 8" R.Fir bears N.82°E. 19.7 ft. scribed S36 CS BT.
15" R.Fir bears N.79°W. 55.0 ft. scribed S35 T28S R3W CS BT.
Note - We find 48" R.Fir bears N.61°E. 52.7 ft., shows good bark scribing.
This BT. may have been scribed for C.C. 2/1 T28S, but not
of record.

South $\frac{1}{4}$ Corner to Section 35 only, T27-3W. ⁸¹
Found - Orig. 18" Fir N.65°W. 42.9 ft., shows good bark scribing.
Orig. 72", now 90" Fir S.85°E.67.0 ft., not 72.6 ft., Dead.
Find $\frac{3}{4}$ " I. R. at corner and Rock Mound.
Note - A $\frac{3}{4}$ " I. R. bears East 13.6 ft. May have been set for North $\frac{1}{4}$ S 2.
New BT's: Rescribe, now 40" R.Fir N.65°W. 45.9 ft. $\frac{1}{4}$ S35 CS BT.
(9" Laurel bears S.85°E. 21.4 ft. scribed $\frac{1}{4}$ S CS BT.

Renew Corner to Sections 34 and 35 only, T27-3W. ⁸²
Found - $\frac{3}{4}$ " I. R. at Corner & Orig. 16", now 24" Cedar bears N.60°E.
33.0 ft., shows good scribing. No other Orig. BT.s. found.
New BT: 6" R.Fir bears N.61°W. 83.4 ft. scribed $\frac{1}{4}$ S34 CS BT.

$\frac{1}{4}$ Corner to Sections 34 and 35 only. ⁸³
Found - Both Orig. BT's. S.E. BT., shows good scribing.
Corner Stone not found. *RE-RENEWED CORNER NO. #169*
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{S34}{S35} T28S R3W$
We do not rescribe new BT's. Orig. 24", now 34" Cedar S.35°W. 8.0 ft., not 7.3 ft.
Orig. 10", now 20" Cedar S.74°E. 29.5 ft., not 27.7 ft.
Corner is at top of south slope & about 50.0 ft. N. of bottom of draw.

Corner Renewed South $\frac{1}{4}$ Corner to Section 33, T27-3W. ⁸⁴
Found - Orig. 30", now 72" Fir N.55°E. 19.8 ft., shows good old bark
scribing. We do not find Orig. S.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
S $\frac{1}{4}$ S33 T27S R3W
New BT: 12" Laurel bears N.11°W. 32.7 ft. scribed $\frac{1}{4}$ S33 CS BT.

James W. Byron, Deputy County Surveyor
John Powell and Wm. Stoffel
September and August, 1962
C. S. File No. 52/126