

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 28 S. T. S. R. 3 W. R. W. W. M.

ROSE-CHARMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy County Surveyor  
John Powell and Wm. Stoffel  
August and September 1962  
C. S. File No. 52/126

Renew Corner to Sections 32 and 33 only, T27-3W. 85  
Found - All Orig. BT's. Orig. 16", now 24" R. Fir N.16°E. 30.4 ft.,  
shows good scribing. Orig. 30", now 36" Fir, not Laurel N.25°W. 32.3  
ft., shows good bark scribing. Orig. 14", now 24" Fir S.30°W. 20.5.,  
shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's S32/S33 T27-3W  
Office, 1962 T28

Renew Corner to Sections 5 and 4 only. 86  
Found - Both Orig. BT's. Orig. 12", now 20" Laurel S.44°E. 24.4 ft., shows  
good scribing. Orig. 5", now 10" Laurel S.37°W. 42.9 ft. old  
face rotted.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
S 5/S4 T27S  
T 28S R3W  
New BT: 13" Laurel bears S.10°W. 22.5 ft. scribed S5 T28S R3W CS BT.  
Note-Sec. Cor. S32/S33 T27S bears N.76°W. 62.9 ft., not West 62.9 ft.

Renew Corner to Sections 33 and 34 only, T27-3W. 87  
Found -  $\frac{3}{4}$ " I. R. at cor. Orig. 30", now 50" Cedar S.30°W. 13.9 ft.,  
shows good old bark scribing. Orig. 8", now 15" Laurel N.35°E.  
58.7 ft., face rotted. Also find stump hole for N.W. BT.  
New BT's: 8" Chinq. bears N.62°E. 13.7 ft. scribed T27S R3W S34 CS BT.  
14" Laurel bears N.7°W. 50.0 ft. scribed T27S R3W S33 CS BT.  
Note - We also old bark scribing on now 36" R. Fir "T28S R3W S33" bears  
S.27°E. 36.0 ft. I believe this tree was scribed 1882 but  
not recorded.

$\frac{1}{4}$  Corner to Sections 14 and 13. 88  
Found - Orig. 30", now 40" Cedar Stump N.54°W. 25.7 ft., shows axe on old  
face. No scribing found. Orig. 6", now 14" Cedar S.35°E. 7.3 ft.  
shows old axe work, now stump. Also find section of old pointed  
stake in place at corner.  
Set - Brass Cap at Cor. & Set Cedar Post alongside Mkd:  
County Surveyor's Office, 1962  $\frac{1}{4}$  S14/S13 T28S R3W.  
Note - Log. Road is about 100 ft. South of  $\frac{1}{4}$  Corner.  
New BT: 10" Maple bears S.81°W. 128.6 ft. scribed  $\frac{1}{4}$  S14 CS BT.  
Rescribe 40" Cedar Stump N.54°W. 25.7 ft.  $\frac{1}{4}$  S14 CS BT.

South  $\frac{1}{4}$  Corner for Section 13. 89  
Found - Orig. 12", now 14" Yewwood Snag S.55°W., not S.35°W. 27.1 ft.,  
shows good scribing. Orig. 36", now 40" Low Cut Fir Stump,  
N.21°W. 25.7 ft., no scribing found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
South  $\frac{1}{4}$  S13 T28S R3W.  
New BT's: 34" Hemlock bears N.85°W. 11.0 ft. scribed S $\frac{1}{4}$  S13 CS BT.  
8" Yewwood bears N.71°E. 5.7 ft. scribed S $\frac{1}{4}$  S13 CS BT.

Section Corner to Sections 10 - 11 - 14 - 15. 90  
Found - Orig. 20", now 36" Fir S.65°W. 35.7 ft., shows good bark scribing.  
Orig. 36", now 39" Fir N.45°W. 11.2 ft., no scribing found.  
Orig. 8", now 12" Laurel N.15°E. 21.1 ft., face rotted, no scribng.  
Orig. S.E. BT. not found.  
Note - Corner is just off the west edge of log. road on top of ridge.  
Set - Brass Cap at Cor. Mkd: County Surveyor's S10 | S11 T28S  
Office, 1962 S15 | S14 R3W  
New BT's: 11" Laurel bears N.7°E. 18.8 ft. scribed S11 T28S R3W CS BT.  
39" R. Fir (O.B.T.) bears N.45°W. 13.2 ft. scribed S10 T28S R3W CS BT.  
7" Dbl. R. Fir S.63°E. 43.8 ft. scribed S14 CS BT.

Corner to Sections 15 and 14 only. 91  
Found - This corner was renewed by Shrum. We find Orig. N.E. N.W. & S.W. BT's.  
Find  $\frac{3}{4}$ " I. R. at corner.  
9" Hemlock N.16 $\frac{1}{2}$ °W. 31.0 ft. scribed RE 4287 S15 BT.  
9" Hemlock S.22°W. 21.4 ft. scribed RE4287 S22 BT.