

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 28 S. T. S. R. 3 W. R. W. W. M.

KOKK-CHAPMAN CO., EUGENE, ORE. 97881

99

Section Corner to Sections 19 - 20 - 29 - 30.

Found - All Orig. BT's. All show good scars & check record.  
The N.E. BT. shows scribe marks.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 

S19	S20
S30	S29

 T28S R3W

No New Bearing Trees:

1/4 Corner to Sections 30 and 29.

Found - Orig. 18", now dead 24" Fir, N.48°E. 33.0 ft., shows good scribing on old face.

Also find stump of Orig. S. W. BT., rotted.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

1/4 S30/S29 T28S R3W

New BT's: 26" R.Fir bears S.68°E. 25.0 ft. scribed 1/4 S29 CS BT.

8" R.Fir bears N.19°W. 31.3 ft. scribed 1/4 S30 CS BT.

See BLU Rehab. 11/2000  
Vol 53 PG 205B1 100

101

1/4 Corner to Sections 5 and 6.

Found - Orig. 15", now 22" Hemlock Stump N.44°W. 2.6 ft., shows good scribng.  
Orig. N.76°E. 33.2 ft., not N.70°E., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

1/4 S6/S5 T28S R3W

New BT: 9" W.Fir bears S.17°W. 25.6 ft. scribed 1/4 S6 CS BT.

# 177

Section Corner to Sections 5 - 6 - 7 - 8.

Found - Orig. 6", now 12" Hemlock N.42°W. 10.6 ft., shows good scribing.  
Orig. 6", now down 18" Hemlock, N.63°E. 26.4 ft., not 8.6 ft., shows scribing.

Orig. 18", now 30" Hemlock, dead, S.3°E. 13.2 ft., not 26.4 ft.,

Orig. 20", now 90" Hemlock S.68°W. 8.6 ft., not (shows scar)

13.2 ft., snag, shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 

S 6	S 5
S 7	S 8

 T28S R3W

New BT's: 30" Hemlock bears S.49°W. 19.3 ft. scribed S7 T28SR3W CS BT.

6" Hemlock bears S.51°E. 21.0 ft. scribed S8 CS BT.

12" Maple bears N.23°E. 18.8 ft. scribed S5 CS BT (scribed 5 ft. (\$ ft. above ground))

102

1/4 Corner to Sections 24 and 25.

Found - Orig. 40", now 48" Fir Snag N.30°W., not N.40°W. 35.0 ft., shows good scribing.

Orig. 24", now dead 36" Fir, S.44°W., not S.54°W., 136.0 ft., shows scribing.

Find Stone at Cor. as recorded, except chisled 1/4 not found.

Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's Office, 1962 

S24	S25
-----	-----

 T28SR3W

New BT's: 11" R.Fir bears N.46°E. 25.0 ft. scribed 1/4 S24 CS BT.

12" R.Fir bears S.9°E. 5.6 ft. scribed 1/4 S24 CS BT.

103

1/4 Corner to Sections 31 and 32.

Found - Orig. 18", now 24" Fir S.60°E., not S.30°E., 24.4 ft., shows good scar.  
Orig. 30", now 32" Fir, West 18.5 ft., shows good scribing.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

1/4 S31/S32 T28S R3W

Rescribe - Orig., now 24" R.Fir S.60°E. 25.0 ft. "1/4 S32 CS BT".

NOTE: THIS COR. FOR THE N. 1/4 COR. SEC. 32 ONLY SEE GOV. MAP.

104

1/4 Corner to Sections 22 and 27.

Found - Orig. 18", now 22" Cedar Snag, shows good scribing, "1/4 S27 BT".

Orig. 16" Cedar, not Alder, N.23°W. 15.4 ft., not N.48°E. 14.5 ft., shows good scribing "1/4 S22 BT".

Also find Corner Stone in Place.

Set - Brass Cap alongside Corner Stone & Mkd: County Surveyor's Office, 1962 

S22	T28S
S27	R3W

New BT: 9" R.Fir bears S.8°E. 44.2 ft. scribed 1/4 S27 CS BT.

105

James W. Byron, Deputy County Surveyor  
John Powell and Mm. Stoffel  
August and September 1962  
C. S. File No. 52/126