

Douglas County Surveyor's Record of  
Government Corners Renewed

28 T. S. 4 R. W. W. M.

- 11  
CORNER BETWEEN 34 and 3 on SOUTH BOUNDARY OF T. 28  
Set Iron Pipe from 30" Original B.T. sharpened stump of  
other B.T. present. Marked the following trees  
Fir 30" dia. bears N.80°E., 22.0 ft. 80  
Fir 30" dia. bears S.22°E., 59.5 ft. S.80°W.
- 12  
CORNER BETWEEN 34 and 35  
Set Iron Pipe for corner. Found 2 original Bearing  
Trees, both badly rotted. Marked the following trees,  
Fir 24" dia. bears N.26½°E., 49.0 ft.  
Fir 18" dia. bears S.64°W., 33.6 ft. 62
- 13  
CORNER BETWEEN 32 and 29.  
Set square post from one Original Bearing Tree and stump  
of other. Marked the following trees  
Fir 48" dia. bears N.23½°W., 30.2 ft.  
Fir 12" dia. bears S.9°E., 49.7 ft. 44
- 14  
SECTION CORNER BETWEEN 29, 30, 31 and 32.  
Set from two Original Bearing Trees standing and two  
stumps set as per distances. Drove Iron Pipe for corner  
and marked the following trees  
Fir 8" dia. bears S.15½°W., 6.0 ft. 79  
Cedar 18" dia. bears N.30½°W., 46.8 ft.  
Cedar 18" dia. bears S.87½°E., 49.5 ft.  
Fir 18" dia. bears S.83°E., 52.8 ft.
- 15  
CORNER BETWEEN 29 and 30  
Found one O.B.T. and 1 stump. Bearing check with field  
notes except that trees are interchanged. One field note  
distance is given as 4 links but checks with 40 links. Set  
square post and marked the following trees  
Yellow Pine 30" dia. bears S.34°E., 30.2 ft. 107  
Cedar 14" dia. bears S.15½°W., 43.0 ft.
- 16  
CORNER BETWEEN 20 and 29.  
Found two Original B.T.s. One rotted and the other one  
dished. Set Iron Pipe from O.B.T.s and marked the fol-  
lowing trees  
Fir 24" dia. bears S10°W., 42.2 ft. 88  
Cedar 20" dia. bears N.12½°W., 31.6 ft.
- 17  
SECTION CORNER BETWEEN 20-21-28-29.  
Set from one O. B.T. and one stump. Others gone. Set  
Post and marked the following trees  
Fir 36" dia. bears N.5°E., 46.3 ft.  
Yew 10" dia. bears S.47½°E., 71.6 ft.  
Fir 36" dia. bears S.24°W., 12.0 ft.  
Fir 30" dia. bears N.45°W., 72.1 ft.
- 18  
CORNER BETWEEN 28 and 29.  
Set midway between section corners, as all signs of trees  
gone. Drove pipe and marked the following trees  
Cedar 18" dia. bears N.45°W., 59.5 ft. 87  
Cedar 24" dia. bears S.63°W., 144.7 ft.
- 19  
SECTION CORNER COMMON TO SECTIONS 11, 12, 13 and 14.  
One old B.T. standing now a 60" Fir S.7°E., 29.7 ft. 75  
Another Fir N.17°W., 23.1 ft. probably recorded as B.T. but  
not marked. Found rotten alder stump N.80°E., 52.1 ft.  
checks with field notes. Set post for corner with B.T.s  
as follows:  
Fir 60" dia. bears S.7°E., 29.7 ft. O.B.T.  
Fir 60" dia. bears N.17°W., 23.1 ft. O.B.T.  
Hemlock 18" dia. bears S.63°W., 103.0 ft.  
Fir 60" dia. bears N.19°E., 70.3 ft.

M 2 - 4  
G. G. Stewart D.C.S.  
Frank Evans  
Stimpson  
C. Crocker  
2/16/22 2/8/22

G. G. Stewart, D.C.S.  
Witnesses  
Frank Beck,  
G. A. Copeland,  
Vol. 3 p. 127  
C.S. File No. 5/27

M 2 - 7

November 1, 1922

O. E. Leighton

Ben. E. Irving  
May 16, 1927  
with  
R. L. Irving  
J. R. Strouss  
J. Moore