

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 4 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97196

$\frac{1}{4}$ corner to secs. 13 & 24. 40
Found: Orig. South BT, now 40 inches, a R. Fir, bark scribed $\frac{1}{4}$ S BT-in
good condition. Also found what I believe to be orig. Maple BT-no
scribing-found center rotted-checks line & dist. to old $1\frac{1}{2}$ inch x $2\frac{1}{2}$ in. bar.
Set an iron pipe with brass cap at corner alongside old iron bar and mkd.
 $\frac{1}{4}$ S $13/24$ T28S R4W, County Surveyors Office, 1957.
From which:
21 inch W. Fir bears N.61°E., 16.8 feet mkd. $\frac{1}{4}$ S 13 CS BT.
The original South BT bears S.3°E., 46.9 feet - I do not rescribe.

$\frac{1}{4}$ corner to secs. 23 & 26. 41
Found:
2 inch square stake at corner. REN. #27
Eppsteins BT, 18 inches, now 30 inches- a Red Fir, S.1°E., 30.4 feet,
bark scribed $\frac{1}{4}$ S CS BT.
Low cut stump checks for bearing & distance & size-no scribing found.
Original BT uprooted and down slope about 20 feet, bark scribed "BT".
Found hole for BT which checks bearing & distance, S.15°E., 21.8 ft.
Set an iron pipe with brass cap at corner point mkd. $\frac{1}{4}$ S 23/26 T28S R4W
County Surveyor's Office, 1957.
From which:
12 inch Hemlock, N.60°E., 17.8 feet mkd. $\frac{1}{4}$ S 23 CS BT.

Section corner to secs. 1, 2, 11 and 12. 42
Found original N. W. BT - face open with good scribing visible, now a 36
inch Cedar. All orth original BTs gone.
Set an iron pipe with brass cap at corner point at record distance and
bearing from orig. BT, mkd. S $\frac{21}{11}$ T 28 S, R 4 W, County Surveyor's
Office, 1957.
From which:
14 inch R. Fir, West 5.2 feet mkd. S 11 T28S R4W CS BT.
12 inch R. Fir, N.47°E., 9.7 feet mkd. S 1 T28S R4W CS BT.
20 inch R. Fir, S.71°E., 30.0 feet mkd. S 12 T28S R4W CS BT.

Section corner to secs. 28, 29, 32 & 33. 43
Found 36 inch Cedar, N.65°E., 9.8 feet dist. with good scribing visible.
Also found stump of Markhams N.W. BT scribed BT-checks bearing & dist. REN. #30
All other BTs down or gone.
Note: corner 1 foot SW from corner fence post.
Set an iron pipe with brass cap at corner mkd. Sec. cor. $\frac{29}{32}$ T28S R4W,
County Surveyor's Office, 1957.
Scribed new trees:
24 inch Cedar, S.55°W., 59.9 feet scribed S 32 T28S R4W CS BT.
5 inch R. Fir, N.68°W., 35.7 feet scribed S 29 CS BT.
20 inch Cedar, S.82°E., 34.5 feet scribed S 33 T28S R4W CS BT.

$\frac{1}{4}$ corner to secs. 29 and 32. 44
Found old 2 foot stake at corner and 34 inch R. Fir stump, bark scribed
CS BT, S.9°E., 41.0 feet (record 49.7 feet). Found 18 inch Laurel
with open face and good scribing. Found 48 inch Fir stump with chip
at base, bark scribed $\frac{1}{4}$ S, N.23 $\frac{1}{2}$ °W., 30.2 feet. REN. #13
Set an iron pipe with brass cap at corner point alongside old fir stake,
mkd. $\frac{1}{4}$ S S 29/32 T 28 S R4 W, County Surveyor's Office, 1957.
Scribe new BT:
20 inch Cedar, S.19 $\frac{1}{2}$ °W., 42.0 feet mkd. $\frac{1}{4}$ S 32 CS BT.

$\frac{1}{4}$ corner to secs. 33 & 34. 45
Retrace Stewarts 1922 survey to fix position of this corner. (See file). REN. #7
Set an iron pipe with brass cap at corner point mkd. $\frac{1}{4}$ S 33/34 T28S, R4W,
County Surveyor's Office, 1957.
Blazed and scribed two trees:
14 inch Maple, S.32°E., 100.0 feet mkd. $\frac{1}{4}$ S 34 CS BT.
10 inch Ewe Wood corner fence post, S.40°W., 11.5 feet mkd. $\frac{1}{4}$ S 33,
CS BT.

James W. Bryon, Deputy County Surveyor
April - May, 1957.
C. S. File No. 47/180.

FD. OK 4/1/57
R. GEISLER
C.S. 63/60

FD. OK
7/26 N.W. Johnstone
M 100-36

FD. OK 5/11
M 113-14
FD. OK 3/18/57
H. Johnstone
M 100-36

FD. OK 9/85
B. HOYT
M 99-40