

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 4 R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 2181

James W. Byron
For E. D. Randall
Sept. 23, 1955
C. S. File No. 47/31
M 8 - 9

1/4 Section Corner to Sec. 13, T28S R4W, & Sec. 18, T28S R3W. 56
No evidence of Original Corner. Found J.R. Markham's Corner & remove
1" I. Pipe set by Markham for 1/4 corner & remeasure (bearings & distances)
to BTs. Rescribe S.E. BT. R4W R3W
Set Brass Cap midway between Sec. Corners on Line marked S13/S18 T28S
County Surveyor's Office, 1955
New BTs: 22" Maple N.35°53'W. 105.82 ft. scribed 1/4 S BT.
12" R.Fir S.82°15'E. 163.7 ft. scribed 1/4 S18 CS BT.

James W. Byron
Milo Godfrey
S. Bilow
Feb. 26, 1958
C. S. File No. 49/67

Section Corner to Secs. 35 & 36 T28S R4W & Secs. 2 & 1 T29S R4W. 57
Found - Three Orig. BT's., all have open faces & show good scribing.
All check bearings & distances.

The N. W. BT. now down.
The N. W. & S. W. BTs. now snags only.
Find Cedar roots for Orig. S. E. BT.
Set Brass Cap at Corner Mkd. $\frac{S35|S36}{S2|S1}$ T28S R4W County Surveyor's
T29S Office, 1958
New BT's: 12" Cedar bears S. 2°E. 16.7 ft. scribed S1 T29S R4W CS BT.
18" W.Fir bears S.81°W. 31.5 ft. scribed S 2 T29S R4W CS BT.
18" Cedar bears N.65°E. 7.6 ft. scribed S36 T28S R4W CS BT.
36" R.Fir bears N. 2°W. 14.7 ft. scribed S35 T28S R4W CS BT.

Section Corner to Sections 25, 26, 35, & 36. 58

As determined by O. BT's.

20" Fir bears N.20°E. 45.5 ft. O.B.T.
24" Fir bears S.73°E. 15.2 ft. O.B.T.
Found bark scribe & remarked.
20" Fir bears S. 5°W. 25.7 ft. dist. O.B.T., I bark scribe S35 BT.
At Corner Point Set 1" x 20" I.R. from which:
5" Fir bears N.30°W. 2.0 ft. dist. mkd. S26 B.T.
18" Cedar " S.88°E. 39.0 ft. dist. mkd. S25 B.T.

FD. 8/10/54 G. LANGRISH - SEE C.S. 57/18 FOR DISCREPANCIES -

1/4 Section Corner to Sections 25 & 26, 59

As determined by O. B. T's.

40" Fir bears S.60°E. 23.1 ft. dist. O.B.T.,
found scribe & remarked, (bark).
45" Fir windfall bears S.35°W. 21.8 ft. dist. O.B.T.
At Corner Point set 1" x 30" I. P. from which
8" W. Fir bears S.60°W. 13.8 ft. dist. mkd. 1/4 S26 B.T.
7" W. Fir bears N.29°W. 16.6 ft. dist. mkd. 1/4 S26 B.T.
11" W.Fir bears N. 9°E. 18.4 ft. dist. mkd. 1/4 S25 B.T.
Creek bears West 130.0 ft.
Road bears West 330.0 ft.

1/4 Section Corner to Sections 26 & 35. 60

As determined by O. B. T's.

17" Fir Stump (logged) bears N.45°E. 11.2 ft. dist. O.B.T.,
found scribe.
At Corner point found old Cedar Tree down & Set 1 1/2" x 22" I.P. from which:
9" Cedar bears S. 6°W. 15.2 ft. dist. mkd. 1/4 S35 B.T.
7" Fir bears S.77°W. 31.5 ft. dist. mkd. 1/4 S35 B.T.
15" Laurel # S.84°W. 51.0 ft. dist. mkd. 1/4 S35 T28S B.T.

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
Jan. 23, 1958
C. S. File No. 49/130

1/4 Section Corner to Sec. 6, T28S R4W, & Sec. 31, T27S R4W. 61

Found - Boyer's 14", now 24" Fir Stump N.72°W. 25.1 ft., I open
& find good scribing "S1". REN #23

Do not find Boyer's S.W. BT. or either Orig. BT.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959

$\frac{1}{4} \frac{S31}{S6}$ T27S R4W
T28S
New BT's: 14" R.Fir bears N.31°E. 96.8 ft. scribed 1/4 S31 CS BT.
14" R.Fir bears S.77°W. 38.5 ft. scribed 1/4 S 6 CS BT.