

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

'72

Corner to Sections 1 and 12 only.

Found - Orig. 14", now 18" Hemlock Snag N.38°W. 26.4 ft., shows good scribing "T28" on old face. No other Orig. BT's found.

Set - Brass Cap at Corner Mkd:

S 1	T28S
R4W S12	R3W

 County Surveyor's Office, 1961

New BT's: 40" R.Fir bears N.85°W. 17.0 ft. scribed T28S R4W S 1 CS BT.
20" Hemlock bears S.1½°W. 31.6 ft. scribed T28S R4W S12 CSBT.

'73

¼ Corner to Sections 1 and 2.

Found - Orig. 24", now 34" Pine S.70°W. 96.4 ft., previously opened shows good scribing "¼".

Orig. N.E. BT. not found.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961
½ S2/S1 T28S R4W.

New BT: 14" Pine bears S.28½°E. 59.4 ft. scribed ½ S1 CS BT.

'74

¼ Corner to Sections 10 and 11.

Found - Orig. 40", now 44" Fir S.75°W. 14.5 ft., shows good scribing "½S"BT". Orig. NE BT not found.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961
½ S10/S11 T28S R4W.

New BT: 6" R.Fir S.38°E. 20.1 ft. scribed T28S R4W S11 CS BT.

Find OK by
BURT HOLT
10/81
M 90-5

'75

Section Corner to Sections 11 - 12 - 13 - 14.

Found - 60" Fir S. 7°E. 29.7 ft., bark scribed, "S13T28S R4WBT" (~~Old~~ Old Scribing - Probably Original)

60" Fir N.17°W. 23.1 ft., bark scribed "S11", does not look like Orig. scribing.

Square Scribed Stake lying on ground alongside corner, REN#19 badly rotted.

Set Brass Cap Mkd: County Surveyor's

S11	S12	T28S	R4W
S14	S13		

 Office, 1961.

New BT's: 10" R.Cedar S.20°W. 39.0 ft. Mkd: T28S R4W S14 CS BT.
12" Maple N.55°W. 10.4 ft. Mkd: T28S R4W S11 CS BT.
8" Hemlock S.76°E. 38.7 ft. Mkd: T28S R4W S13 CS BT.
12" Alder N.59°E. 20.9 ft. Mkd: T28S R4W S12 CS BT.

Corner lies approximately 15 ft. N. of small creek flowing East.

FD. OK 4/7/88
R. GEISLER
C.S. 63/60

'76

¼ Corner to Section 14 and 13.

Found - B.B.I. Corner Post rotted off & downhill, REN#21

Orig. N.E. BT. shows bark scribing "½S", now down.

B.B.I. now 16" Hemlock N.60°W. 11.9 ft., shows scribe mks.

Set Brass Cap Mkd: County Surveyor's Office, 1961 ½ S14/S13 T28SR4W.

B.B.I's. Post alongside Brass Cap.

New BT: 10" R.Fir bears N.75°E. 23.4 ft. scribed ½ S13 CS BT.

'77

Sec. Corner to Sec. 12-13, T28S-4W. & Secs. 7 & 18, T28S-3W.

Found - 1" I. P. at Cor. - Orig. 60", now 60" Cedar, face & side gone, burned out.

Orig. 24", now 30" Laurel N.55°E. 42.9 ft., shows old scribing.

Fir Snag, rotted, that checks for S.W. BT.

Set - Brass Cap alongside 1" I. P. Mkd: County Surveyor's

S12	S 7	T28S
S13	S18	R 3W

 Office, 1961 R4W

New BT's: 60" Cedar O.B.T. bears N.70°W. 29.7 ft. scribed by others, S12.
20" Laurel bears S.55°W. 23.5 ft. scribed by others, S13 T28S R4W 2880
R.Fir bears S.37°E. 25.0 ft. scribed S18 T28S R3W CS BT.

'78

East ¼ Corner Section 12, T28S - R4W.

Found - Orig. 16", now 30" Fir, down, S.30°E. 9.2 ft. We open & find good scribing "¼". Orig. SW. BT not found.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961
½ S12 T28S R4W

(continued next page)

James W. Byron, Deputy County Surveyor
Milo Godfrey
Clete Putnam
C. S. File No. 49/67
July 18, 1961