

Douglas County Surveyor's Record of
Government Corners Renewed

T 28 T. S. R 4 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

New BT's: 18" Fir bears S.24°E. 22.6 ft. scribed $\frac{1}{4}$ S CS BT.
50" Fir bears S.76°W. 60.5 ft. scribed $\frac{1}{4}$ S12 CS BT.

Section Corner to Sections 29 - 30 - 31 - 32. *FD. OK 6/91 M113-28*
Found - I: Pipe at Corner & All BT's. as recorded by Stewart, *REN. #14*
S.E. Fir BT. & S.W. Fir BT's., now Stumps. S.W. BT. shows
good scribing. *FD. OK 3/186 H. J. J. STONE W. 100-36*

Set - Brass Cap at Corner & Alongside I. Pipe Mkd:

S30	S29
S31	S32

 T28S R4W
County Surveyor's Office, 1961

New BT's: 8" R.Fir bears S.45°W. 47.8 ft. scribed S31 T28S R4W CS BT.
18" Laurel bears N.71°E. 19.9 ft. scribed S29 T28S R4W CS BT.

$\frac{1}{4}$ Corner to Sec. 34, T28-4W. & Sec. 3, T29S-4W. 79

Found - $\frac{3}{4}$ " I. P. in $\frac{1}{4}$ E. W. Fence Line and Both BT's. as recorded by
Stewart, 1922. S.E. BT. shows good scribing " $\frac{1}{4}$ S". *REN. #11*

New BT's: 9" R.Fir bears N.56°E. 8.5 ft. scribed $\frac{1}{4}$ S34 CS BT.
8" R.Fir bears S.75°E. 21.4 ft. scribed $\frac{1}{4}$ S 3 CS BT.

$\frac{1}{4}$ Corner to Sec. 33, T28-4W. & Sec. 4, T29-4W. 80

Found - $\frac{3}{4}$ " I. P. at Corner & under E.W. Fence. We also find both BT's,
recorded. S.W. BT. down. N. E. BT., now 18" Fir Snag,
shows good scribing "BT". - *SEE REN. #6*

Set - Brass Cap alongside Corner I.P. & Mkd: County Surveyor's

S33	T28S
Office, 1961	R4W S 4 T29S

New BT's: 8" R.Fir bears S.78°E. 23.8 ft. scribed $\frac{1}{4}$ S 4 CS BT.
14" R.Fir bears N.49°W. 34.1 ft. scribed $\frac{1}{4}$ S33 CS BT.

Sec. Cor. to Secs. 33 & 34, T28-4W. & Secs. 3 & 4, T29-4W. 81

Found - $\frac{3}{4}$ " I. Pipe at Corner & Both BT's. as recorded by Stewart, 1922. *REN. #5*
S.E. BT., now down, shows scribe marks. S.W. BT. shows good scar.
Old Board Fence Corner Thus:



Set - Brass Cap alongside Corner Pipe & Mkd: County Surveyor's Office, 1961

S33	S34	T28S	R4W
S 4	S 3	T29S	R4W

FD. BC. 7/13 HAINES SEE GIS FILE

New BT's: 20" R.Fir bears S.51 $\frac{1}{2}$ °E. 30.2 ft. scribed S3 T29S R4W CS BT.
5" R.Fir bears S.82 $\frac{1}{2}$ °E. 24.4 ft. scribed S 3 CS BT.

$\frac{1}{4}$ Corner to Section 36.; and Sec. 31 of T.28-3 82

Found - Orig. 18", now 24" Fir N.65°E. 6.6 ft., shows good scars. I
do not open. - Orig. 12", now 13" Fir N.76°W. 13.0 ft.,
not N.85°W. 11.9 ft. (record). Note - This BT. is in small
slide area & out of position, shows good scribing " $\frac{1}{4}$ S".

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1961
East $\frac{1}{4}$ S36 T28S R4W.

New BT: 20" R.Fir bears S.57°W. 14.0 ft. scribed E $\frac{1}{4}$ S36 CS BT.

Closing Corner to Secs. 30 & 31, T28S R3W. - East Endry. of T28S R4W. 83

Found - Scribed Stake at Cor.-Orig. 20", now 32" Fir N.49°E. 34.3 ft.,
shows good scar, I do not open. - Orig. 24", now down & partly rotted Fir,
S.80°E. 11.2 ft. I find good scribing on old stump section.

Set - Brass Cap alongside corner Stake Mkd: County Surveyor's

S30	T28S
Office, 1961	R4W S31 R3W CC

New BT: 12" R.Fir bears S. 8°E. 7.3 ft. scribed S31 T28S R3W CS BT.

Corner to Sections 25 and 36 only. 84

Found - Orig. 12", now 18" Laurel N.65°W. 27.7 ft. We open & find good
scribe marks. - Orig. S.W. BT., now stump, rotted.

Set - Brass Cap at Corner Mkd: County Surveyor's

S25	T28S
Office, 1961	R4W S36 R3W

New BT's: 20" R.Fir bears S.71°W. 21.0 ft. scribed T28S R4W S36 CS BT.
10" Cedar bears N.23°W. 25.0 ft. scribed T28S R4W S25 CS BT.

James W. Byron, Deputy County Surveyor
Dale McFarland
Jim Powell
August 1961
C. S. File No. 49/67