

Douglas County Surveyor's Record of  
Government Corners Renewed

T 28 T.S. R 4 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$  Section Corner to Sections 25 and 36. 86  
Found - Orig. 24", now 36" Fir S.15°W. 26.4 ft., shows good bark  
scribing "S" BT. - Orig. N.W. BT. not found.  
Set - Brass Cap at Corner Mkd: County Surveyor's  $\frac{1}{4}$  S25 T28S R4W  
Office, 1961 S36  
New BT's: 9" Cedar bears N.75°W. 21.2 ft. scribed  $\frac{1}{4}$  S25 CS BT.  
7" R.Fir bears S.31°E. 17.5 ft. scribed  $\frac{1}{4}$  S36 CS BT.

$\frac{1}{4}$  Corner to Sections 29 and 28. 87  
Found -  $\frac{3}{4}$ " I. P. at Corner & under N.S. Fence. <sup>REN #18</sup> Also find both BT's.  
as recorded by B.B.I. - N.W. BT., now down, shows scars.  
We do not open either BT.  
Set - Brass Cap alongside  $\frac{3}{4}$ " I. P. & Mkd: County Surveyor's Office,  
1961  $\frac{1}{4}$  S29/S28 T28S R4W.  
New BT: 14" R.Fir bears N.17°W. 96.6 ft. scribed  $\frac{1}{4}$  S29 CS BT.

$\frac{1}{4}$  Corner to Sections 29 and 20. 88  
Found - 1" I. Pipe at Corner & Both BT's. as recorded by Stewart.  
S.W. BT., now stump, shows scars. We open N.W. BT. & find  
good scribing "4". This BT. now snag. <sup>REN #16</sup>  
New BT's: 13" R.Fir bears S.62 $\frac{1}{2}$ °E. 19.3 ft. scribed  $\frac{1}{4}$  S29 CS BT.  
24" Laurel bears N.14°E. 28.6 ft. scribed  $\frac{1}{4}$  S20 CS BT.

Sec. Cor. to Secs. 30 & 31, T28-4W. & Secs. 25 & 36, T28-5W. 89  
Found - Orig. 9", now 30" Fir Stump S.70°W. 13.2 ft. We open & find  
good scribing "S3".  
Stump Section that checks record S.E. BT.  
Orig. N.W. & N.E. BT's. not found.  
Set - Brass Cap at Corner Mkd: County Surveyor's S25 | S30 T28S  
Office, 1961 R5W S36 | S31 R4W  
New BT's: 21" R.Fir bears N.37°W. 12.0 ft. scribed S25 T28S R5W CS BT.  
24" R.Fir bears N.17 $\frac{1}{2}$ °E. 49.7 ft. scribed S30 T28S R4W CS BT.  
18" Laurel bears S.17°W. 43.4 ft. scribed S36 T28SR5W CS BT.  
No trees near to S. E.

Sec. Cor. to Secs. 19 & 30, T28-4W. & Secs. 24 & 25, T28-5W. 90  
Found - Orig. 18", now down & mostly rotted Pine. We find good  
scribing "19 SR4W" on old section, BT. bears N.88°E. 39.6 ft.  
Orig. S.E. BT., down. No trace of N.W. Or S.W. BT's.  
 $\frac{1}{2}$ " I. P. 2 ft. North of Corner. N.S. Wire Fence is West of Cor.  
Set - Brass Cap at Corner Mkd: County Surveyor's S24 | S19 T28S  
Office, 1961 R5W S25 | S30 R4W  
New BT's: 16" Cedar bears S.24°E. 10.5 ft. scribed S30 T28S R4W CS BT.  
10" Pine bears N.54°E. 6.7 ft. scribed S19 T28S R4W CS BT.  
11" Cedar bears S.14°W. 11.2 ft. scribed S25 T28S R5W CS BT.  
10" Pine bears N.45°W. 22.7 ft. scribed S24 T28S R5W CS BT.

$\frac{1}{4}$  Corner to Section 19 and 20. 91  
Found - Orig. 24", now 36" Fir Stump N.20°W. 27.7 ft., shows good  
bark scribing "S". Also find Stump of Orig. N.E. BT.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1961  
 $\frac{1}{4}$  S19/S20 T28S R4W.  
New BT's: 14" Cedar bears S.28°W. 10.0 ft. scribed  $\frac{1}{4}$  S19 CS BT.  
9" Cedar bears N.65°E. 15.3 ft. scribed  $\frac{1}{4}$  S20 CS BT.

$\frac{1}{4}$  Corner to Sections 18 and 17. 92  
Found - Orig. 30", now 36" Fir N.80°E. 12.5 ft. We open & find  
good scribing. Also find bark scribing "B", near base.  
Orig. N.W. BT. not found.  
Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961  
 $\frac{1}{4}$  S18/S17 T28S R4W.  
New BT's: Rescribe O.E.T. 36" Fir N.80°E. 13.0 ft.  $\frac{1}{4}$  S17 CS BT.  
25" R.Fir bears N.31°W. 22.6 ft. scribed  $\frac{1}{4}$  S18 CS BT.

FD OK BY  
JOHNSTONE, 3/8/64  
M 100-36

FD OK BY  
JOHNSTONE, 3/8/64  
M 100-36

James W. Byron, Deputy County Surveyor  
Dale McFarland  
Jim Powell  
August & September 1961  
C. S. File No. 49/67