

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE., 51881

James W. Byron, Deputy County Surveyor
Dale McFarland
J. Powell
September 1961
C. S. File No. 49/67

Section Corner to Sections 8 - 9 - 17 - 16. 93
Found - No Original BT's. found of record. We do find, now 40" Fir properly bark scribed for corner tree.
Now down & partly rotted 18" Maple bears from corner..
Tree on which I believe I find faint scribe marks. No other BT's found for corner tree. We do find remains of rotten trees and low cut stumps in this area. I use bark scribed tree for corner tree as the scribing seems to be the right age for Orig. Also we find and & others have found errors at other corners in this township.
Set - Brass Cap at Base & on West Side of Corner Tree Mkd:
County Surveyor's

S8	S9
SI7	SI6

 T28S R4W
Office, 1961.
New BT's: 11" R.Fir bears N.43°W. 25.6 ft. scribed S 8 T28S R4W CS BT.
16" Hemlock bears S.52°W. 34.4 ft. scribed SI7 T28S R4W CS BT.
36" Cedar bears S.35°E. 37.8 ft. scribed SI6 T28S R4W CS BT.

$\frac{1}{4}$ Corner to Sec. 4, T28-4W. & Sec. 33, T27-4W. 94
Found - $\frac{3}{4}$ " I. P. at corner & under E W Fence. Find both BT's as recorded by Frear, 1918. We open N.W. BT. & find good scribe marks. Both BT's. now stumps. REN #2
New BT's: 8" R.Fir bears N.16 $\frac{1}{2}$ °E. 75.7 ft. scribed $\frac{1}{4}$ S33 CS BT.
9" Laurel bears N.23 $\frac{1}{2}$ °W. 45.5 scribed $\frac{1}{4}$ S33 CS BT.
No trees near to South.

Corner to Secs. 35 and 36, T27-4W., North Boundary of T28-4W. 95
Found - Orig. 6", now 30" R.Fir S.57°W, 21.8 ft. Orig. 24", now 30" R.Fir N.58°W. 27.7 ft., shows good bark scribing.
N.E. & S.E. BT's., now 30" Firs, show good bark scribing, now down slope about 50 ft. Stump holes check record bearings & distances.
N. E. BT. not Maple.
Set - Brass Cap at Corner Mkd: County Surveyor's

S35/S36	T27S
T28S	

Office, 1961
New BT: 16"R.Fir bears N.47°E. 57.3 ft. scribed S36 T27S R4W CS BT.

$\frac{1}{4}$ Corner to Sections 8 and 17. 96
Found - No Orig. BT's. of record. We do find R.Fir, now 58", bears N.40°W. 10.7 ft., shows bark scribing "BT $\frac{1}{4}$ S" (1/16" Rad.Scribe used)
R.Fir, now 40", bears S.19°W. 11.6 ft, shows good bark scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's

$\frac{1}{4}$ S 8	T28S R4W
SI7	

Office, 1961
New BT's: 9" R.Fir bears N.4 $\frac{1}{2}$ °E. 33.0 ft. scribed $\frac{1}{4}$ S8 CS BT.
10" R.Fir bears S.43°W. 57.0 ft. scribed $\frac{1}{4}$ SI7 CS BT.
Note - The Bark scribing on the found BT's. appears to be Byar's scribing as the trees were near to corner. We faced the scribing and set $\frac{1}{4}$ corner.

F. C. Frear
11/18/1921
Wit: Jones
Ingram
Weber

S. W. Cor. Sec. 32, T27-4W. Cor. No. 5, T27-4W. 97
I re-established from one old BT: viz. 18" Cedar bears S.28°E. 11.2 ft., marks plain & other trees all destroyed.
Set - 2" x 12" Wagon Boxing from which:
24" Cedar bears S.82°W. 28.3 feet. CORNER NO. 102

Frank Cain,
Co. Surv.
May
1915
Cor. No. 7, T29-4W.

Sec. Cor. to Secs. 32 & 33, T28-4W. & Secs. 4 & 5, T29-4W. 98
Renew from Orig. Trees. 2 Orig. trees do not check.
Set - Post from which Orig. Trees bear as follows:
A Fir 20" bears N.70°20'E. 80 lks.
A Fir 20" bears N.82°15'E. 55 lks.
A Fir 42" bears S.72°30'E. 125 lks.
A Fir 24" bears S.17°25'W. 138 lks. CORNER NO. 100