

Douglas County Surveyor's Record of
Government Corners Renewed

28

T. S.

5

R. W. W. M.

SEC. COR. 1 & 2, T 28 S, R 5 W, 35 & 36, T 27 S, R 5 W. 21
Reset from one old B. T. stump, marks plain, S $85\frac{1}{2}^{\circ}$ E, 450 lks.
I set $1\frac{1}{2}$ " x $1\frac{1}{2}$ " x 36" angle iron from which
9" Pine bears N 86° E, 185.3 ft. dist.
12" B. O. bears S $60\frac{1}{2}^{\circ}$ E, 59.5 ft. dist.
8" Y - W. O. bears S $34\frac{1}{2}^{\circ}$ W, 63.3 ft. dist.
5" W. O. bears N $75\frac{1}{2}^{\circ}$ W, 113.5 ft. dist.

Floyd C. Frear
Durwood Owens
Roy Hatfield
Witnesses
March 31, 1948

J. H. Markham, Jr.
Engineer

SEC, COR, 25-26-35-36 22
Corner determined from the remains of an old B.T.
Dead / Ash laying on the ground bears N 45° E 70.0 ft. dist.,
The old scribe is very plain.
Set an Iron post, 30" long $\frac{3}{4}$ " diam, 24" in ground,
from which
10" Fir bears S 38° E 33 ft., mkd S 36 2880 B.T.
18" B. Oak bears S 23° W 50 ft, mkd. S 35 2880 BT.
15" Cedar bears N 37° W 3.0 ft, mkd. S 26 2880 BT.
11" Fir bears N 73° E 18 ft. dist, mkd. S 25 2880BT.

9/21/49
C.S. 4/206

Claude Kerr
Logging Engineer
July, 1950

$\frac{1}{4}$ CORNER BETWEEN SECS. 23 and 24. 23
I found Fir BT bearing N 25° E for 16 lks.
I chopped down to old face and found the scribe markings reading
S E T. This BT is now a 24" solid gray about 12" high and is
just below a 10 ft. high rock bluff. The other BT is gone.
I put a new 4" x 4" fir limb post in for the corner and also put
my cruiser mark "K" on the BT.

SEC. COR. 13-14-23-24 24
Found only one remaining BT in good condition. This BT is the
48" Douglas Fir bearing N 19° E for 47 lks. from the corner. Scribe on
bark reads S13, T 28 S, R 5 W.
I reset this corner from the BT, using a 4" x 4" Ince's Cedar
Post and marking S13, S14, S23, and S24 with crayon on proper faces of the
post.

SEC. COR. 27 - 28 - 33 - 34 25
Determined by old B.T. *D.K.*
A B. Oak 28" diam. bears N 24° E 40.2 ft. dist, I rescribe S 27
A B. Oak stump bears S 30° W 25.0 ft. dist. *Ren #50*
At corner point set $\frac{3}{4}$ in. x 30 in. iron pipe 18 in. in ground, from
which
A W. Oak 6 in. diam. bears N 58° W 39.8 ft. dist. marked S 28,
2880, B.T.
A W. Oak 7 in. diam. bears S 10° W 34.0 ft. dist. marked S 33,
2880 B.T.
A W. Oak 6 in. diam. bears S 23° E, 21.0 ft. dist. marked S 34,
2880, B. T.

John H. Markham, Jr.
Engineer
Geo. Vaughn - Witness
August 10, 11, 18, 1950
C.S. 40/171

$\frac{1}{4}$ SEC. COR. 34 and 35 26
Determined from remains of old B.T.
A 48 in. Fir snag bears N 53° E 50.5 ft. dist., scribe legible.
A 45 in. Fir stump bears N 37° W 14.0 ft. dist.
At corner point set $\frac{3}{4}$ in. x 30 in. I.P. 15 in. in ground and made a
pile of rocks, from which
A W. Oak 10 in. diam. bears N 86° W 40.0 ft. dist. marked $\frac{1}{4}$ S,
S 34, 2880, B.T.
A Fir 7 in. diam. bears N 74° E, 13.0 ft. dist. marked $\frac{1}{4}$ S, S 35,
2880, B. T.

SEC. COR. 26-27-34-35 27
DETERMINED BY DOUBLE PROPORTIONATE MEASUREMENT
At corner point, set $\frac{3}{4}$ in. x 24 in. iron bar 12 in. in ground
from which,
A Pine 49 in. diam. bears N 88° W, 529.0 ft. marked S 27, 2880 B.T.
A W. Oak 10 in. diam. bears North 309.0 ft. marked X, 2880, B. T.
A W. Oak 13 in. diam. bears N 84° E, 215.0 ft. dist. marked S 26,
2880, B.T.
An Apple, $1\frac{1}{2}$ in. diam. bears S 67° W 9.0 ft. dist. *not marked*
Found a large iron wheel buried 16.0 ft. East of corner.

RENEWED, SEE CORNER NO. 119