

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 5 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97196

60

John H. Markham, Jr.
Wit. R.G. Boyd
For Stomar Lbr. Co.
Jan. 20, 1958
C. S. File No. 42/325

Section Corner to Sections 29, 30, 31, & 32.
As determined by O.B.T.s. :
13" W.O. bears N.16°W. 51.5 ft. dist. O.B.T. I rescribed S30 B.T.
30" W.O. windfall S.78°W. 17.2 ft. O.B.T. fd. scribe.
16" W.O. windfall S.78°E. 20.5 ft. O.B.T. fd. scribe.
At Corner Point Set 1"x30" I.P. from which:
11" La. bears N.57°E. 17.7 ft. dist. marked T28S R5W S29 BT.
6" La. bears S.61°E. 17.0 ft. dist. marked T28S R5W S32 BT.
26" La. bears S.51°W. 46.0 ft. dist. marked T28S R5W S31 BT.
Fence Corner bears N.45°E. 7.0 ft. dist., fences run South & East.
Creek bears West 170.0 ft.
Section Corner $\frac{31}{32}$ bears South 5254 ft.
 $\frac{615}{615}$

FD 5/91
D. BAKER
M113-32

Center Line County Road bears South 2055 ft.

~~WRONG TWP. & RANGE - SHOULD BE T28S, R.4W.~~

~~Section Corner to Sections 25, 26, 35, & 36.
(as det. by O.B.T's.)
20" Fir bears N.20°E. 45.5 ft. O.B.T.
24" Fir bears S.73°E. 15.2 ft. O.B.T.
Found bark scribe & remarked.
20" Fir bears S. 5°W. 25.7 ft. dist. O.B.T. - I bark scribed S35 BT.
At corner point set $\frac{3}{4}$ " x 20" I. R. from which:
5" Fir bears N.30°W. 2.0 ft. dist. mkd. S26 B.T.
18" Cedar " S.88°E. 39.0 ft. dist. mkd. S25 B.T.~~

John H. Markham, Jr.
Witness: L. B. Campbell
For S. Y. M. Logging Co.
Feb. 17, 1958
C. S. File No. 42/330

~~$\frac{1}{4}$ Section Corner to Sections 25 & 26, as det. by O.B.T.s.
40" Fir bears S.60°E. 23.1 ft. dist. O.B.T. fd. scribe & remarked (bark)
45" Fir windfall bears S.35°W. 21.8 ft. dist. O.B.T.
At Corner Point set 1" x 30" I. P. from which:
8" W. Fir bears S.60°W. 13.8 ft. dist. mkd. $\frac{1}{4}$ S26 B.T.
7" W. Fir bears N.29°W. 16.6 ft. dist. mkd. $\frac{1}{4}$ S26 B.T.
11" W. Fir bears N. 9°E. 18.4 ft. dist. mkd. $\frac{1}{4}$ S25 B.T.
Creek bears West 130.0 ft.
Road bears West 330.0 ft.~~

~~$\frac{1}{4}$ Section Corner to Sections 26 & 35, as det. by O.B.T.s.
17" Fir Stump(logged) bears N.45°E. 11.2 ft. dist. O.B.T. fd. scribe.
At Corner point found Old Cedar Tree down and Set 1 $\frac{1}{2}$ " x 22" I.P from which:
9" Cedar bears S. 6°W. 15.2 ft. dist. mkd. $\frac{1}{4}$ S35 B.T.
7" Fir bears S.77°W. 31.5 ft. dist. mkd. $\frac{1}{4}$ S35 B.T.
15" La. bears S.84°W. 51.0 ft. dist. mkd. $\frac{1}{4}$ S35 T28S B.T.~~

61

Section Corner to Sections 19, 20, 29, & 30.
Found - Black Oak, now 44" diam., N.65°W. 297.7 ft., showing scar.
chipped tree open & found reverse imprint of "BT" scribe.
A 30" Oak, dead & down, lies S.5 $\frac{1}{2}$ °W. approx. 414 ft. This
tree has been chopped open previously and I found reverse
imprint of scribing "R5W" on one piece.
No evidence found of other two BT's.
At Corner set Iron Pipe with Brass Cap stamped " S19 | S20 T28S R5W
County Surveyor's Office, 1958 S30 | S29
Blazed & Scribed 24" W. Oak N.47°E. 265.9 ft. "T28S R5W S20 CS BT"
No other trees near.

FD 5/91
D. BAKER
M113-32

James W. Byron, Deputy
M. Godfrey
S. Bilow
Feb. 1958
CS. File No. 49/64

Section Corner to Sections 20, 21, 28, & 29.
Found - Laurel Tree, now 40" diam., S.12°W. 98.5 ft. (not 109.6ft.)
which has been chopped open several years ago, showing
scribe marks on old face. I could make out an "8", also
"S 29". (This tree lies up a 30 degree slope from corner,
which could account for difference in distance.)
Fir Tree, now 32" diam., N.65 $\frac{1}{4}$ °W. 45.5 ft. We chopped this
tree open to expose part of old face & scribe marks "S20".
Ring count shows this to be an Orig. BT. - No trace of
other 2 BT's found.

62

(continued over)