

Douglas County Surveyor's Record of  
Government Corners Renewed

28

T. S.

5

R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97881

86

$\frac{1}{4}$  Corner to Sections 16 and 21.  
Found - Orig. 14", now 26" Down Oak S.69°E. 70.6 ft. We open &  
find good scribing " $\frac{1}{4}$ ". Also find down Stump Section  
that checks for N.E. BT.  
Note - E. W. Fence is 10 ft. North  
Set Brass Cap Mkd: County Surveyor's  $\frac{1}{4}$  S16 T28S R5W  
Office, 1961 S21  
New BT's: 15" R.Fir bears N.10°E. 34.3 ft. scribed  $\frac{1}{4}$  S16 CS BT.  
13" R.Fir bears S. 9°E. 29.3 ft. scribed  $\frac{1}{4}$  S21 CS BT.

87

Section Corner to Sections 17 - 18 - 19 - 20.  
Found -  $1\frac{1}{2}$ " I. Pipe at corner - BT's still standing but dead:  
24" W.Oak N.19°E. 11.2 ft. REN #2  
16" W.Oak S.56 $\frac{3}{4}$ °W. 49.8 ft. (fd. scribing)  
Other BT's. destroyed.  
Set - Brass Cap Mkd: County Surveyor's T28S R5W S18 | S17  
Office, 1961 S19 | S20  
New BT's: 8" W.Oak S.89°W. 54.3 ft. Mkd: T28S R5W S19 CS BT.  
11" W.Oak N.33°W. 93.4 ft. Mkd: T28S R5W S18 CS BT.  
7" W.Oak N.33°E. 98.0 ft. Mkd: T28S R5W S17 CS BT.  
9" W.Oak S.42°E. 92.0 ft. Mkd: T28S R5W S20 CS BT.  
Set Yellow tag on fence post along Roberts Creek Rd. approximately  
410 ft. N. of corner.

88

$\frac{1}{4}$  Corner to Sections 17 and 20.  
Found -  $1\frac{1}{2}$ " I.P. at corner 6" above gr. & both BT's. We open  
S.E. BT. and find good scribing. REN #14  
Rescribe S.E. Bearing Tree:  $\frac{1}{4}$  S20 CS BT.

89

Section Corner to Sections 17 - 16 - 20 - 21.  
Found - All BT's. & pointed Rock at corner. N.W. BT., now REN #15  
stump, we open near base & find scribe marks.  
7", now 14" R.Fir S.69 $\frac{1}{2}$ °W. 19.6 ft., not 25 $\frac{1}{2}$ °W. 19.6 ft.,  
shows good scars. The S.E. BT. now stump.  
The N.E. BT. now down.  
Set - Brass Cap alongside corner stone Mkd: County Surveyor's  
Office, 1961 S17 | S16 T28S R5W  
S20 | S21  
New BT's: 7" W.Oak bears N.47 $\frac{1}{2}$ °W. 43.3 ft. scribed S17 T28S R5W CS BT.  
15" Laurel bears S.29°E. 45.6 ft. scribed S21 T28SR5W CS BT.  
10" Laurel bears N.11°E. 15.8 ft. scribed S16 T28S R5W CS BT.  
Note - Corner at E. W. Fence.

90

$\frac{1}{4}$  Corner to Section 31, T28-5W. & Sec. 6, T29-5W.  
Found - 20", now S.29°E. 31.7 ft. We open & find good scribing.  
We do not find N.W. BT. Find  $\frac{3}{4}$ " I.P. in N/S fence bears N.65°E. 4.0 ft.  
Set - Brass Cap at corner Mkd: County Surveyor's  $\frac{1}{4}$  S 31 T28  
Office, 1961 S 6 T29  
New BT's: 16" Laurel bears S.13°W. 27.3 ft. scribed  $\frac{1}{4}$  S 6 CS BT.  
9" Laurel bears N.29 $\frac{1}{2}$ °E. 8.8 ft. scribed  $\frac{1}{4}$  S31 CS BT.  
Fences noted by sketch in file.

See F.B. 107  
pg. 36\*

91

Section Corner to Sections 10 - 11 - 15 - 14.  
Found - Orig. 18", now 24", W.Oak snag, N.22°W. 34.3 ft. Old  
face rotted out. Orig. 15", now 24" W.Oak S.44 $\frac{1}{2}$ °E. 40.3 ft.,  
we open & find good scribing. No other BT's. found.  
Set - Brass Cap Mkd: County Surveyor's S10 | S11 T28S R5W  
Office, 1961 S15 | S14  
New BT's: 7" W.Oak bears N.26°W. 45.7 ft. scribed S10 T28S R5W CS BT.  
12" W.Oak bears N.30°E. 34.6 ft. scribed S11 T28S R5W CS BT.  
42" B.Oak bears S.27°E. 77.7 ft. scribed S14 T28S R5W CS BT.  
No trees near to S.W.

James W. Byron, Deputy County Surveyor  
Dale McFarland  
J. Powell  
November 1961  
C.S. File No. 49/64

RENEWED