

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

99

North $\frac{1}{4}$ Corner to Section 3.
 Found - No. Orig. BT's. Do find Frear's, now broken 16" Ash
 Snag N. $34\frac{1}{2}^{\circ}$ E. 38.4 ft., shows good scribing " $\frac{1}{4}$ " in
 section on ground. *Rev. #33*
 We do not find I. Pipe set by Frear.
 Note - $\frac{1}{4}$ Cor. is 11 ft. South of East West Fence.
 Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961
 North $\frac{1}{4}$ S 3 CS BT. T27S, T28S R5W.
 New BT's: 30" W.Oak bears S. 3° E. 168.6 ft. scribed N $\frac{1}{4}$ S3 CS BT. (Scribed High)
 18" Ash bears S. 61° W. 36.4 ft. scribed N $\frac{1}{4}$ S3 CS BT.

100

$\frac{1}{4}$ Corner to Sections 3 and 10.
 Found - Orig. 18", now 30" B.Oak N. $84\frac{3}{4}^{\circ}$ W. 353.8 ft., shows parts of
 old scribe marks on old face, previously opened.
 Orig. 15", now 30" Oak, down & partly rotted S. $86\frac{1}{2}^{\circ}$ W. 371.6'.
 Note - Corner at West edge of North gate. Post in N. S. Fence Line.
 Set - Brass Cap Mkd: County Surveyor's $\frac{1}{4}$ S 3 T28S R5W
 Office, 1961 S10
 New BT's: 21" Office, 1961 S10
 21" W.Oak bears S. 70° W. 284.6 ft. scribed $\frac{1}{4}$ S10 CS BT.
 9" Oak, in cluster, N. 76° W. 290.8 ft. scribed $\frac{1}{4}$ S 3 CS BT.
(SEE ALSO 1886 VISIT IN VOL. 1 PG 70-71) 8/19/92

101

Section Corner to Sections 4 - 3 - 9 - 10.
 Found - All 4 Orig. BT's., all check O.K. Orig. SE. BT, now dead,
 We open & find good scribing "TS".
 Set - Brass Cap Mkd: County Surveyor's

S 4	S 3
S 9	S10

 T28S R5W
 Office, 1961
 New BT: 10" W.Oak bears S. 88° E. 23.5 ft. scribed S10 T28S R5W CS BT.

102

$\frac{1}{4}$ Section Corner to Sections 4 and 9.
 Found - Both Orig. BT's. Orig. 14", now 22" B.Oak S. $86\frac{1}{2}^{\circ}$ W. 127.4 ft.
 We open & find good scribing "S".
 Orig. 30", now W. Oak bears N. 19° W. 66.0 ft., shows
 good scar, I do not open.
 Set - Brass Cap at Corner Mkd: County Surveyor's

S4	$\frac{1}{4}$
S9	

 T28SR5W
 Office, 1961
 New BT: 18" W.Oak bears S. $55\frac{1}{4}^{\circ}$ W. 60.3 ft. scribed $\frac{1}{4}$ S9 CS BT.

103

Section Corner to Sections 5 - 4 - 8 - 9.
 Found - Orig. 15", now 30" B.Oak N. 25° W. 16.5 ft. We open &
 find good scribing "S".
 Orig. N.E. BT., down & rotted.
 Orig. S.E. & S.W. BT's., alive, but centers rotted, no scribing.
 Set - Brass Cap at Cor. Mkd: County Surveyor's

S5	S4
S8	S9

 T28BR5W
 Office, 1961
 New BT's: 14" W.Oak bears N. 66° W. 47.0 ft. scribed S 5 T28S R5W CS BT.
 13" R.Fir bears S. 12° W. 8.0 ft. scribed S8 T28S R5W CS BT.
 18" R.Fir bears S. $61\frac{1}{2}^{\circ}$ E. 34.4 ft. scribed S9 T28S R5W CS BT.
 9" W.Oak bears N. 17° E. 36.9 ft. scribed S4 CS BT.

105

Section Corner to Sections 5 - 6 - 7 - 8.
 Found - All 4 Orig. BT's. All show scars & check record.
 N.E. BT., now 18" B.Oak Snag. We open & find good
 scribe marks.
 Set - Brass Cap Mkd: County Surveyor's

S 6	S 5
S 7	S 8

 T28S R5W
 Office, 1961
 New BT: 16" B.Oak bears N. 46° E. 23.6 ft. scribed S5 T28S R5W CS BT.

James W. Byron, Deputy County Surveyor
 D. McFarland - J. Powell
 November 1961
 C. S. File No. 49/64