

Douglas County Surveyor's Record of
Government Corners Renewed

T 28 S. . . T. S. R 5 W. . . R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Sections 25 - 26 - 35 - 36. 111
 Found - 1" I. Pipe at corner & all Markham's BT's. REN #22
 Orig. S.W. & N.E. BT's, show scribing. 134
 B. O., now 20", S. 23°W. 55.8 ft., shows scribing on partly closed face.
 Rescribe Orig. 24", now 40" Laurel S. 20°E. 80.0 ft. S36 T28S R5W CS BT.
 New BT's: 16" Cedar bears N. 68°W. 10.8 ft. scribed S26 T28S R5W CS BT.
 12" R. Fir bears N. 36½°E. 49.3 ft. scribed S25 T28S R5W CS BT.
 Note - 1" I.P. at corner is O.K. Markham N.W. BT. is down. N.E & S.E. BT's. now snags. Do Not Set Brass Cap.



¼ Corner to Sections 8 and 9. 112
 Found - Both BT's which show good scars as recorded by B.B.I. REN #19
 We also find remains of large Oak that checks close for N.W. BT.
 Orig. record is 12" B.O. N. 19°W. 129 lks. & 18" W.O. N. 11°E. 161 lks. B.B.I. apparently transposed dist. & used 161 lks. for N.W. BT. per his notes & record.
 I relocate B.B.I. corner & set Brass Cap for True Corner N. 19°W. 21.1 ft.
 Mark Brass Cap ¼ S8/S9 T28S R5W County Surveyor's Office, 1961.
 New BT's: 8" W.Oak bears S. 84°W. 47.9 ft. scribed ¼ S 8 CS BT.
 11" W.Oak bears S. 80°E. 5.7 ft. scribed ¼ S 9 CS BT.
 Note - E. W. Fence is 8 ft. South of ¼ Corner.

Section Corner to Sections 13 - 14 - 23 - 24. 113
 Found - Orig. 48", now 48" Fir Snag, N. 19°E. 31.0 ft., shows good bark scribing "BT". We also find remains of S.W. & N.W. BT's. S.E. BT., now down. We find squared stake down at corner. REN #24
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1961

S14	S13
S23	S24

 New BT's: 9" Cedar bears S. 89°E. 17.6 ft. scribed S24 CS BT.
 26" R. Fir bears N. 88°E. 55.6 ft. scribed S13 T28S R5W CS BT.
 14" R. Fir bears N. 62°W. 36.7 ft. scribed S14 T28S R5W CS BT.
 8" Cedar bears S. 61°W. 28.3 ft. scribed S23 CS BT.

¼ Corner to Sections 23 and 24. 114
 Found - Orig. 12", now 24" Fir Snag N. 25°E. 10.6 ft., previously opened, shows good scribing "BT". N.W. BT. not found. See Ren #23
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1961 ¼ S23/S24 T28S R5W.
 New BT: 38" R. Fir bears S. 63°E. 78.3 ft., bark scribed, "BT" S24 CS BT.
 Set PK in Rock outcrop on top of point 6 ft. above ground bears N. 67°E. 5.6 ft.
 Brass Cap at foot of 10 ft. high Rock Bluff which is in last group of rock bluffs going north along section line.

¼ Corner to Sections 24 and 25. 115
 Found - Both Rocks of record. Rock East of Line thus: 
 High point 5' above ground made 2" + (chisled) on W. face 12" below top which bears N. 87°E. 200.0 ft. from ¼ corner. Rock S. 33°E. 290.4 ft. Thus: 
 Point 6' above gr. used to fix position of ¼ corner.
 Note - Corner is under old East West Fence.
 Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961 ¼

S24
S25

 T28S R5W
 No Trees Near:

James W. Byron, Deputy County Surveyor
 Dale McFarland
 J. Powell
 December 1961
 C. S. File No. 19/64

Fd. B.C. B/90
 M110-57

Fd. B.C. B/90
 M110-57