

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 28 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

~~1/4 Corner to Sec. 32, T28-5 and Sec. 5, T29-5W. <sup>18 28-6 & 29-6</sup>  
Found - Both BT's, as recorded by Cole, 1915. N.W. BT., now 30",  
Fir Stump, cut high, shows good bark scribing "1/4 S32".  
S. E. Maple BT., now down.  
Note - Corner is 6 ft. North of E. W. Fence.  
Set - Brass Cap at Cor. Mkd: County Surveyor's 1/4 S32 T~~

1/4 Corner to Sections 2 and 11. 124  
Found - No Original BT's.  
Note - See C. S. File No. 52/100 or M 23 - 5, 1/4 Corner  
Set by Proportionate Measurement.  
Set - Brass Cap at Corner Mkd: County Surveyor's 1/4 S 2 T28S  
Office, 1962 S11 R5W  
New BT's: 12" W.Oak bears S.87°W. 7.0 ft. scribed 1/4 S11 CS BT.  
10" B.Oak bears East 22.0 ft. scribed 1/4 S 2 CS BT.

(SEE ALSO 1886 VISIT, VOL 1 P 70-71) 8/19/92 125  
Section Corner to Sections 3 - 2 - 10 - 11.  
Found 1/4 Both Original BT's. Orig. 16", now 30", down & rotted  
Oak, S.9°W. We find good reverse scribing.  
Orig. 8", now 16" Oak Stump S.16°E., shows good reverse scribing.  
Note - See C. S. File No. 52/100  
Set - Brass Cap along North Side of Corner Fence Post & Mkd:  
County Surveyor's S 3 | S 2 T28S R5W.  
Office, 1962 S10 | S11  
No trees near.  
Set - Stone 12" x 10" base, 18" high, 6" out of ground. Top  
3" x 3". Chisled + on top, bears N.36°E. 4.3 ft.  
Stone, 10" x 6" Base, 18" High, 4" out of ground,  
wedge shape. Top 10" x 2". Chisled + on North  
Corner, bears N.53 1/2°W. 4.2 ft.

James W. Byron, Deputy  
For Douglas County  
Jan. 29, 1962  
C. S. File #52/100  
Map File M 23 - 5

Sec. Cor. to Secs. 2 & 3, T28-5W. & Secs. 34 & 35, T27-5W. 126  
Found - Orig. 26", now 46" B.Oak S.35°E. 54.1 ft. Open & fd. good scribing.  
Orig. 24", now lrg. Oak Stump S.46°W. 34.3 ft., center rotted.  
Orig. 20", now 40" B.Oak, down, N.5°W. 37.6 ft.  
Orig. 10", now 30" B.Oak N.62 1/2°E. 21.8 ft. I do not open.  
New BT's: 28" B.Oak S.28 1/2°W. 69.8 ft. scribed S 3 T28S R5W CS BT.  
46" B.Oak S.33 1/2°E. 55.0 ft. rescribed S 2 T28S R5W CS BT.  
11" W.Oak bears N. 2°W. 59.9 ft. scribed S34 T27S R5W CS BT.  
Set - Brass Cap at Cor. Mkd: County Surveyor's S34 | S35 T27S  
Office, 1959 S 3 | S 2 T28S  
Note - E. W. Bence 10 feet North.

James W. Byron, Deputy  
Mallo E. Godfrey  
Clate Putnam  
Dec. 18, 1959  
C. S. File No. 49/62

West 1/4 Sec. Cor. to Sec. 19, T28-4W. Twp. Line. Det. by O.B.T.  
13" W.O. Stump bears S. 2°E. 389.8 ft. O.B.T. 127  
26" W.O. bears N.15°E. 155.0 ft. Found Scribe. O.B.T.  
At Cor. Point Set 2" x 24" Iron Pipe in Mound of Stone from which:  
8" W.O. bears N.10°E. 146.5 ft. dist. mkd: 1/4 S19 B.T.  
6" W.O. bears N.43°E. 51.6 ft. dist. mkd: 1/4 S19 B.T.  
9" W.O. bears N.32°W. 50.0 ft. dist. mkd: 1/4 S24 B.T.  
20' x 20' x 6' High Rock Mound in Saddle of Main Ridge bears N.52°W. 245.0'.  
Note - The most southerly BT. should have been at 343.0 feet but  
I find it at 389.8 feet. There is a difference of 47.0 ft.  
Note - Also that Gov't. on re-chaining found S. 1/2 Mile 52.7 ft. long.

John H. Markham, Jr.  
For Stomar Lbr. Co.  
Oct. 21, 1957  
C. S. File No.  
42/316

1/4 Corner to Sections 11 and 12. 128  
Found - Brass Cap at Corner & S.W. BT. as recorded. Rev #59  
South East BT. now down.  
Set - 1/2" I. Rod under N. S. Fence & on line between Brass Cap  
& S.75°W. BT. 1/2" I. R. bears S.75°W. 41.3 ft. from 1/4 Cor.  
New BT: 28" W.Oak bears S.16°W. 342.3 feet scribed 1/4 S11 CS BT.

James W. Byron  
and Crew  
Nov. 15, 1962

C. S. File  
No. 49/64

FO. OK 2-92  
BY WHITSON  
M.P. 1962-004