

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 6 R. W. W. M.

Floyd Cole Deputy C.S.
C. F. Andrew Witness
O. A. Parker
Frank Roger April 5, 1915
Tog Rice Rock of Records #2
June 17, 1915 ps. 205
18¹/₂ ps. 17
18¹/₂ ps. 19

H. I. Epstein, C. Grear, B. Germond
Dep. Co. John Lambert Pierce
Brosi Thompson
Oct. 11, 1916

L. H. Smick Sur.
Glen Taylor Feb. 1920

Jesse W. Cole
Witnesses -
January 1921

N. W. COR. OF JOSEPH GAGE D.L.C. No. 51 see # 45 1
Set a stake, 59 lks. south of a rock set by G. E. Roberts
from stake.

A. B. Oak 18" in dia. N. 11°45' W. 196 lks.
A. B. Oak 9" in dia. N. 43° E. 369 lks.

S. W. CORNER OF JOHN DDX CL. NO. 49 2

Set Rock 7" x 7" x 10" with pieces cast iron binder frame.
6" below surface, from which

A. B. Oak 28" in dia. bears N. 44° W. 45 lks. 47
A. B. Oak 36" in dia. bears S. 68° E. 141 lks.

CORNER SOUTH SIDE OF SECTION 32. 3

Renew corner with Oak Post 4 x 4 x 42" form original

B.T.s and marked
A Fir 24" dia. bears N. 22° W. 8 ft. 102
Maple 7" dia. bears S. 21° E., 51 ft.

CORNER COMMON TO SECTIONS 28, 27, 21, and 22 in T. 28
S. R. 6 W. 4

Set in Blue River Basalt stone 4" x 7" x 16" marked 118

C.S. and a cross from the calls of two (2) original Gov-
ernment Bearing Trees and witnessed as follows

A Black Oak 26" dia. bears N. 83° W., 13.8 ft. (side measure)
A White Oak 28" dia. bears S. 2° W., 56.0 ft. (side measure)

CORNER COMMON TO SECTIONS 15, 16, 21 and 22. 5

I reestablished this corner from three old original
trees and set in 1 1/2" x 36" gal. iron pipe. No new trees
were marked. 126

CORNER SECTIONS 4, 5, 8, and 9. 6

Reset from old B.T.s by setting a 3/4" x 30" Iron Pipe
from which

A White Oak 14" dia. bears N. 48° W., 115 lks.
A Black Oak 14" dia. bears S. 48° E., 147 1/2 lks.

RENEWED 1/2 CORNER BETWEEN SECTIONS 25 and 26 FD 0540 1963-34 7

Renewed corner by setting a 4" x 4" x 40" Oak post on
line between section corners and at a distance between
foot of hill and creek proportions according to Government
field notes. Marked the following trees

Oak 9" dia. bears S. 25° E., 61.8 ft.
Oak 30" dia. bears S. 31° 15' E., 164.1 ft. 54

CORNER TO SECTIONS 25, 26, 35, and 36. 8

Renewed the corner from the original B.T.s which are
alive and standing. Set a 4" x 4" x 36" Oak Post. Trees
check closely with Government field notes 100

1/2 CORNER BETWEEN 25 and 36. 9

Renewed corner from original B.T.s set a 4" x 9" x 36"
Oak Post and a mound of rock. 91

CORNER TO SECTIONS 23, 24, 25, and 26. 10

Renewed from two original B.T.s which bear as follows.

Set Oak stake 4 x 4 x 40" from which
An Oak 30" dia. bears N. 60° 30' E., 168.3 ft. bears
old scribe 98

An Oak 30" dia. bears N. 48° 30' E., 112.2 ft. bears
old scribe

Marked new trees as follows

An Oak 6" dia. bears S. 19° W., 16.5 ft.

An Oak 38" dia. bears N. 31° 30' W., 56.4 ft. This

tree shows scar but could not be identified as an original
B.T. on account of rot.