

Douglas County Surveyor's Record of
Government Corners Renewed

28 T.S. 6 R. W. W. M.

COPIES CHAPMAN CO., EUGENE, ORE. 91000

30

SECTION CORNER COMMON TO SECTION 28, 29, 32 and 33.
Set stake 4" x 4" x 3' Cedar. Marked two new trees
Black Oak 8" dia. bears S. 42° W., 71 ft.
Black Oak 15" dia. bears S. 59° E., 81 ft.
Set Meander corner between section 32 and 29, on bank
of South Umpqua River from old 12" White Oak. Set a Ford
Axle for corner, old white oak was rotting so marked a new
B.T. which is
A Black Oak 40" dia. bears S. 6° E., 52 ft.

H.L. Eppstein
Wit.
James Wolford
W.L. Doland
May 2, 1926

A. Boyer
Wit.
N.E. Richardson
Wit.
H.L. Eppstein
Co. Sur.
Apr. 1931

30-A

Vol. 3 Pg. 268

1/4 CORNER BETWEEN 15 and 16.
Set a 1 1/2" Pipe in ground. Marked
6" Prune tree N. 63° 50' W., 48.0 ft.
8" Prune Tree S. 53° 28' E., 28.6 ft.

SEE COR. # 120 31
C.S. 14/63

1/4 CORNER BETWEEN 29 and 32.
Large Iron Bar in ground from which Old Maple nearly gone
bears S. 19° W., 69 lks. I also set a 5/8" x 24" Iron Bar at fence
corner S. 61 1/2° E., 49 ft.
A 5/8" x 24" Iron Bar S. 6 1/2° E., 42.0 ft.

SEE CORNER NO. 42

32

1/4 SECTION CORNER BETWEEN 28 and 29.
Trees are as follows
White Oak 28" dia. bears S. 65° E., 161 lks.
Black Oak bears S. 67° W., about 350 lks.

SEE CORNER NO. 44

33

CORNER BETWEEN SECTIONS 23 and 24.
Set 2" x 2" x 2' Fir stake from which
White Oak 8" dia. bears N. 12 1/2° E., 19 1/2 lks.
White Oak 9" dia. bears S. 13 1/2° E., 22 lks.

SEE CORNER NO. 50

34

CENTER SECTION OF 32.
Marked
White Oak 20" dia. bears S. 25 1/2° W., 153 ft.
White Oak 30" dia. bears N. 49 1/2° W., 156 ft.
Black Oak 18" dia. bears N. 6 1/2° E., 64 ft.
Cedar 12" dia. bears S. 23° E., 43 ft.

35

CORNER SECTIONS BETWEEN 16, 17, 20 and 21.
Set 1 x 48" Galvanized Iron Pipe and marked
Black Oak 48" dia. bears S. 11 1/2° E., 200 lks.

SEE CORNER NO. 122

36

1/4 CORNER BETWEEN SECTIONS 16 and 17.
Corner is a Large Boulder. Marked
Black Oak 24" dia. bears N. 78° W., 46 lks.

SEE CORNER NO. 123

37

STANDARD 1/4 SECTION CORNER ON NORTH BOUNDARY OF SECTION 1.
Position identified from an O.B.T. a 48" Black Oak S. 7° E.
6.33 lks. which is now a dead tree very sound and hard.
Chopped out old blaze and found original service marks in
excellent condition. Drove an Iron Rod 3/8" diam. and 48"
long in the ground for the corner, from which
An 8" Oak bears S. 67° W., approximately 20 ft.

SEE CORNER NO. 85

38

SECTION CORNER BETWEEN 5, 6, 7, and 8.
Position identified from O.B.T.s in S.W. and S.E. quadrants.
O.B.T. in N.E. quadrant gone. Set a 16" x 8" x 6" Rock for
corner and marked 2 new trees
12" White Oak S. 48 1/2° E., 93.5 ft.
8" White Oak N. 69 1/2° E., 202 ft.

SEE CORNER NO. 66

39

SECTION CORNER 20, 21, 28 and 29.
Set from N. line (N.W. corner) of Ruth Blair's home site as
originally given her by Sam Miller. Mr. Miller testified to
location of this corner so set 4 x 4 Cedar Post from which
Leaning Ash 30" dia. bears N. 10° W., 635.0 ft.
Ash 42" dia. bears N. 14 1/2° E., 564. ft.

40

Set 1 1/2" I. P. for cor. from O. B.T. which are Cottonwood not Ash
Distances and courses are correct except for N 14 1/2° E which is 560.4 ft.
Reset by A.R. Evans May 1949

Cor. Nos. Ed. 2/17/29
a.s. 2/2/61

Ben B. Irvin
Wit.
D.S.C.
A.L. Irvine
Wm. Kohlhagen
March 9, 1935

A. Boyer
Wit.
Clyde Heater
Wit.
Ralph Heater
Geo. Piper
Wit.
March 5, 1945

M. B. Germond
June 25, 1915

F. C. Frear
Jan. 11, 1918

July 16, 1922
F. C. Frear
Wit.
N. E. Richardson
Co. Rd. Mstr.
Wit.
N. E. Richardson
Wit.
H. L. Eppstein
Wit.
R. D. Wolford