

# County Surveyor's Record, Douglas County, Oregon

T 28 S, R 6 W, WM.

WEST COAST PRINTING & BINDING CO. PORTLAND 19770

**CHAINS**

**RE-RENEWED. SEE CORNER NO. 144 41**

1/4 Cor. BET. SECS. 27 & 28.

Found O. B. T. N 7° E 43 lks. slope dist. and stump of other also mound of rock. REN #12  
 Set a 1"x36" G. I. P. with a brass cap stamped County Surveyors Office S 27/S 28 from which  
 12" Fir bears N 66 1/2° W 16.5 ft.  
 20" Fir bears S 51 1/2° E 13.3 ft.

1/4 COR. BETWEEN 29 & 32 42

**RE-RENEWED. SEE CORNER NO. 111**

Both iron reference pins previously set have been destroyed and covered up. Old Original B. T., Maple which bears S 19° W, 69 lks., is still up and remarked. REN #32  
 I set a 3" x 3" x 4' angle iron, North 45 ft. from 1/4 corner.

1/4 COR. BET. 20-29 127 43

Reset from O. B. T.  
 14" Balm, Down, N 38° E 210.5 ft., set in 1922 G. Stewart REN #20  
 Set a 1/2" iron pipe 40" long and set new B. T.'s.  
 36" Balm bears N 57° W 222 ft. scribed 1/2 S 20 B T 1581  
 15" Cedar bears scribed 1/2 S 20 B.T 1581

1/4 Cor. Bet. Secs. 28 & 29 44

As this corner is recorded in the "corners renewed" As being N. 65° W 131' from a 28" W. Oak and 350' from a black Oak which bears S. 67° W. The figure 131 in the former tie is meant to be 1.31 chains. The bearing given is correct. REN #33  
 Set a 3/4" I. P. from which a : 140  
 48" W. Oak Bears N 67° 30' E 196' From the pipe to the center of the tree ? This distance was measured on the slope.

The N. W. Cor. Joseph Gage D. L. C. #51 See Ren #1 45  
 Set 1" iron pipe Brass Cap  
 Set from O. B. T. s in good condition

The N. E. Cor. Joseph Gage D. L. C. #51 46  
 Set from 1 O. B. T.  
 1" iron pipe set Brass Cap from which ;  
 8" oak bears S 56° W. 26.9 scribed cl 5 lcs B.T.  
 10" oak bears N 50° W. 25.3 scribed cl 49 cs B.T.  
 Lookinglass Creek N. about 40'

The S. W. Cor. John Cox claim No. 49 47  
 Set 1" iron pipe brass cap from fd. rock & binder frame REN #2

Corner of Sections 48  
 2-3-10-11  
 Reset  
 1/2" x 40" Reinforcing Bar 6" below below road from which a  
 1 1/2" x 36" axle bears South 10' also the Initial Point of Bournes Subdivision (S.E. Cor. Lot 30) bears N. 0° 13' E 50 feet

Cor. Secs. 13, 14, 23, 24. 49  
 Set 4 X 4 oak post 4' long, for cor.  
 Marked 3 New Bts., No B. TS. Fd.

**SEE CORNER NO. 53**

A 7" Oak, bears N 5° E, 16.8'  
 Scribed - nT 28 S, R 6 W, S13BT  
 A 6" Oak, bears N 76° W, 27.0'  
 Scribed - T 28 S, R 6 W, S14BT  
 A 3" Oak, bears S 5° E, 13.4'  
 Scribed S24BT

I started at the cor. for sections 23, 24, 25, & 26, chaining north on a random line. I checked on the ridge mentioned as 78 + 00 chs. north, and so chained 132' past it. No O. B. Ts. Could be found so I ran west and hit the line fence. As the original notes showed a ridge 10 chs. West I chained 660.0' back east from the ridge and hit 19.8 east of my point on the random line. The corner was set here.  
 We checked this corner futher by checking north to Roberts Creek which the notes call 6.00 chs. & checked closely .

N. E. Richardson-Surv.  
M. E. Godfrey-Wit  
L. S. Kershner-Wit.  
Maf. 1947

A. Boyer - Surv.  
Piper - Wit.  
F. C. Frear  
Durwood Owens  
March 31, 1948  
C. S. 46/151  
Oct. 1, 1949  
A. Boyer Surv.  
Don Smith Wit.  
July 19, 1952  
Drawer #41  
Envelope #59

Set by Ben. B. Irving  
Oct. 1952  
File #45  
Env. #95

Set by F. C. Frear  
Durwood Owens  
Sep. 20, 1952

Set By Claude Kerr.  
Dec. 1952  
Drawer 41  
Envelope 101

FD. B.C.  
12/16/52 D. BENTZ  
N. 98-7

SEE ALSO  
OLD REN. VOL. 1 P. 17