

Douglas County Surveyor's Record of  
Government Corners Renewed

28 T. S. 6 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97196

Section Corner to Sections 7, 8, 17, & 18. 74

Found - Three Orig. BT's:

Orig. 26", now 40" rotted Stump N.65°W. 37.0 ft., good scribing "BT".

Orig. 10", now 30" W. Oak N.42½°E. 36.3 ft., checks bearing & distance.

Orig. 12", now 30" W. Oak shows old scar. I do not open, S61°E. 8.0 ft.

No trace of Original S.W. BT.

Set Brass Cap at Corner Mkd: 

S7	S8
S18	S17

 T28S R6W County Surveyor's Office, 1958.

New BT's: 10" W. Oak bears S.61½°W. 71.5 ft. scribed S18 T28S R6W CS BT.

12" W. Oak bears N.63½°W. 11.9 ft. scribed S 7 T28S R6W CS BT.

Note: See Sketch in file for exact location of this corner.

¼ Section Corner to Sections 31 & 32. 75

Found - Orig. 20", now 30" B. Oak N.67°E. 70.0 ft. I open & find good scribing "S".

Find stump hole that checks bearing & distance for Orig. N.W. BT.

Set Brass Cap at Corner Mkd: ¼ S31/S32 T28S R6W County Surveyor's Office, 1958

New BT's: 14" R. Fir bears N.25°E. 50.9 ft. scribed ¼ S32 CS BT.

15" R. Fir bears N.29°W. 40.9 ft. scribed ¼ S31 CS BT.

¼ Section Corner to Section 7, T28S, R6W & Sec. 12, T28S, R7W. #167 76

Found - Both BT's. as recorded by Frear & both are now partly dead. Each checks for bearing & distance. The B. Oak to N. W. shows good scar. I do not open. SEE REN.# 99 T.28-7  
Also find gun barrel at Corner.

I do not set Brass Cap at Corner.

New BT's: 8" W. Oak bears S.54½°W. 34.0 ft. scribed ¼ S12 CS BT.

8" B. Oak bears S.46°E. 11.9 ft. scribed ¼ S 7 CS BT.

Section Corner to Secs. 7 & 18, T28S R6W, & Secs. 12 & 13, T28S R7W. 77

Found - Orig. 18", now down, 40" B.O. S.86¾°W., opened years ago, good reverse scribing found "S".

Orig. 15", now down, 40" B.O. (record N.52¼°W. 398.6 ft.) we find should be N.82¼°W. 398.6 ft., I open & find good scribing "BT".

Now 40" B.O., shows old face & good scar, center rotted, no scribing found. Checks bearing for N.E. BT. distance is 66 ft. greater than record. I believe this is the orig. N.E. BT.

Orig. BT. for N.E. Corner DLC #53, which I find to be 66' greater than record, also.

Set Brass Cap at Corner Mkd: 

R7W	S12	S 7	R6W
S13	S18		

 T28S County Surveyor's Office, 1958

New BT's: 14" W.O. bears N.39½°W. 50.0 ft. scribed S12 T28S R7W CS BT.

14" W.O. bears S.55½°W. 133.7 ft. scribed S13 T28S R7W CS BT.

14" W.O. bears N.14½°E. 88.0 ft. scribed S 7 T28S R6W CS BT.

Fence is North - No trees near to S. E.

¼ Section Corner to Section 19, T28S R6W, & Sec. 24, T28S R7W. 78

Found - Both Orig. BT's: Orig. 12", now 20" Oak Snag N.82°W. 53.5 ft., I open & find good scribing "S".

Orig. 24", now 40" Oak Snag S.88°E. 184.6 ft. shows good scar, I do not open.

Set Brass Cap at Corner Mkd: ¼ S24/S19 T28S County Surveyor's Office, 1958  
R7W R6W

New BT's: 16" Pine bears N.72°E. 1.7 ft. scribed ¼ S19 CS BT.

9" Laurel bears S.30½°W. 31.6 ft. scribed ¼ S24 CS BT.

James W. Byron, Deputy  
Milo Godfrey  
S. A. Billo  
November, 1958  
C. S. File No. 49/50

RE-NEWED SECTION CORNER