

Douglas County Surveyor's Record of
Government Corners Renewed

T 28 S T. S. R 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

1/4 Corner to Sections 23 and 26. 96

Found - Both BT's as recorded by Cole, 1921. The S.E. BT., REN #11
now stump shows good scars. N.E. BT. shows good
bark scribing "1/4 S BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's 1/4 S23 T28-6W
Office, 1961 S26

New BT: 10" W.Oak bears S.86°E. 28.0 ft. scribed 1/4 S23 CS BT.
Note - E. W. Fence 3 ft. South.

Section Corner to Sections 22 - 23 - 26 - 27. 97

Found - Orig. 6", now 12" W.Oak N.68°E. 25.1 ft. We open & find
good scribing "R6". Orig. 10", now 20" B.Oak S.2°W.
34.6 ft., not 36.7 ft. We do not open.

Orig. 12"; now 20" B.O. N.23°W. 14.5 ft. shows old face,
now rotted. Orig. S.E. BT. not found.

Find Gun Barrell at Corner.

Set - Brass Cap Mkd: County Surveyor's S22 / S23 T28SR6W
Office; 1961 S27 / S26

New BT's: R.Fir bears N.28 1/2°E. scribed S23 CS BT.

Rescribe Orig., now 20" B.O. N.23°W. 14.5 ft. mkd:
T28S R6W S22 CS BT.

13" R.Fir bears S.21°E. 46.8 ft. scribed S26 T28SR6W CS BT.

Note - Fences Thus:



Section Corner to Sections 23 - 24 - 25 - 26. 98

Found - 6", now 18" W.Oak S.19°W. 16.5 ft., shows good scribe Mks."S"
Orig. 30", now 38" B.Oak Snag N.31 1/2°W. 56.4 ft.

Orig. 14", now down & rotted Oak S.48 1/2°E. 112.0 ft. REN #10

Orig. 24", now 36" B.Oak N.60 1/2°E. 168.3 ft., shows good scar.

Set - Brass Cap Mkd: County Surveyor's S23 / S24 T28S R6W
Office, 1961 S26 / S25

New BT's: 11" Laurel bears N.48°E. 46.0 ft. scribed S24 T28S R6W CS BT.

8" W.Oak bears N.54°W. 32.0 ft. scribed S23 T28S R6W CS BT.

14" W.Oak bears S.9°E. 5.3 ft. scribed T28S R6W S25.

18" Dbl. W.Oak bears 19°W. 16.5 ft. scribed T28S R6W S26CS BT.

Note - 4 way Fence corner bears N.80°W. 15.0 ft.

1/4 Corner to Sections 35 and 36. 99

Found - Both BT's. recorded by Woods 1925. 12", now 18" B.Oak
N.56 1/2°E., not N.46°E. 54.1 ft, shows good scars. REN #28

12", now 16" B.Oak Stump N.40°15'W. 58.7 ft., shows good
scribing "B".

Find 1" x 18" I. Pipe at Corner, not on record.

Set - Brass Cap alongside I.P. & Mkd: County Surveyor's Office, 1961

New BT: 22" B.Oak bears N.25°W. 93.5 ft. scribed 1/4 S35 CS BT.

Section Corner to Sections 25 - 26 - 35 - 36. 100

Found - Orig. 8", now 26" B.Oak S.49°W. 37.6 ft., Open & fd. REN #8
Find Stump Hole that checks N.E. BT. N.W. & S.W. BT's. not fd.

Set - Brass Cap at Cor. Mkd: County Surveyor's S26 / S25 T28S R6W
Office, 1961 S35 / S36

New BT's: 13" W.Oak bears S.11°W. 33.3 ft. scribed S35 T28S R6W CSBT.

8" W.Oak bears S.13°E. 41.4 ft. scribed S36 CS BT.

15" W.Oak bears N.40 1/2°E. 30.2 ft. S25 T28S R6W CS BT.

11" B.Oak bears N.48 1/2°W. 46.6 ft. scribed S26 T28S R6W CSBT.

Section Cor. to Secs. 35 & 36, T28-6W. & Secs. 2 & 1, T29-6W. 101

Found - Orig. 12", now 18" W.Oak N.84 1/2°E. 64.7 ft. We open & fd. scrbing.

Orig. 24", now 40" B.Oak N.25 1/4°W. 225.7 ft., shows scar.

Orig. S.E. BT. not found.

Orig. 15", now 24" B.Oak S.21°W. 83.2 ft., shows scar. 147

Set Brass Cap at Cor. Mkd: County Surveyor's S35 / S36 T28S R6W
Office, 1961 S2 / S1 T29S

New BT's: Rescribe Orig. 12", now 18" W.Oak N.85 1/2°E. 64.7 ft. scribed S36T28S R6WCSBT

13" B.Oak bears N.2 1/2°W. 59.3 ft. scribed S35 T28S R6W CS BT

Rescribe Orig. 15", now 24" B.Oak S21°W. 83.2 ft. S2 T29SR6W CS BT.

10" Tr. Laurel bears S.1 1/2°E. 30.0 ft. scribed S1 CS BT.

James W. Byron, Deputy County Surveyor
Dale McFarland
John Powell
December 1961
C. S. File No. 49/139

RE-RENEWED. SEE CORNER NO. #159

FD. OAK 9/192 By BENNET
M/12-56