


Douglas County Surveyor's Record of  
Government Corners Renewed

T. 28 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881


Section Corner to Sections 21 - 22 - 27 - 28. 118  
Found - Rock & BT's. as recorded and at three-way Fence Corner.  
BT's. show good scribing. Ren #4  
New BT's: 9" W.Oak bears S.57°E. 35.5 ft. scribed S27 T28S R6W CS BT.  
8" Treble W. Oak N.83½°E. 43.3 ft. scribed S22 CS BT. 145

¼ Corner to Sections 8 and 9. 119  
Found - Orig. 10", now 28" B.O. S.47°E. 51.5 ft. We open & find good scribe marks.  
Orig. 14", now 30", B.Oak N.48°W. 7.3 ft., shows scar.  
Fence Corner Thus:   
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
½ S8/S9 T28S R6W  
New BT's: 32" B.Oak bears S.73°E. 88.6 ft. scribed ½ S 9 CS BT.  
10" W.Oak bears N.80°W. 25.5 ft. scribed ½ S 8 CS BT.

¼ Corner to Sections 16 and 15. 120  
Found - 1½" I.P. near top of bank on East Side of drainage ditch, from which top of 30" concrete pipe in East West Ditch bears S.82°W. 20.9 ft. - Ren #31  
No trees near for Bearing Trees.

Section Corner to Sections 15 - 16 - 21 - 22. 121  
Found - ½" I.P. at Corner and BT. as recorded by Byron, 1954. CS/45260 REN #5  
Set - Brass Cap alongside I.P. & Mkd: County Surveyor's Office, 1962  
S16 | S15  
S21 | S22 T28S R6W  
New BT: 9" W.Oak bears S.34°E. 56.4 ft. scribed S22 T28S R6W CS BT. 139

Section Corner to Sections 16 - 17 - 20 - 21. 122  
Found - Orig. 18", now 52" B.Oak N.67°E. 47.6 ft. previously opened, old face rotted. #153  
1" I.P. at corner & now 54" B.Oak S.11½°E. 132' ft., REN #36  
shows good scar. We do not open.  
Note - E. W. Fence 1.0 ft North.  
New BT's: rescribe, now 52" B.Oak N.69°E. 37.5 ft. S16 T28SR6WCSBT.  
12" B.Oak bears S.17°W. 54.8 ft. scribed S20T28SR6WCSBT.  
No trees near to N. W.

¼ Corner to Section 17 and 16. 123  
Found - Pointed Rock at Corner 6" above ground.  
Now B.Oak N.78°W. 30.4 ft., shows good scars, REN #37  
recorded by Frear.  
Fence Corner Thus:   
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's Office, 1962 ½ S17/S16 T28S R6W.  
New BT: 5" W.Oak bears N.5½°E. 13.0 ft. scribed ½ S16 CS BT.

Section Corner to Sections 17 - 18 - 19 - 20. 124  
Found - Rock Outcrops & Barn, as recorded by B.B.I., 1922. REN #21  
¾" I. R. bears N.44°W. 5.0 ft. May have been set for Cor.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
S18 | S17  
S19 | S20 T28SR6W  
Chisled 2" + on Rock Outcrop N.79°W. 54.0 ft. Also chisled B.O. on Rock just West of Corner.  
No trees near.

¼ Corner to Section 18 and 17. 125  
Found - 8" x 3" x 6" High Rock at Cor. & Both BT's. We open -  
Orig. 13", now 25" W.Oak N.85°E. 169.6 ft. & find good scribe.  
We chisel 1" + and ½ on top of Corner Rock. #182  
New BT: 13" W.Oak bears S.58°E. 60.4 ft. scribed ½ S17 CS BT.

James W. Byron, Deputy County Surveyor  
Dale McFarland and John Powell  
January 1962  
C. S. File No. 49/139

FD. 2/88  
M105-55  
G. BRUGHMAN

RE-RENEWED, SEE CORNER NO. #118

RE-RENEWED, SEE CORNER NO. #119

RE-RENEWED, SEE CORNER NO. #120

RE-RENEWED, SEE CORNER NO. #121

RE-RENEWED, SEE CORNER NO. #122

RE-RENEWED, SEE CORNER NO. #123

RE-RENEWED, SEE CORNER NO. #124

RE-RENEWED, SEE CORNER NO. #125