

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

143

1/4 Corner to Sec. 1, T28-6W. & Sec. 6, T28-5W.
SET - 3/4" Iron Rod for 1/4 Corner by Proportionate
Measurement.

New BT's: 10" Oak N. 41°30' E. 31.4 ft.
8" Oak S. 49° 30' W. 16.3 ft.

Feb. 7, 1967

Glenn S.
Baughman
2/7/67
Map File
M 32 - 58

144

1/4 Corner to Sections 27 and 28.

Found - 1947 C. S. Brass Cap & BT's. as recorded in Ren. #41.
Orig. Bearing Tree alive.

Richardson's BT's. are now Snag to N. W. & Stump to S.E.
with scribe visible.

Set - 6 ft. Steel fence post 2.0 ft. north of corner.

New BT's: 11" Laurel N. 3° E. 9.5 ft. mkd. 1/4 S27 CS BT.

13" Laurel S. 23° W. 41.4 ft. mkd. 1/4 S28 CS BT.

Note - This corner lies on steep north slope approx. 350 ft.
south of S.P. RR, course E. & W.

Vernon "Ray"
Tracy
J. Heritage &
E. West
9/1/67
C.S. File
No. 49/139

145

Section Corner to Sections 21 - 22 - ~~26~~²⁸ - 27.

Found - Stone 9x7x16 mkd. CS, See Ren. #118.

Stone found at a three-way fence corner.

26", now 28" B.Oak, N.83°W. 13.8 ft., shows face.

28", now 30" W.Oak, S. 2°W. 50.0 ft., shows scribing.

9", now 12" W.Oak, S.57°E. 35.5 ft., shows good face.

8", now 10" treble W.Oak, N.88°E. 43.3 ft., shows good face.

Set - Brass Cap at Sec. Cor. Mk'd: County Surveyor's T28S R6W

Office S 21 | S 22

1967 S 28 | S 27

Note - This corner lies 176.0 ft. west of Edgewood Street.

9/27/67

MICROFILM TO HERE 10/67

146

S. W. Corner D. L. C. No. 43.

Found - Corner Stone at DLC Corner marked with Cross (Stone Broken)

Removed remains of stone which is 28x21x13 & Set Brass Cap.


11", now 13" Pear, N.40 1/2°E. 47.3 ft., scribe visible. - Ren. #129

Set - Brass Cap at DLC Cor. Mk'd: County Surveyor's T28S R6W

Office S.W. Cor.

1968 D.L.C.#43

Bearing Trees O.K. No other trees available



6/27/68

147

Section Corner to Secs. 1 & 2, T29-6W. and Secs. 35 & 36, T28-6W.

At Corner Point, found I-5 high way fill. Brass Cap buried, Ren.#101.

from which: 18" W. O. N.85 E. 64.7 ft. O.B.T.

13" B.O1 N. 2 W. 59.3 ft. O.B.T.

All other trees missing.

6" Steel sign post set in concrete reads: Portland 187

bears S.60°30'W. Roseburg 10

102.0 ft., slope distance.

East end freeway culvert, 48"diam. bears S.30E 135.5 ft., slope dist.

John H.
MARKHAM, JR.
Sept. 1968
C.S. File
No. 51/292

148

Section Corner to Sections 9 - 10 - 15 - 16.

Found - Stone, See C. S. File 44/120 for Wenderoth's Corner.

Replaced with 5/8" Iron Rod.

Face of large rock bears N.12°30'E. 71.94 feet and East 47 feet,
measured on slope.

Aug. 1970

Don E.
Garrett
For McLaughlin
M 40 - 25

Fd. Cor. A Prt.
M 105-55
G. BAUGHMAN

RE-RENEWED, SEE CORNER NO. 151

SEPT. 68