

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 6 W. R.W.W.M.

KONE-CHAPMAN CO., EUGENE, ORE. 21881

149

John M. Powell & Crew
C. S. File No. 49/50

Section Corner to Sections 6 and 5 only, T28-6W.
Found - 1961 Co. Brass Cap, properly marked but disturbed from original position. See Ren. #83.
Orig. 24" W. Oak S. 61°W. 679.8 ft., tree opened before, scribe visible, "S" and other marks.
24" B. Oak S. 88°W. 497.0 ft., tree partially grown over, parts of scribing visible.
Set - New Brass Cap at Cor. with Steel Post alongside & old cap in hole, Corner set in Concrete Mkd: County Surveyor's T27S R6W S 32
Office, 1970 T28S S 6 | S 5

Note - Brass Cap 7" underground.
New BT: 24" B. Oak N. 20°W. 534.3 ft. scribed T27S R6W S CS BT.
Set - 5/8" I. Rod N. 20°W. 29.1 ft. in E-W fence line.

Dec. 1970

MARK 21

150

V. R. Tracy
J. Heritage
C.S. File 56/34
July 1973

Section Corner, Secs. 18 & 19; and Secs. 13 & 24 of T28-7.
Found - I. rod as set by single proportion, done by F.L. Ingram, P.L.S. 902 & recorded in C.S. File 56/14.
We remove I. rod and at the same location
Set - 1" I.P. and brass cap mkd. COUNTY SURVEYORS OFFICE T28S R7W 24 19 T28S R6W 1973 #158

New BT's - 48" Cottonwood, S. 46 1/2°W., 15.0 ft. mkd. T28S R7W S24 CS BT.
12" Maple, N. 34°W., 19.2 ft. mkd. T28S R7W S13 CS. BT.
18" Maple, N. 65°E., 143.6 ft. mkd. T28S R6W S18 CS BT.
20" Cottonwood, S. 13 1/2°E., 41.5 ft. mkd. T28S R6W S19 CS BT.
Note - We find no trace of original BT's.

July 1973

151

Larry E. Monreano
Pete Earle
C.S. 56/39
10/23/73

Sec. Corner, Secs. 35 & 36, T.28-6, Secs. 1 & 2, T.29-6
Found - 13" B. Oak, N. 3°W., 59.3 ft. scribed S35 T28S R6W CS BT.
18" (now 22" W. Oak, N. 85 1/2°E., 64.7 ft. scribed S36 T28S R6 CS BT. Ren. #147
6" Steel sign post set in concrete bears S. 62°W. East end of culvert 48" diam., bears S. 31°E.
Set - Brass cap at section corner mkd. COUNTY SURVEYORS T 28 S R 6 W OFFICE S35 S36 1973 S 2 S 1 T 29 S R 6 W

New BT's - 18" W. Oak, Bears S. 34 1/2°E., 196.4 ft. scribed T29S R6W S1 CS BT. Following are slope distances and angles taken to BT: 82' @ 19° = 77.5 ft.
100' @ 4°30' = 99.7'
1972' level = 19.2
196.4'

10/23/73

Don E. Garret
for Jimmie L. Johnson
March 1974
M 53-13A & B

1/4 Corner for Sec. 36 and Sec. 1, T29=6
Set - 1" Iron Pipe
BT's - 9" W. Oak, bears S. 13°45'W., 26.0 ft. scribed 1/4 S1 BT.
9" W. Oak, bears N. 17°E., 26.2 ft. scribed 1/4 S36 BT.

152

3/74

153

Karen Reed
Frank Silagy
Doug. Co. Surveyors Office
Feb. 12, 1979
C.S. 60/24

Section Corner for Secs. 16, 17 20 and 21.
Found - 1" I. pipe, 40" in the ground, 8" above ground as per Ren. #36.
An orig. 18" now 36" Black oak bears N. 67°E., 37.6 ft. with chopped out bark.
A 12" now 17" B. Oak bears S. 15°W., 54.8 ft. with healed double blaze. Ren. #122
A 48" now 56" Black Oak bears S. 11 1/2°E., 133 ft. with well healed blaze. Ren. #36.
Set - Referenced out I. Pipe and placed I. pipe with brass cap marked "Douglas Co. Surveyor" T28S S17 S16 S20 S21 R6W 1979" in position of pipe on west side of cap.
New Accessories:
5/8" I. Rod with alum. cap marked "B.O-" bears N. 32°W., 22.5 ft. set flush with ground.
No trees available in this quadrant.

2/12/79