

Douglas County Surveyor's Record of  
Government Corners Renewed

T 28 T. S. R 6 R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

154

1/4 Corner for Sections 4 and 9.

Found - Iron pipe with brass cap marked "Douglas County Surveyors Office" T28S R6W 1/4S 4 9. Cap 18" above ground - located at fence corner, with E-W fence and S. fence. Ren. #58

A 20" now 40" B. Oak bears S.54°E., 128.7 ft. with chopped out blaze visible scribing "1/4 BT". (Orig.)

A 2 ft. high 21" Fir stump bears S.7°E., 27.6 ft. No visible evidence of blaze or scribing. Could possibly be SE BT in Ren. #58.

A 17" now 22" D. Fir bears N.38°E., 37.0 ft. with well healed blaze.

No other original trees found.

New Accessories:

A 35" Pine bears N.62°W., 44.9 ft. scribed "1/4 S4 CS BT" in double blaze.

A 14" D. Fir bears S.34°W., 25.9 ft. scribed "1/4 S9 CS BT" in double blaze.

2/12/79

155

1/4 Corner for Secs. 9 and 16.

Set - Brass cap marked "T28S, R6W, W.M. 1/4 S9, S16 P.L.S. 430 1979"

From which:

18" White Oak BT marked by George Wenderoth in 1951 bears S.77°20'W., 122.9 ft. See Ren. #57

36" Black Oak BT marked by George Wenderoth in 1951 bears S.39°10'W., 233.1 ft.

7/23/79

Bruce Shaner of  
Shaner Engineering  
July 23, 1979  
C.S. 58/176

156

1/4 Corner for Sections 21 and 22

Set - Brass Cap  
Re-established 1/4 cor. from found orig. 1/2" iron pipe, lot corners on East line of Suksdorf Coos Junction Hill Tracts.

RE-RENEWED, SEE CORNER NO. #163

2/78

Glenn Baughman  
For: Fred Harder  
Feb. 1978  
C.S. M 65 - 59

Center

1/4 Corner for Section 8

Set - Marked a post (?) on all sides for center of Sec. 8

From which:

A laurel, 16" marked CS 1/16S bears S.73 W., 43 lks.

A laurel 24" marked CS 1/16S bears N.82 1/2 W., 41 lks.

A fir, 14" marked CS 1/16S bears N.23 E., 45 1/2 lks.

A fir 26" marked CS 1/16S bears S.88 3/4 E., 38 lks.

Note: Field book gives distances run that would bear out this being the center of the section but notes say scribing is 1/16S.

3/6/1914

157

NOTE: 157  
MAY OR  
PRESERVE SET  
CORNER  
D.P.

Old field book  
by ?  
For ?  
March 6, 1914  
F.B. 33 Pg. 42

158

Section corner for Secs. 18 and 19; and Secs. 23 & 24 of T.28-7

Found - A 1" diam. I.P. set firmly in the ground protruding 0.9 ft. above ground with brass cap stamped "County Surveyors Office T28S S13 S18 S24 S19 R7W R6W 1973" Ren. #150

A 48" diam. cottonwood bearing S.46 1/2°W., 15.0 ft. with visible scribe "28S 7W S2 S BT" in a partially healed single blaze.

A 12" diam., maple (easterly fork of double trunk tree) bears N.34°W., 19.2 ft. with visible scribe "28S R7W S13 CS BT" in double blaze.

An 18" diam. maple now 19" (southerly fork of a double trunk tree) bears N.65°E., 143.6 ft. dist. with visible scribe "T28S R6W S18 CS BT" in a single blaze.

A 20" cottonwood now 22" down tree with visible scribe "28 R" in a single blaze. The stump bears S.13 1/2°E., 41.5 ft. Place boat spike in stump at record bearing at a dist. of 40.9 ft.

No original BTs found.

Set - New corner set by calculating correct position from survey by F.L. Ingram, 1973, (C.S. 56/14). New position bears S.2°W., 29.8 ft. from found monument. Remove cap from 1973 monument, leave pipe in place and drive yellow plastic cap marked "Douglas County" into pipe.

#168

Karen Reed,  
Douglas County  
Surveyors Office  
Terrie Plouff  
May 11, 1982  
C.S. 61/36