

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 7 R. W. W. M.

F. C. Frear Dep. Co. Sur.
 Geo. Bacon
 E. F. Ollivant
 Jan. 5, 1913.
 Vol. 3 B. 78 & 36
 F.O. 73 Book 45 x 49-50
 C.S. 5/27
 R. C. Stewart Dep. Co. Sur.
 A. O. Strickland
 A. Dyser
 A. Erickson
 March 16, 1922
 G. G. Stewart Dep. Co. Sur.
 W. Johnson
 J. B. Howard
 C. M. Howard
 July 8, 1923
 G. G. Stewart Dep. Co. Sur.
 W. Johnson
 J. B. Howard
 C. M. Howard
 Oct. 19, 1922

- S.W. COR OF E. OLLIVANT D. L. C. 51 T. 28 S. R. 77. 1
 I renewed this corner from the original Bearing tree which was alive and standing and bearing scribble marks. 103
 I set a Rock. 18" x 18" x 4" for Cor. and marked a 50" Fir N. 20° W. 3.0 ft.
-
- CORNER BETWEEN SECTIONS 1 and 12. 2
 Renew corner from old Government B.T.s. Set in a 1 1/2" x 30" Iron Rod, from which
 A 30" Black Oak bears S. 13° E., 3.65 chs. 147
-
- SECTION CORNER COMMON TO SECTIONS 1, 6, 7, and 12. (T28-6) 3
 Renew from old B.T.s. Set in 12" x 12" x 18" sandstone, from which
 A White Oak 36" dia. bears N. 20 1/2° E., 2.28 chs.
 A White Oak 30" dia. bears N. 3 1/2° W., 1.78
 A Black Oak 24" dia. bears S. 22° W., 1.21
 A Black Oak 30" dia. bears S. 17 1/2° E., 1.65
See Ren #81 for T28-6 1958 Ren.
-
- CORNER OF SECTIONS 22, 23, 26, and 27. 4
 Renew from old B.T. Set in a 2" x 1" x 24" Iron Bar. 80
 Remark all old B.T.s except in section 23. This tree rotted.
-
- CORNER BETWEEN 3 and 10. 5
 Renew from stump of old B.T. Set sq. Cedar Post. Marked
 White Oak 8" dia. bears N. 85 1/2° W., 48.5 ft. 194
 Black Oak 18" dia. bears South 35.4 ft.
-
- CORNER BETWEEN 9 and 10. 6
 Renew from old B.T. one standing and one down. Set Iron Pipe. Marked
 Fir 10" dia. bears N. 51° E., 22.0 ft. 146
 Black Oak 18" dia. bears N. 80° W., 14.5 ft. O.E.T.
-
- CORNER BETWEEN 4 and 9. 7
 Renew from Original B.T. standing. Set gun barrel for corner. Marked
 Laurel 8" dia. bears N. 54° E., 29.0 ft. 160
 Pine 12" dia. bears S. 4° W., 56.0 ft.
-
- CORNER BETWEEN 4 and 3. 8
 Renew from stumps of Original B.T.s. Set Iron Bar for corner. Marked
 Fir 12" dia. bears S. 66° W., 50.0 ft. 142
 Black Oak 24" dia. bears N. 53° W., 163.0 ft.
-
- SECTION CORNER 3, 4, 9, and 10. 9
 Establish by intersection of lines between quarter corners. Set Iron Pipe. Marked
 Black Oak 16" dia. bears N. 63° E., 71.9 ft. 143
 Black Oak 10" dia. bears N. 11° W., 24.7 ft.
-
- CORNER SOUTH SIDE OF SECTION 31. 10
 Set Iron Pipe on true line between Section corners. (?) 46
 Cannot find O.B.T.s. Marked
 Ash 14" dia. bears N. 24° E., 26.5 ft. SEE COR # 46
 Ash 16" dia. bears N. 59° W., 54.2 ft.
-
- INNER "L" CORNER OF D.L.C. # 49 John Freeman Claim 11
 Set iron pipe from O.B.T. Marked
 Black Oak 10" dia. bears S. 83 1/2° E., 19.7 ft. 214
 White Oak 18" dia. bears N. 29° W., 35.6 ft. O.B.T.
- SEPT. 1968 - SEARCHED FOR, NOT FOUND V.R.T.