

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 7 R. W. W. M.

ADAM CHAPMAN CO., EBBING, ORE. 51028

✓ S.W. CORNER EXT. "L" OF CL. 49 12
Set pointed rock for corner from O.B.T. Marked
Fir 12" dia. bears N.75 $\frac{1}{2}$ °E., 33.0 ft.
Fir 12" dia. bears N.32°E., 62.5 ft. 116

✓ N.E. CORNER OF CL. 49 13
Set Iron Bar from remains of O.B.T. pointed out by
W.S. Johnson as O.B.T. 196
White Oak 12" dia. bears S.65°W., 15.0 ft.
Black Oak 6" dia. bears N.77 $\frac{1}{2}$ °E. 18.0 ft.

✓ S.E. CORNER OF CL. 49. 14
Set Iron pipe from O.B.T. Marked *SEPT. 1968 - SEARCHED FOR
NOT FOUND.
V.R.T.*
Fir 12" dia. bears S.41°W., 33.8 ft.
Black Oak 36" dia. bears N.35°W., 258.5 ft. O.B.T.

✓ N.W. CORNER OF CL. 49 15
Set Iron Pipe from O.B.T. badly rotted. Corner checks
with original line blazes. Marked 195
Black Oak 16" dia. bears N.86°E., 9.8 ft.
Black Oak 18" dia. bears N.8 $\frac{1}{2}$ °W., 18.5 ft.

✓ SECTION CORNER COMMON TO 23, 24, 25, and 26. 16
Set Iron Pipe from O.B.T.s Marked 193
Black Oak 8" dia. bears N.42°15'W., 31.2 ft.
White Oak 6" dia. bears S.54°W., 32.5 ft.
White Oak 8" dia. bears S.41°E., 27.5 ft.
White Oak 14" dia. bears N.80°E., 122.8 ft.

✓ CORNER BETWEEN 25 and 26. 17
Set Iron Pipe from O.B.T. Marked 192
Black Oak 18" dia. bears S.11°W., 32.5 ft.
White Oak 12" dia. bears N.34°E., 5.8 ft.

✓ SECTION CORNER BETWEEN 29, 30, 31 and 32. 18
Renewed from O.B.T.s and one stump. Set Iron Pipe. 87
Marked
White Oak 30" dia. bears N.6°E., 26.3 ft.
Black Oak 36" dia. bears N.19°W., 9.8 ft.
Black Oak 36" dia. bears S.30°E., 39.8 ft.
Pine 24" dia. bears S.46°W., 60.3 ft.

✓ CORNER BETWEEN 29 and 30 32 *Corrected 10-25-50* 19
Renewed from two O.B.T.s which do not agree with Government
Notes: Use accepted location for corner. Drove Iron Pipe
and marked 212
White Oak 30" dia. bears S.38 $\frac{1}{2}$ °W., 47.8 ft.
White Oak 30" dia. bears N.73°E., 65.8 ft.

✓ CORNER BETWEEN 28 and 29. 20
B.T.s gone. Set from South line of Claim 55 as per
Government Notes. Set Iron Pipe for corner. Marked 88
Black Oak 20" dia. bears S.84°E., 93.0 ft.
Fir 8" dia. bears N.36°W., 47.5 ft.

✓ SECTION CORNER 20, 21, 28 and 29. 21
Reset from three O.B.T.s and one stump. Trees open and
decaying. Set Iron Pipe and marked
Black Oak 24" dia. bears N.85 $\frac{1}{2}$ °E., 31.5 ft.
Black Oak 48" dia. bears N.12°W., 214.5 ft.
Black Oak 16" dia. bears S.79°W., 28.0 ft.
Black Oak 24" dia. bears S.39°E., 38.0 ft.

SEE CORNER NO. 63

G. G. Stewart Deputy
Witnesses
C. Crocker
V. Johnson
October 1922

G. G. Stewart Deputy
September 1922
Witnesses
C. Crocker
J. H. Porter
Vol. 3 R. 126